Introduction to



Claire Dross Yannick Moy





Introduction to SPARK Release 2024-04

Claire Dross and Yannick Moy

Apr 27, 2024

CONTENTS:

1	SPA	RK Overview 3
	1.1	What is it?
	1.2	What do the tools do?
	1.3	Key Tools
	1.4	A trivial example
	1.5	The Programming Language
	1.6	Limitations
		1.6.1 No side-effects in expressions
		1.6.2 No aliasing of names
	1.7	Designating SPARK Code
	1.8	Code Examples / Pitfalls
		1.8.1 Example #1
		1.8.2 Example #2
		1.8.3 Example #3
		1.8.4 Example #4
		1.8.5 Example #5
		1.8.6 Example #6
		1.8.7 Example #7
		1.8.8 Example #8
		1.8.9 Example #9
		1.8.10 Example #10
2	Flov	v Analysis 21
	2.1	What does flow analysis do?
	2.2	Errors Detected
		2.2.1 Uninitialized Variables
		2.2.1Uninitialized Variables212.2.2Ineffective Statements22
		2.2.1Uninitialized Variables212.2.2Ineffective Statements222.2.3Incorrect Parameter Mode24
	2.3	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.2.3Incorrect Parameter Mode24Additional Verifications25
	2.3	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.2.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts25
	2.3	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26
	2.3 2.4	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.2.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26Shortcomings28
	2.3 2.4	2.2.1 Uninitialized Variables212.2.2 Ineffective Statements222.2.3 Incorrect Parameter Mode24Additional Verifications252.3.1 Global Contracts252.3.2 Depends Contracts26Shortcomings282.4.1 Modularity28
	2.3 2.4	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26Shortcomings282.4.1Modularity282.4.2Composite Types29
	2.3 2.4	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.2.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26Shortcomings282.4.1Modularity282.4.2Composite Types292.4.3Value Dependency31
	2.3 2.4	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26Shortcomings282.4.1Modularity282.4.2Composite Types292.4.3Value Dependency312.4.4Contract Computation33
	2.32.42.5	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26Shortcomings282.4.1Modularity282.4.2Composite Types292.4.3Value Dependency312.4.4Contract Computation33Code Examples / Pitfalls33
	2.3 2.4 2.5	2.2.1Uninitialized Variables212.2.2Ineffective Statements222.3Incorrect Parameter Mode24Additional Verifications252.3.1Global Contracts252.3.2Depends Contracts26Shortcomings282.4.1Modularity282.4.2Composite Types292.4.3Value Dependency312.4.4Contract Computation33Code Examples / Pitfalls332.5.1Example #133
	2.32.42.5	2.2.1 Uninitialized Variables 21 2.2.2 Ineffective Statements 22 2.3.1 Incorrect Parameter Mode 24 Additional Verifications 25 2.3.1 Global Contracts 25 2.3.2 Depends Contracts 26 Shortcomings 28 2.4.1 Modularity 28 2.4.2 Composite Types 29 2.4.3 Value Dependency 31 2.4.4 Contract Computation 33 Code Examples / Pitfalls 33 2.5.1 Example #1 33 2.5.2 Example #2 34
	2.32.42.5	2.2.1 Uninitialized Variables 21 2.2.2 Ineffective Statements 22 2.3.1 Incorrect Parameter Mode 24 Additional Verifications 25 2.3.1 Global Contracts 25 2.3.2 Depends Contracts 26 Shortcomings 28 2.4.1 Modularity 28 2.4.2 Composite Types 29 2.4.3 Value Dependency 31 2.4.4 Contract Computation 33 Code Examples / Pitfalls 33 2.5.1 Example #1 33 2.5.2 Example #2 34 2.5.3 Example #3 35
	2.3 2.4 2.5	2.2.1 Uninitialized Variables 21 2.2.2 Ineffective Statements 22 2.3 Incorrect Parameter Mode 24 Additional Verifications 25 2.3.1 Global Contracts 25 2.3.2 Depends Contracts 26 Shortcomings 28 2.4.1 Modularity 28 2.4.2 Composite Types 29 2.4.3 Value Dependency 31 2.4.4 Contract Computation 33 Code Examples / Pitfalls 33 2.5.1 Example #1 33 2.5.2 Example #3 35 2.5.4 Example #4 36
	 2.3 2.4 2.5 	2.2.1 Uninitialized Variables 21 2.2.2 Ineffective Statements 22 2.3 Incorrect Parameter Mode 24 Additional Verifications 25 2.3.1 Global Contracts 25 2.3.2 Depends Contracts 26 Shortcomings 28 2.4.1 Modularity 28 2.4.2 Composite Types 29 2.4.3 Value Dependency 31 2.4.4 Contract Computation 33 Code Examples / Pitfalls 33 2.5.1 Example #1 33 2.5.2 Example #3 35 2.5.4 Example #4 36 2.5.5 Example #5 38
	 2.3 2.4 2.5 	2.2.1 Uninitialized Variables 21 2.2.2 Ineffective Statements 22 2.3 Incorrect Parameter Mode 24 Additional Verifications 25 2.3.1 Global Contracts 25 2.3.2 Depends Contracts 26 Shortcomings 28 2.4.1 Modularity 28 2.4.2 Composite Types 29 2.4.3 Value Dependency 31 2.4.4 Contract Computation 33 Code Examples / Pitfalls 33 2.5.1 Example #1 33 2.5.2 Example #4 36 2.5.3 Example #4 36 2.5.4 Example #5 38 2.5.6 Example #6 39

		2.5.8 Example #8	L
		2.5.9 Example #9 43	3
		2.5.10 Example #10	ł
3	Proc	of of Program Integrity 47	,
	3.1	Runtime Errors	7
	3.2	Modularity)
		3.2.1 Exceptions)
	3.3	Contracts	2
		3.3.1 Executable Semantics	ł
		3.3.2 Additional Assertions and Contracts	5
	3.4	Debugging Failed Proof Attempts 56	5
		3.4.1 Debugging Errors in Code or Specification	7
		3.4.2 Debugging Cases where more Information is Required 59)
		3.4.3 Debugging Prover Limitations)
	3.5	Code Examples / Pitfalls	2
		3.5.1 Example #1 62	2
		3.5.2 Example #2	ł
		3.5.3 Example #3	5
		3.5.4 Example #4	Ś
		3.5.5 Example #5	/
		3.5.6 Example #6	3
		3.5.7 Example #7)
		3.5.8 Example #8)
		3.5.9 Example #9	L
		3.5.10 Example #10	<i>'</i>
4	Stat	e Abstraction 73	3
	4 1	What's an Abstraction? 73	Ż
	4.2	Why is Abstraction Useful?	1
	4.3	Abstraction of a Package's State	5
	4.4	Declaring a State Abstraction	5
	4.5	Refining an Abstract State	5
	4.6	Representing Private Variables	1
	4.7	Additional State	3
		4.7.1 Nested Packages	3
		4.7.2 Constants that Depend on Variables)
	4.8	Subprogram Contracts	L
		4.8.1 Global and Depends	L
		4.8.2 Preconditions and Postconditions	3
	4.9	Initialization of Local Variables	ີ່ວ
	4.10	Code Examples / Pitfalls	3
		4.10.1 Example #1	3
		4.10.2 Example #2)
		4.10.3 Example #3)
		4.10.4 Example #4	L
		4.10.5 Example #5	2
		4.10.6 Example #6	3
		4.10.7 Example # /	ł
		4.10.8 Example #8)
		4.10.9 Example #9	5
		4.10.10Example #10	,
5	Proc	of of Functional Correctness 101	
	5 1	Bevond Program Integrity	1
		I Deren in the second sec	1
	5.2	Advanced Contracts	Δ
	5.2	Advanced Contracts	45
	5.2	Advanced Contracts 10 5.2.1 Ghost Code 10 5.2.2 Ghost Functions 10	4 5 8

5.3	Guide	Proof				 												112
	5.3.1	Local Ghost Va	riat	ble	S	 											 	112
	5.3.2	Ghost Procedu	res			 											 	114
	5.3.3	Handling of Lo	ops			 												115
	5.3.4	Loop Invariant	s.			 												117
5.4	Code E	Examples / Pitfa	lls			 											 	122
	5.4.1	Example #1.				 											 	122
	5.4.2	Example #2.				 											 	124
	5.4.3	Example #3.				 											 	125
	5.4.4	Example #4.				 											 	126
	5.4.5	Example #5.				 											 	128
	5.4.6	Example #6.				 											 	129
	5.4.7	Example #7.				 											 	130
	5.4.8	Example #8.				 											 	131
	5.4.9	Example #9.				 											 	133
	5.4.10	Example #10				 											 	134

Copyright © 2018 - 2022, AdaCore

This book is published under a CC BY-SA license, which means that you can copy, redistribute, remix, transform, and build upon the content for any purpose, even commercially, as long as you give appropriate credit, provide a link to the license, and indicate if changes were made. If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. You can find license details on this page¹



This tutorial is an interactive introduction to the SPARK programming language and its formal verification tools. You will learn the difference between Ada and SPARK and how to use the various analysis tools that come with SPARK.

This document was prepared by Claire Dross and Yannick Moy.

Note: The code examples in this course use an 80-column limit, which is a typical limit for Ada code. Note that, on devices with a small screen size, some code examples might be difficult to read.

Note: Each code example from this book has an associated "code block metadata", which contains the name of the "project" and an MD5 hash value. This information is used to identify a single code example.

You can find all code examples in a zip file, which you can download from the learn website². The directory structure in the zip file is based on the code block metadata. For example, if you're searching for a code example with this metadata:

- Project: Courses.Intro_To_Ada.Imperative_Language.Greet
- MD5: cba89a34b87c9dfa71533d982d05e6ab

you will find it in this directory:

projects/Courses/Intro_To_Ada/Imperative_Language/Greet/ cba89a34b87c9dfa71533d982d05e6ab/

In order to use this code example, just follow these steps:

- 1. Unpack the zip file;
- 2. Go to target directory;
- 3. Start GNAT Studio on this directory;
- 4. Build (or compile) the project;
- 5. Run the application (if a main procedure is available in the project).

¹ http://creativecommons.org/licenses/by-sa/4.0

² https://learn.adacore.com/zip/learning-ada_code.zip

CHAPTER ONE

SPARK OVERVIEW

This tutorial is an introduction to the SPARK programming language and its formal verification tools. You need not know any specific programming language (although going over the Introduction to Ada course first may help) or have experience in formal verification.

1.1 What is it?

SPARK refers to two different things:

- a programming language targeted at functional specification and static verification, and
- a set of development and verification tools for that language.

The SPARK language is based on a subset of the Ada language. Ada is particularly well suited to formal verification since it was designed for critical software development. SPARK builds on that foundation.



Version 2012 of Ada introduced the use of *aspects*, which can be used for subprogram contracts, and version 2014 of SPARK added its own aspects to further aid static analysis.

1.2 What do the tools do?

We start by reviewing static verification of programs, which is verification of the source code performed without compiling or executing it. Verification uses tools that perform static analysis. These can take various forms. They include tools that check types and enforce visibility rules, such as the compiler, in addition to those that perform more complex reasoning, such as abstract interpretation, as done by a tool like CodePeer³ from AdaCore. The tools that come with SPARK perform two different forms of static analysis:

- *flow analysis* is the fastest form of analysis. It checks initializations of variables and looks at data dependencies between inputs and outputs of subprograms. It can also find unused assignments and unmodified variables.
- *proof* checks for the absence of runtime errors as well as the conformance of the program with its specifications.

1.3 Key Tools

The tool for formal verification of the SPARK language is called *GNATprove*. It checks for conformance with the SPARK subset and performs flow analysis and proof of the source code. Several other tools support the SPARK language, including both the GNAT compiler⁴ and the GNAT Studio integrated development environment⁵.

1.4 A trivial example

We start with a simple example of a subprogram in Ada that uses SPARK aspects to specify verifiable subprogram contracts. The subprogram, called Increment, adds 1 to the value of its parameter X:

Listing 1: increment.ads

```
1 procedure Increment
2 (X : in out Integer)
3 with
4 Global => null,
5 Depends => (X => X),
6 Pre => X < Integer'Last,
7 Post => X = X'Old + 1;
```

Listing 2: increment.adb

```
procedure Increment
(X : in out Integer)
is
4 begin
5 X := X + 1;
6 end Increment;
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Trivial_Example
MD5: ce28b1facb44917b6cc208639c187064

³ https://www.adacore.com/codepeer

⁴ https://www.adacore.com/gnatpro

⁵ https://www.adacore.com/gnatpro/toolsuite/gps

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... increment.adb:5:10: info: overflow check proved increment.ads:4:03: info: data dependencies proved increment.ads:5:03: info: flow dependencies proved increment.ads:7:14: info: postcondition proved increment.ads:7:24: info: overflow check proved

The contracts are written using the Ada *aspect* feature and those shown specify several properties of this subprogram:

- The SPARK Global aspect says that Increment does not read or write any global variables.
- The SPARK Depend aspect is especially interesting for security: it says that the value of the parameter X after the call depends only on the (previous) value of X.
- The Pre and Post aspects of Ada specify functional properties of Increment:
 - Increment is only allowed to be called if the value of X prior to the call is less than Integer'Last. This ensures that the addition operation performed in the subprogram body doesn't overflow.
 - Increment does indeed perform an increment of X: the value of X after a call is one greater than its value before the call.

GNATprove can verify all of these contracts. In addition, it verifies that no error can be raised at runtime when executing Increment's body.

1.5 The Programming Language

It's important to understand why there are differences between the SPARK and Ada languages. The aim when designing the SPARK subset of Ada was to create the largest possible subset of Ada that was still amenable to simple specification and sound verification.

The most notable restrictions from Ada are related to exceptions and access types, both of which are known to considerably increase the amount of user-written annotations required for full support. Backwards goto statements and controlled types are also not supported since they introduce non-trivial control flow. The two remaining restrictions relate to side-effects in expressions and aliasing of names, which we now cover in more detail.

1.6 Limitations

1.6.1 No side-effects in expressions

The SPARK language doesn't allow side-effects in expressions. In other words, evaluating a SPARK expression must not update any object. This limitation is necessary to avoid unpredictable behavior that depends on order of evaluation, parameter passing mechanisms, or compiler optimizations. The expression for Dummy below is non-deterministic due to the order in which the two calls to F are evaluated. It's therefore not legal SPARK. Listing 3: show_illegal_ada_code.adb

```
procedure Show Illegal Ada Code is
1
2
      function F (X : in out Integer) return Integer is
3
          Tmp : constant Integer := X;
4
      begin
5
         X := X + 1;
6
         return Tmp;
7
      end F;
8
9
      Dummy : Integer := 0;
10
11
   begin
12
      Dummy := F (Dummy) - F (Dummy); -- ??
13
   end Show Illegal Ada Code;
14
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Illegal_Ada_Code
MD5: a5cbf1824526857da94791ac1790200c

Build output

Prover output

In fact, the code above is not even legal Ada, so the same error is generated by the GNAT compiler. But SPARK goes further and GNATprove also produces an error for the following equivalent code that is accepted by the Ada compiler:

Listing 4: show_illegal_spark_code.adb

```
procedure Show Illegal SPARK Code is
1
2
      Dummy : Integer := 0;
3
4
      function F return Integer is
5
         Tmp : constant Integer := Dummy;
6
      begin
7
          Dummy := Dummy + 1;
8
          return Tmp;
9
      end F;
10
11
   begin
12
      Dummy := F - F; -- ??
13
  end Show_Illegal_SPARK_Code;
14
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Overview.Illegal_SPARK_Code
MD5: e747edb6ee147adb7fba97c9e7c8d5ef
```

The SPARK languages enforces the lack of side-effects in expressions by forbidding sideeffects in functions, which include modifications to either parameters or global variables. As a consequence, SPARK forbids functions with **out** or **in out** parameters in addition to functions modifying a global variable. Function F below is illegal in SPARK, while Function Incr might be legal if it doesn't modify any global variables and function Incr_And_Log might be illegal if it modifies global variables to perform logging.

```
function F (X : in out Integer) return Integer; -- Illegal
function Incr (X : Integer) return Integer; -- OK?
function Incr_And_Log (X : Integer) return Integer; -- OK?
```

In most cases, you can easily replace these functions by procedures with an **out** parameter that returns the computed value.

When it has access to function bodies, GNATprove verifies that those functions are indeed free from side-effects. Here for example, the two functions Incr and Incr_And_Log have the same signature, but only Incr is legal in SPARK. Incr_And_Log isn't: it attempts to update the global variable Call_Count.

Listing 5: side_effects.ads

```
package Side_Effects is
function Incr (X : Integer) return Integer; -- OK?
function Incr_And_Log (X : Integer) return Integer; -- OK?
end Side_Effects;
```

Listing 6: side effects.adb

```
package body Side Effects is
1
2
      function Incr (X : Integer) return Integer
3
      is (X + 1); -- OK
4
5
      Call_Count : Natural := 0;
6
7
      function Incr_And_Log (X : Integer) return Integer is
8
      begin
9
          Call Count := Call Count + 1; -- Illegal
10
          return X + 1;
11
      end Incr And Log;
12
13
  end Side_Effects;
14
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Overview.Side_Effects
MD5: 1b555e4b7bb519eea4df718a9356a2ed
```

1.6.2 No aliasing of names

Another restriction imposed by the SPARK subset concerns aliasing⁶. We say that two names are *aliased* if they refer to the same object. There are two reasons why aliasing is forbidden in SPARK:

- It makes verification more difficult because it requires taking into account the fact that modifications to variables with different names may actually update the same object.
- Results may seem unexpected from a user point of view. The results of a subprogram call may depend on compiler-specific attributes, such as parameter passing mechanisms, when its parameters are aliased.

Aliasing can occur as part of the parameter passing that occurs in a subprogram call. Functions have no side-effects in SPARK, so aliasing of parameters in function calls isn't problematic; we need only consider procedure calls. When a procedure is called, SPARK verifies that no **out** or **in out** parameter is aliased with either another parameter of the procedure or a global variable modified in the procedure's body.

Procedure Move_To_Total is an example where the possibility of aliasing wasn't taken into account by the programmer:

```
procedure No Aliasing is
1
2
      Total : Natural := 0;
3
4
      procedure Move To Total (Source : in out Natural)
5
        with Post => Total = Total'Old + Source'Old and Source = 0
6
      is
7
      begin
8
         Total := Total + Source;
9
         Source := 0;
10
      end Move To Total;
11
12
      X : Natural := 3;
13
14
   begin
15
      Move To Total (X);
                                 -- OK
16
      pragma Assert (Total = 3); -- OK
17
      Move To Total (Total); -- flow analysis error
18
      pragma Assert (Total = 6); -- runtime error
19
   end No_Aliasing;
20
```

Listing 7: no_aliasing.adb

Code block metadata

```
Project: Courses.Intro_To_Spark.Overview.Aliasing
MD5: 91038ef030fe27e3b000ab3db9c134ad
```

⁶ https://en.wikipedia.org/wiki/Aliasing_(computing)

Runtime output

raised ADA.ASSERTIONS.ASSERTION_ERROR : no_aliasing.adb:19

Move_To_Total adds the value of its input parameter Source to the global variable Total and then resets Source to 0. The programmer has clearly not taken into account the possibility of an aliasing between Total and Source. (This sort of error is quite common.)

This procedure itself is valid SPARK. When doing verification, GNATprove assumes, like the programmer did, that there's no aliasing between Total and Source. To ensure this assumption is valid, GNATprove checks for possible aliasing on every call to Move_To_Total. Its final call in procedure No_Aliasing violates this assumption, which produces both a message from GNATprove and a runtime error (an assertion violation corresponding to the expected change in Total from calling Move_To_Total). Note that the postcondition of Move_To_Total is not violated on this second call since integer parameters are passed by copy and the postcondition is checked before the copy-back from the formal parameters to the actual arguments.

Aliasing can also occur as a result of using access types (pointers⁷ in Ada). These are restricted in SPARK so that only benign aliasing is allowed, when both names are only used to read the data. In particular, assignment between access objects operates a transfer of ownership, where the source object loses its permission to read or write the underlying allocated memory.

Procedure Ownership_Transfer is an example of code that is legal in Ada but rejected in SPARK due to aliasing:

Listing 8: ownership transfer.adb

```
procedure Ownership Transfer is
1
      type Int Ptr is access Integer;
2
            : Int_Ptr;
      Х
3
             : Int Ptr;
      Υ
4
      Dummy : Integer;
5
   begin
6
             := new Integer'(1);
      Х
7
      X.all := X.all + 1;
8
            := X;
      Y
9
      Y.all := Y.all + 1;
10
      X.all := X.all + 1; -- illegal
11
      X.all := 1;
                            -- illegal
12
      Dummy := X.all;
                            -- illegal
13
  end Ownership_Transfer;
14
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Ownership_Transfer MD5: 951felc930d43a5009e607994ae0dd03

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
```

(continues on next page)

⁷ https://en.wikipedia.org/wiki/Pointer_(computer_programming)

(continued from previous page)

```
ownership_transfer.adb:11:06: error: dereference from "X" is not writable
ownership_transfer.adb:11:06: error: object was moved at line 9
ownership_transfer.adb:11:15: error: dereference from "X" is not readable
ownership_transfer.adb:11:15: error: object was moved at line 9
ownership_transfer.adb:12:06: error: dereference from "X" is not writable
ownership_transfer.adb:12:06: error: object was moved at line 9
ownership_transfer.adb:13:15: error: object was moved at line 9
ownership_transfer.adb:13:15: error: dereference from "X" is not readable
ownership_transfer.adb:13:15: error: dereference from "X" is not readable
ownership_transfer.adb:13:15: error: object was moved at line 9
gnatprove: error during analysis of data and information flow
```

After the assignment of X to Y, variable X cannot be used anymore to read or write the underlying allocated memory.

Note: For more details on these limitations, see the SPARK User's Guide⁸.

1.7 Designating SPARK Code

Since the SPARK language is restricted to only allow easily specifiable and verifiable constructs, there are times when you can't or don't want to abide by these limitations over your entire code base. Therefore, the SPARK tools only check conformance to the SPARK subset on code which you identify as being in SPARK.

You do this by using an aspect named SPARK_Mode. If you don't explicitly specify otherwise, SPARK_Mode is *Off*, meaning you can use the complete set of Ada features in that code and that it should not be analyzed by GNATprove. You can change this default either selectively (on some units or subprograms or packages inside units) or globally (using a configuration pragma, which is what we're doing in this tutorial). To allow simple reuse of existing Ada libraries, entities declared in imported units with no explicit SPARK_Mode can still be used from SPARK code. The tool only checks for SPARK conformance on the declaration of those entities which are actually used within the SPARK code.

Here's a common case of using the SPARK_Mode aspect:

```
package P
  with SPARK_Mode => On
is
    -- package spec is IN SPARK, so can be used by SPARK clients
end P;
package body P
  with SPARK_Mode => Off
is
    -- body is NOT IN SPARK, so is ignored by GNATprove
end P;
```

The package P only defines entities whose specifications are in the SPARK subset. However, it wants to use all Ada features in its body. Therefore the body should not be analyzed and has its SPARK_Mode aspect set to *Off*.

You can specify SPARK_Mode in a fine-grained manner on a per-unit basis. An Ada package has four different components: the visible and private parts of its specification and the declarative and statement parts of its body. You can specify SPARK_Mode as being either *On* or *Off* on any of those parts. Likewise, a subprogram has two parts: its specification and its body.

⁸ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/language_restrictions.html# language-restrictions

A general rule in SPARK is that once SPARK_Mode has been set to Off, it can never be switched On again in the same part of a package or subprogram. This prevents setting SPARK_Mode to On for local units of a unit with SPARK_Mode Off and switching back to SPARK_Mode On for a part of a given unit where it was set fo Off in a previous part.

Note: For more details on the use of SPARK_Mode, see the SPARK User's Guide⁹.

1.8 Code Examples / Pitfalls

1.8.1 Example #1

Here's a package defining an abstract stack type (defined as a private type in SPARK) of Element objects along with some subprograms providing the usual functionalities of stacks. It's marked as being in the SPARK subset.

Listing 9: stack_package.ads

```
package Stack Package
1
     with SPARK Mode => On
2
3
   is
      type Element is new Natural;
4
      type Stack is private;
5
6
      function Empty return Stack;
7
      procedure Push (S : in out Stack; E : Element);
8
      function Pop (S : in out Stack) return Element;
9
10
   private
11
      type Stack is record
12
         Top : Integer;
13
14
      end record;
15
16
   end Stack Package;
17
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Overview.Example_01
MD5: 2b15e13e850435fb93406054d70b51c6
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

stack_package.ads:9:13: error: function with "in out" parameter is not allowed in

_____SPARK

stack_package.ads:9:13: error: violation of aspect SPARK_Mode at line 2

gnatprove: error during analysis of data and information flow
```

Side-effects in expressions are not allowed in SPARK. Therefore, Pop is not allowed to modify its parameter S.

⁹ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/spark_mode.html

1.8.2 Example #2

Let's turn to an abstract state machine version of a stack, where the unit provides a single instance of a stack. The content of the stack (global variables Content and Top) is not directly visible to clients. In this stripped-down version, only the function Pop is available to clients. The package spec and body are marked as being in the SPARK subset.

Listing 10: global_stack.ads

```
1 package Global_Stack
2 with SPARK_Mode => On
3 is
4 type Element is new Integer;
5
6 function Pop return Element;
7
8 end Global Stack;
```

Listing 11: global_stack.adb

```
package body Global Stack
1
     with SPARK_Mode => On
2
   is
3
      Max : constant Natural := 100;
4
      type Element Array is array (1 .. Max) of Element;
5
6
      Content : Element_Array;
7
              : Natural;
      Тор
8
9
       function Pop return Element is
10
         E : constant Element := Content (Top);
11
      beain
12
          Top := Top - 1;
13
          return E;
14
      end Pop;
15
16
   end Global Stack;
17
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Overview.Example_02
MD5: 8c4eb564643eef48264b5e43a6f580b9
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

global_stack.adb:7:04: warning: variable "Content" is read but never assigned [-

□gnatwv]

global_stack.ads:6:13: error: function with output global "Top" is not allowed in

□SPARK

gnatprove: error during analysis of data and information flow
```

As above, functions should be free from side-effects. Here, Pop updates the global variable Top, which is not allowed in SPARK.

1.8.3 Example #3

We now consider two procedures: Permute and Swap. Permute applies a circular permutation to the value of its three parameters. Swap then uses Permute to swap the value of X and Y.

```
Listing 12: p.ads
```

```
1 package P
2 with SPARK_Mode => On
3 is
4 procedure Permute (X, Y, Z : in out Positive);
5 procedure Swap (X, Y : in out Positive);
6 end P;
```

```
Listing 13: p.adb
```

```
package body P
1
     with SPARK Mode => On
2
   is
3
      procedure Permute (X, Y, Z : in out Positive) is
4
          Tmp : constant Positive := X;
5
      begin
6
          X := Y;
7
          Y := Z;
8
          Z := Tmp;
9
      end Permute;
10
11
      procedure Swap (X, Y : in out Positive) is
12
       beain
13
          Permute (X, Y, Y);
14
      end Swap;
15
   end P;
16
```

Listing 14: test_swap.adb

```
with P; use P;
1
2
   procedure Test_Swap
3
     with SPARK_Mode => On
4
   is
5
      A : Integer := 1;
6
      B : Integer := 2;
7
  beain
8
      Swap (A, B);
9
  end Test_Swap;
10
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_03
MD5: 0868a806061d86af4d2a03b1e7dc83c2

Build output

```
p.adb:14:19: error: writable actual for "Y" overlaps with actual for "Z"
gprbuild: *** compilation phase failed
```

```
Phase 1 of 2: generation of Global contracts ...
p.adb:14:19: error: writable actual for "Y" overlaps with actual for "Z"
gnatprove: error during generation of Global contracts
```

Here, the values for parameters Y and Z are aliased in the call to Permute, which is not allowed in SPARK. In fact, in this particular case, this is even a violation of Ada rules so the same error is issued by the Ada compiler.

In this example, we see the reason why aliasing is not allowed in SPARK: since Y and Z are **Positive**, they are passed by copy and the result of the call to Permute depends on the order in which they're copied back after the call.

1.8.4 Example #4

Here, the Swap procedure is used to swap the value of the two record components of R.

Listing 15: p.ads

```
package P
1
     with SPARK Mode => On
2
   is
3
      type Rec is record
4
         F1 : Positive;
5
         F2 : Positive;
6
      end record;
7
8
      procedure Swap_Fields (R : in out Rec);
9
      procedure Swap (X, Y : in out Positive);
10
   end P;
11
```

```
Listing 16: p.adb
```

```
package body P
1
     with SPARK Mode => On
2
   is
3
      procedure Swap (X, Y : in out Positive) is
4
          Tmp : constant Positive := X;
5
6
      begin
          X := Y;
7
          Y := Tmp;
8
      end Swap;
9
10
      procedure Swap_Fields (R : in out Rec) is
11
       begin
12
          Swap (R.F1, R.F2);
13
      end Swap_Fields;
14
15
   end P;
16
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_04
MD5: ae4d3ebe8dd1a8f67f35cedffdea2ac9

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ...

This code is correct. The call to Swap is safe: two different components of the same record can't refer to the same object.

1.8.5 Example #5

Here's a slight modification of the previous example using an array instead of a record: Swap_Indexes calls Swap on values stored in the array A.

```
Listing 17: p.ads
```

```
1 package P
2 with SPARK_Mode => On
3 is
4 type P_Array is array (Natural range <>) of Positive;
5
6 procedure Swap_Indexes (A : in out P_Array; I, J : Natural);
7 procedure Swap (X, Y : in out Positive);
8 end P;
```

```
Listing 18: p.adb
```

```
package body P
1
     with SPARK Mode => On
2
   is
3
      procedure Swap (X, Y : in out Positive) is
4
          Tmp : constant Positive := X;
5
      begin
6
          X := Y;
7
          Y := Tmp;
8
      end Swap;
9
10
      procedure Swap_Indexes (A : in out P_Array; I, J : Natural) is
11
      begin
12
          Swap (A (I), A (J));
13
      end Swap Indexes;
14
15
   end P;
16
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_05
MD5: 62a95179572e36443995ff54a2d5ef08

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
p.adb:13:13: medium: formal parameters "X" and "Y" might be aliased (SPARK RM 6.4.
_{\ominus}2)
gnatprove: unproved check messages considered as errors
```

GNATprove detects a possible case of aliasing. Unlike the previous example, it has no way of knowing that the two elements A (I) and A (J) are actually distinct when we call Swap. GNATprove issues a check message here instead of an error, giving you the possibility of justifying the message after review (meaning that you've verified manually that this can't, in fact, occur).

1.8.6 Example #6

We now consider a package declaring a type Dictionary, an array containing a word per letter. The procedure Store allows us to insert a word at the correct index in a dictionary.

```
Listing 19: p.ads
```

```
with Ada.Finalization;
1
2
   package P
3
     with SPARK Mode => On
4
   is
5
      subtype Letter is Character range 'a' ... 'z';
6
      type String_Access is new Ada.Finalization.Controlled with record
7
8
         Ptr : access String;
9
      end record;
      type Dictionary is array (Letter) of String_Access;
10
11
      procedure Store (D : in out Dictionary; W : String);
12
   end P;
13
```

Listing 20: p.adb

```
package body P
1
    with SPARK Mode => On
2
  is
З
     procedure Store (D : in out Dictionary; W : String) is
4
        First Letter := W (W'First);
5
     begin
6
        D (First Letter).Ptr := new String'(W);
7
8
     end Store;
  end P;
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_06
MD5: 9175bcd1474e2143462b860c01d8602e

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

p.adb:7:07: error: "String_Access" is not allowed in SPARK (due to controlled

↓types)

p.adb:7:07: error: violation of aspect SPARK_Mode at line 2

p.adb:7:31: error: borrow or observe of an expression which is not part of stand-

↓alone object or parameter is not allowed in SPARK (SPARK RM 3.10(3)))

p.adb:7:31: error: violation of aspect SPARK_Mode at line 2

p.ads:7:09: error: "Controlled" is not allowed in SPARK (due to controlled types)

p.ads:7:09: error: violation of aspect SPARK_Mode at line 4

p.ads:10:04: error: "String_Access" is not allowed in SPARK (due to controlled_

↓types)

p.ads:10:04: error: violation of aspect SPARK_Mode at line 4

gnatprove: error during analysis of data and information flow
```

This code is not correct: controlled types are not part of the SPARK subset. The solution here is to use SPARK_Mode to separate the definition of String_Access from the rest of the code in a fine grained manner.

1.8.7 Example #7

Here's a new version of the previous example, which we've modified to hide the controlled type inside the private part of package P, using pragma SPARK_Mode (Off) at the start of the private part.

```
Listing 21: p.ads
```

```
with Ada.Finalization;
1
2
   package P
3
     with SPARK_Mode => On
4
   is
5
      subtype Letter is Character range 'a' ... 'z';
6
      type String Access is private;
7
      type Dictionary is array (Letter) of String Access;
8
9
      function New_String_Access (W : String) return String_Access;
10
11
      procedure Store (D : in out Dictionary; W : String);
12
13
   private
14
      pragma SPARK_Mode (Off);
15
16
      type String_Access is new Ada.Finalization.Controlled with record
17
         Ptr : access String;
18
      end record;
19
20
      function New String Access (W : String) return String Access is
21
         (Ada.Finalization.Controlled with Ptr => new String'(W));
22
   end P;
23
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Overview.Example_07
MD5: cb04206c9734eb95f6444757d005dae2
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
```

Since the controlled type is defined and used inside of a part of the code ignored by GNATprove, this code is correct.

1.8.8 Example #8

Let's put together the new spec for package P with the body of P seen previously.

```
Listing 22: p.ads
```

```
with Ada.Finalization;
1
2
  package P
3
     with SPARK Mode => On
4
   is
5
      subtype Letter is Character range 'a' ... 'z';
6
      type String Access is private;
7
      type Dictionary is array (Letter) of String Access;
8
9
```

(continues on next page)

```
function New_String_Access (W : String) return String_Access;
10
11
      procedure Store (D : in out Dictionary; W : String);
12
13
   private
14
      pragma SPARK_Mode (Off);
15
16
      type String_Access is new Ada.Finalization.Controlled with record
17
         Ptr : access String;
18
      end record;
19
20
      function New_String_Access (W : String) return String_Access is
21
22
        (Ada.Finalization.Controlled with Ptr => new String'(W));
   end P;
23
```

Listing 23: p.adb

```
package body P
1
    with SPARK Mode => On
2
   is
3
      procedure Store (D : in out Dictionary; W : String) is
4
         First_Letter : constant Letter := W (W'First);
5
      beain
6
         D (First_Letter) := New_String_Access (W);
7
      end Store;
8
  end P:
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_08
MD5: dacb2d50d0ddc6c620ee9945cb819369

Prover output

```
Phase 1 of 2: generation of Global contracts ...

p.adb:1:01: error: incorrect application of SPARK_Mode at /vagrant/frontend/dist/

∴test_output/projects/Courses/Intro_To_Spark/Overview/Example_08/

∴dacb2d50d0ddc6c620ee9945cb819369/main_spark.adc:12

p.adb:1:01: error: value Off was set for SPARK_Mode on "P" at p.ads:15

p.adb:2:08: error: incorrect use of SPARK_Mode

p.adb:2:08: error: value Off was set for SPARK_Mode on "P" at p.ads:15

gnatprove: error during generation of Global contracts
```

The body of Store doesn't actually use any construct that's not in the SPARK subset, but we nevertheless can't set SPARK_Mode to On for P's body because it has visibility to P's private part, which is not in SPARK, even if we don't use it.

1.8.9 Example #9

Next, we moved the declaration and the body of the procedure Store to another package named Q.

Listing 24: p.ads

```
1 with Ada.Finalization;
2
3 package P
4 with SPARK_Mode => On
5 is
```

(continues on next page)

(continued from previous page)

(continued from previous page)

```
subtype Letter is Character range 'a' ... 'z';
6
      type String_Access is private;
7
      type Dictionary is array (Letter) of String_Access;
8
9
      function New_String_Access (W : String) return String_Access;
10
11
   private
12
      pragma SPARK_Mode (Off);
13
14
      type String_Access is new Ada.Finalization.Controlled with record
15
         Ptr : access String;
16
      end record;
17
18
      function New_String_Access (W : String) return String_Access is
19
        (Ada.Finalization.Controlled with Ptr => new String'(W));
20
   end P;
21
```

Listing 25: q.ads

```
1 with P; use P;
2 package Q
3 with SPARK_Mode => On
4 is
5 procedure Store (D : in out Dictionary; W : String);
6 end Q;
```

Listing 26: q.adb

```
package body Q
1
     with SPARK Mode => On
2
   is
3
      procedure Store (D : in out Dictionary; W : String) is
4
5
         First_Letter : constant Letter := W (W'First);
      begin
6
         D (First_Letter) := New_String_Access (W);
7
      end Store;
8
  end Q;
a
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_09
MD5: b397e82987c100de5a53ede16fbef37f

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
```

And now everything is fine: we've managed to retain the use of the controlled type while having most of our code in the SPARK subset so GNATprove is able to analyze it.

1.8.10 Example #10

Our final example is a package with two functions to search for the value 0 inside an array A. The first raises an exception if 0 isn't found in A while the other simply returns 0 in that case.

```
Listing 27: p.ads
```

```
package P
1
     with SPARK Mode => On
2
   is
3
      type N_Array is array (Positive range <>) of Natural;
4
      Not Found : exception;
5
6
      function Search_Zero_P (A : N_Array) return Positive;
7
8
      function Search_Zero_N (A : N_Array) return Natural;
9
   end P;
10
```

Listing 28: p.adb

```
package body P
1
     with SPARK Mode => On
2
   is
3
      function Search Zero P (A : N Array) return Positive is
4
      begin
5
          for I in A'Range loop
6
             if A(I) = 0 then
7
                return I;
8
             end if:
9
         end loop;
10
          raise Not Found;
11
      end Search Zero P;
12
13
      function Search_Zero_N (A : N_Array) return Natural
14
        with SPARK Mode => Off is
15
      begin
16
         return Search_Zero_P (A);
17
      exception
18
         when Not Found => return 0;
19
      end Search Zero N;
20
   end P;
21
```

Code block metadata

Project: Courses.Intro_To_Spark.Overview.Example_10
MD5: 4b9656698ab1d42cebc72817f8a00637

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... p.adb:11:07: medium: exception might be raised gnatprove: unproved check messages considered as errors

This code is perfectly correct, despite the use of exception handling, because we've carefully isolated this non-SPARK feature in a function body marked with a SPARK_Mode of Off so it's ignored by GNATprove. However, GNATprove tries to show that Not_Found is never raised in Search_Zero_P, producing a message about a possible exception being raised. Looking at Search_Zero_N, it's indeed likely that an exception is meant to be raised in some cases, which means you need to verify that Not_Found is only raised when appropriate using other methods such as peer review or testing.

CHAPTER TWO

FLOW ANALYSIS

In this section we present the flow analysis capability provided by the GNATprove tool, a critical tool for using SPARK.

2.1 What does flow analysis do?

Flow analysis concentrates primarily on variables. It models how information flows through them during a subprogram's execution, connecting the final values of variables to their initial values. It analyzes global variables declared at library level, local variables, and formal parameters of subprograms.

Nesting of subprograms creates what we call *scope variables*: variables declared locally to an enclosing unit. From the perspective of a nested subprogram, scope variables look very much like global variables

Flow analysis is usually fast, roughly as fast as compilation. It detects various types of errors and finds violations of some SPARK legality rules, such as the absence of aliasing and freedom of expressions from side-effects. We discussed these rules in the *SPARK Overview* (page 3).

Flow analysis is *sound*: if it doesn't detect any errors of a type it's supposed to detect, we know for sure there are no such errors.

2.2 Errors Detected

2.2.1 Uninitialized Variables

We now present each class of errors detected by flow analysis. The first is the reading of an uninitialized variable. This is nearly always an error: it introduces non-determinism and breaks the type system because the value of an uninitialized variable may be outside the range of its subtype. For these reasons, SPARK requires every variable to be initialized before being read.

Flow analysis is responsible for ensuring that SPARK code always fulfills this requirement. For example, in the function Max_Array shown below, we've neglected to initialize the value of Max prior to entering the loop. As a consequence, the value read by the condition of the if statement may be uninitialized. Flow analysis detects and reports this error.

Listing 1: show_uninitialized.ads

```
package Show_Uninitialized is
type Array_Of_Naturals is array (Integer range <>) of Natural;
```

(continues on next page)

(continued from previous page)

```
function Max_Array (A : Array_Of_Naturals) return Natural;
```

```
end Show_Uninitialized;
```

4

5 6

7

Listing 2: show_uninitialized.adb

```
package body Show Uninitialized is
1
2
      function Max Array (A : Array Of Naturals) return Natural is
3
         Max : Natural:
4
      begin
5
          for I in A'Range loop
6
             if A (I) > Max then -- Here Max may not be initialized
7
                Max := A (I);
8
             end if:
9
          end loop;
10
          return Max;
11
      end Max Array;
12
13
   end Show_Uninitialized;
14
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Uninitialized
MD5: 82fe32cbe33e25bac5466f86ee2e03c4

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

show_uninitialized.adb:7:21: warning: "Max" may be referenced before it has a

~value [enabled by default]

show_uninitialized.adb:7:21: medium: "Max" might not be initialized

show_uninitialized.adb:11:14: medium: "Max" might not be initialized

gnatprove: unproved check messages considered as errors
```

Note: For more details on how flow analysis verifies data initialization, see the SPARK User's Guide¹⁰.

2.2.2 Ineffective Statements

Ineffective statements are different than dead code: they're executed, and often even modify the value of variables, but have no effect on any of the subprogram's visible outputs: parameters, global variables or the function result. Ineffective statements should be avoided because they make the code less readable and more difficult to maintain.

More importantly, they're often caused by errors in the program: the statement may have been written for some purpose, but isn't accomplishing that purpose. These kinds of errors can be difficult to detect in other ways.

For example, the subprograms Swap1 and Swap2 shown below don't properly swap their two parameters X and Y. This error caused a statement to be ineffective. That ineffective statement is not an error in itself, but flow analysis produces a warning since it can be indicative of an error, as it is here.

 $^{^{10}\} https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/language_restrictions.html \# data-initialization-policy$

Listing 3: show_ineffective_statements.ads

```
package Show_Ineffective_Statements is
type T is new Integer;
procedure Swap1 (X, Y : in out T);
mrocedure Swap2 (X, Y : in out T);
end Show_Ineffective_Statements;
```

Listing 4: show_ineffective_statements.adb

```
package body Show_Ineffective_Statements is
1
2
      procedure Swap1 (X, Y : in out T) is
3
         Tmp : T;
4
      begin
5
          Tmp := X; -- This statement is ineffective
6
         X := Y;
7
         Υ
            := X;
8
      end Swap1;
9
10
      Tmp : T := 0;
11
12
      procedure Swap2 (X, Y : in out T) is
13
          Temp : T := X; -- This variable is unused
14
      begin
15
         X := Y;
16
         Y := Tmp;
17
      end Swap2;
18
19
   end Show_Ineffective_Statements;
20
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Ineffective_Statements
MD5: 473a9215e9e98bd25147998d43847a12

Prover output

So far, we've seen examples where flow analysis warns about ineffective statements and unused variables.

2.2.3 Incorrect Parameter Mode

Parameter modes are an important part of documenting the usage of a subprogram and affect the code generated for that subprogram. Flow analysis checks that each specified parameter mode corresponds to the usage of that parameter in the subprogram's body. It checks that an **in** parameter is never modified, either directly or through a subprogram call, checks that the initial value of an **out** parameter is never read in the subprogram (since it may not be defined on subprogram entry), and warns when an **in out** parameter isn't modified or when its initial value isn't used. All of these may be signs of an error.

We see an example below. The subprogram Swap is incorrect and GNATprove warns about an input which isn't read:

```
1 package Show_Incorrect_Param_Mode is
2
3 type T is new Integer;
4
5 procedure Swap (X, Y : in out T);
6
7 end Show_Incorrect_Param_Mode;
```

Listing 6: show_incorrect_param_mode.adb

```
package body Show Incorrect Param Mode is
1
2
      procedure Swap (X, Y : in out T) is
3
         Tmp : T := X;
4
      begin
5
         Y := X; -- The initial value of Y is not used
6
         X := Tmp; -- Y is computed to be an out parameter
7
      end Swap;
8
9
  end Show Incorrect Param Mode;
10
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Incorrect_Param_Mode
MD5: 1e33dbf461daab0daed01c83025232fc
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_incorrect_param_mode.ads:5:23: warning: unused initial value of "Y"
```

In SPARK, unlike Ada, you should declare an **out** parameter to be **in out** if it's not modified on every path, in which case its value may depend on its initial value. SPARK is stricter than Ada to allow more static detection of errors. This table summarizes SPARK's valid parameter modes as a function of whether reads and writes are done to the parameter.

Initial value read	Written on some path	Written on every path	Parameter mode
Х			in
Х	Х		in out
Х		Х	in out
	Х		in out
		Х	out

2.3 Additional Verifications

2.3.1 Global Contracts

So far, none of the verifications we've seen require you to write any additional annotations. However, flow analysis also checks flow annotations that you write. In SPARK, you can specify the set of global and scoped variables accessed or modified by a subprogram. You do this using a contract named Global.

When you specify a Global contract for a subprogram, flow analysis checks that it's both correct and complete, meaning that no variables other than those stated in the contract are accessed or modified, either directly or through a subprogram call, and that all those listed are accessed or modified. For example, we may want to specify that the function Get_Value_Of_X reads the value of the global variable X and doesn't access any other global variable. If we do this through a comment, as is usually done in other languages, GNATprove can't verify that the code complies with this specification:

```
package Show_Global_Contracts is
X : Natural := 0;
```

```
function Get_Value_Of_X return Natural;
-- Get_Value_Of_X reads the value of the global variable X
```

```
end Show_Global_Contracts;
```

You write global contracts as part of the subprogram specification. In addition to their value in flow analysis, they also provide useful information to users of a subprogram. The value you specify for the Global aspect is an aggregate-like list of global variable names, grouped together according to their mode.

In the example below, the procedure Set_X_To_Y_Plus_Z reads both Y and Z. We indicate this by specifying them as the value for Input. It also writes X, which we specify using Output. Since Set_X_To_X_Plus_Y both writes X and reads its initial value, X's mode is In_Out. Like parameters, if no mode is specified in a Global aspect, the default is Input. We see this in the case of the declaration of Get_Value_Of_X. Finally, if a subprogram, such as Incr_Parameter_X, doesn't reference any global variables, you set the value of the global contract to **null**.

```
Listing 7: show_global_contracts.ads
```

```
package Show Global Contracts is
1
2
      X, Y, Z : Natural := 0;
3
4
      procedure Set_X_To_Y_Plus_Z with
5
         Global => (Input => (Y, Z), -- reads values of Y and Z
6
                                       -- modifies value of X
                     Output => X);
7
8
      procedure Set_X_To_X_Plus_Y with
9
        Global => (Input => Y, -- reads value of Y
In_Out => X); -- modifies value of X and
10
11
                                    -- also reads its initial value
12
13
      function Get Value Of X return Natural with
14
         Global => X; -- reads the value of the global variable X
15
16
      procedure Incr Parameter X (X : in out Natural) with
17
         Global => null; -- do not reference any global variable
18
```

(continues on next page)

20 end Show_Global_Contracts;

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Global_Contracts
MD5: 2cbf90f2d27b6b0043a2e29449e79df9
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ...

Note: For more details on global contracts, see the SPARK User's Guide¹¹.

2.3.2 Depends Contracts

You may also supply a Depends contract for a subprogram to specify dependencies between its inputs and outputs. These dependencies include not only global variables but also parameters and the function's result. When you supply a Depends contract for a subprogram, flow analysis checks that it's correct and complete, that is, for each dependency you list, the variable depends on those listed and on no others.

For example, you may want to say that the new value of each parameter of Swap, shown below, depends only on the initial value of the other parameter and that the value of X after the return of Set_X_To_Zero doesn't depend on any global variables. If you indicate this through a comment, as you often do in other languages, GNATprove can't verify that this is actually the case.

```
package Show_Depends_Contracts is
  type T is new Integer;
  procedure Swap (X, Y : in out T);
  -- The value of X (resp. Y) after the call depends only
  -- on the value of Y (resp. X) before the call
  X : Natural;
  procedure Set_X_To_Zero;
  -- The value of X after the call depends on no input
end Show Depends Contracts;
```

Like Global contracts, you specify a Depends contract in subprogram declarations using an aspect. Its value is a list of one or more dependency relations between the outputs and inputs of the subprogram. Each relation is represented as two lists of variable names separated by an arrow. On the left of each arrow are variables whose final value depends on the initial value of the variables you list on the right.

For example, here we indicate that the final value of each parameter of Swap depends only on the initial value of the other parameter. If the subprogram is a function, we list its result as an output, using the Result attribute, as we do for Get_Value_Of_X below.

(continued from previous page)

 $^{^{11}\} https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/subprogram_contracts.html \#\ data-dependencies$

```
Listing 8: show_depends_contracts.ads
```

```
package Show_Depends_Contracts is
1
2
       type T is new Integer;
3
4
       X, Y, Z : T := 0;
5
6
       procedure Swap (X, Y : in out T) with
7
         Depends \Rightarrow (X \Rightarrow Y,
8
                      -- X depends on the initial value of Y
9
                      Y => X);
10
                       -- Y depends on the initial value of X
11
12
       function Get_Value_Of_X return T with
13
         Depends => (Get Value Of X'Result => X);
14
                       -- result depends on the initial value of X
15
16
       procedure Set_X_To_Y_Plus_Z with
17
         Depends \Rightarrow (X \Rightarrow (Y, Z));
18
                       -- X depends on the initial values of Y and Z
19
20
       procedure Set_X_To_X_Plus_Y with
21
         Depends \Rightarrow (X \Rightarrow Y);
22
                  -- X depends on Y and X's initial value
23
24
       procedure Do_Nothing (X : T) with
25
         Depends => (null => X);
26
                       -- no output is affected by X
27
28
       procedure Set_X_To_Zero with
29
         Depends => (X => null);
30
                      -- X depends on no input
31
32
   end Show_Depends_Contracts;
33
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Depends_Contracts
MD5: 290866c4208b6deff717a402bc2aef34

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ...

Often, the final value of a variable depends on its own initial value. You can specify this in a concise way using the + character, as we did in the specification of $Set_X_To_X_Plus_Y$ above. If there's more than one variable on the left of the arrow, a + means each variables depends on itself, not that they all depend on each other. You can write the corresponding dependency with (=> +) or without (=>+) whitespace.

If you have a program where an input isn't used to compute the final value of any output, you express that by writting **null** on the left of the dependency relation, as we did for the Do_Nothing subprogram above. You can only write one such dependency relation, which lists all unused inputs of the subprogram, and it must be written last. Such an annotation also silences flow analysis' warning about unused parameters. You can also write **null** on the right of a dependency relation to indicate that an output doesn't depend on any input. We do that above for the procedure Set_X_To_Zero.

Note: For more details on depends contracts, see the SPARK User's Guide¹².

2.4 Shortcomings

2.4.1 Modularity

Flow analysis is sound, meaning that if it doesn't output a message on some analyzed SPARK code, you can be assured that none of the errors it tests for can occur in that code. On the other hand, flow analysis often issues messages when there are, in fact, no errors. The first, and probably most common reason for this relates to modularity.

To scale flow analysis to large projects, verifications are usually done on a per-subprogram basis, including detection of uninitialized variables. To analyze this modularly, flow analysis needs to assume the initialization of inputs on subprogram entry and modification of outputs during subprogram execution. Therefore, each time a subprogram is called, flow analysis checks that global and parameter inputs are initialized and each time a subprogram returns, it checks that global and parameter outputs were modified.

This can produce error messages on perfectly correct subprograms. An example is Set_X_To_Y_Plus_Z below, which only sets its **out** parameter X when 0verflow is **False**.

1	<pre>procedure Set_X_To_Y_Plus_Z</pre>
2	(Y, Z : Natural;
3	X : out Natural;
4	Overflow : out Boolean)
5	is
6	begin
7	<pre>if Natural'Last - Z < Y then</pre>
8	Overflow := True; X should be initialized on every path
9	else
10	<pre>Overflow := False;</pre>
11	X := Y + Z;
12	end if;
13	<pre>end Set_X_To_Y_Plus_Z;</pre>

Listing 9: set_x_to_y_plus_z.adb

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Set_X_To_Y_Plus_Z MD5: be47cd769d2a7267c0bd1bb2ef0d6328

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

set_x_to_y_plus_z.adb:3:04: medium: "X" might not be initialized in "Set_X_To_Y_

□Plus_Z" [reason for check: OUT parameter should be initialized on return]

□ □ [possible fix: initialize "X" on all paths or make "X" an IN OUT parameter]

gnatprove: unproved check messages considered as errors
```

The message means that flow analysis wasn't able to verify that the program didn't read an uninitialized variable. To solve this problem, you can either set X to a dummy value when there's an overflow or manually verify that X is never used after a call to Set_X_To_Y_Plus_Z that returned **True** as the value of 0verflow.

 $^{12}\ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/subprogram_contracts.html \# flow-dependencies$

2.4.2 Composite Types

Another common cause of false alarms is caused by the way flow analysis handles composite types. Let's start with arrays.

Flow analysis treats an entire array as single object instead of one object per element, so it considers modifying a single element to be a modification of the array as a whole. Obviously, this makes reasoning about which global variables are accessed less precise and hence the dependencies of those variables are also less precise. This also affects the ability to accurately detect reads of uninitialized data.

It's sometimes impossible for flow analysis to determine if an entire array object has been initialized. For example, after we write code to initialize every element of an unconstrained array A in chunks, we may still receive a message from flow analysis claiming that the array isn't initialized. To resolve this issue, you can either use a simpler loop over the full range of the array, or (even better) an aggregate assignment, or, if that's not possible, verify initialization of the object manually.

Listing 10: show_composite_types_shortcoming.ads

```
package Show_Composite_Types_Shortcoming is
type T is array (Natural range <>) of Integer;
procedure Init_Chunks (A : out T);
procedure Init_Loop (A : out T);
procedure Init_Aggregate (A : out T);
```

```
9 end Show_Composite_Types_Shortcoming;
```

```
Listing 11: show_composite_types_shortcoming.adb
```

```
package body Show Composite Types Shortcoming is
1
2
      procedure Init_Chunks (A : out T) is
3
      begin
4
          A (A'First) := 0;
5
          for I in A'First + 1 .. A'Last loop
6
             A (I) := 0;
7
          end loop;
8
             flow analysis doesn't know that A is initialized
9
      end Init Chunks;
10
11
      procedure Init Loop (A : out T) is
12
      begin
13
          for I in A'Range loop
14
             A (I) := 0;
15
          end loop;
16
          -- flow analysis knows that A is initialized
17
      end Init_Loop;
18
19
      procedure Init Aggregate (A : out T) is
20
      begin
21
          A := (others \Rightarrow 0);
22
          -- flow analysis knows that A is initialized
23
      end Init Aggregate;
24
25
   end Show_Composite_Types_Shortcoming;
26
```

Code block metadata
Project: Courses.Intro_To_Spark.Flow_Analysis.Composite_Types_Shortcoming
MD5: a366dcdd141191466027b2b928560c5e

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ... show_composite_types_shortcoming.ads:5:27: medium: "A" might not be initialized in "Init_Chunks" [reason for check: OUT parameter should be fully initialized on "return] [possible fix: initialize "A" on all paths, make "A" an IN OUT parameter or annotate it with aspect Relaxed_Initialization] gnatprove: unproved check messages considered as errors

Flow analysis is more precise on record objects because it tracks the value of each component of a record separately within a single subprogram. So when a record object is initialized by successive assignments of its components, flow analysis knows that the entire object is initialized. However, record objects are still treated as single objects when analyzed as an input or output of a subprogram.

Listing 12: show_record_flow_analysis.ads

```
package Show Record Flow Analysis is
1
2
      type Rec is record
3
         F1 : Natural;
4
         F2 : Natural;
5
      end record:
6
7
      procedure Init (R : out Rec);
8
9
   end Show Record Flow Analysis;
10
```

Listing 13: show_record_flow_analysis.adb

```
package body Show Record Flow Analysis is
1
2
      procedure Init (R : out Rec) is
3
      begin
4
         R.F1 := 0;
5
         R.F2 := 0;
6
         -- R is initialized
7
      end Init;
8
9
   end Show Record Flow Analysis;
10
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Record_Flow_Analysis_1
MD5: 24cd553b87b737536912b1bb780f6402
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
show_record_flow_analysis.ads:8:20: info: initialization of "R" proved
```

Flow analysis complains when a procedure call initializes only some components of a record object. It'll notify you of uninitialized components, as we see in subprogram Init_F2 below.

Listing 14: show_record_flow_analysis.ads

```
package Show Record Flow Analysis is
1
2
      type Rec is record
3
         F1 : Natural;
4
          F2 : Natural;
5
      end record:
6
7
      procedure Init (R : out Rec);
8
      procedure Init_F2 (R : in out Rec);
9
10
   end Show_Record_Flow_Analysis;
11
```

```
Listing 15: show_record_flow_analysis.adb
```

```
package body Show Record Flow Analysis is
1
2
3
      procedure Init_F2
         (R : in out Rec) is
4
5
      begin
         R.F2 := 0;
6
      end Init_F2;
7
8
9
      procedure Init (R : out Rec) is
      begin
10
          R.F1 := 0;
11
          Init_F2 (R); -- R should be initialized before this call
12
13
      end Init;
14
   end Show_Record_Flow_Analysis;
15
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Record_Flow_Analysis_2
MD5: efeecb787bf9d68977ed9701689cd6c4

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
show_record_flow_analysis.adb:12:16: high: "R.F2" is not initialized
gnatprove: unproved check messages considered as errors
```

2.4.3 Value Dependency

Flow analysis is not value-dependent: it never reasons about the values of expressions, only whether they have been set to some value or not. As a consequence, if some execution path in a subprogram is impossible, but the impossibility can only be determined by looking at the values of expressions, flow analysis still considers that path feasible and may emit messages based on it believing that execution along such a path is possible.

For example, in the version of Absolute_Value below, flow analysis computes that R is uninitialized on a path that enters neither of the two conditional statements. Because it doesn't consider values of expressions, it can't know that such a path is impossible.

Listing 16: absolute value.a

```
procedure Absolute Value
1
     (X : Integer;
2
      R : out Natural)
3
   is
4
   beain
5
      if X < 0 then
6
         R := -X;
7
      end if;
8
      if X \ge 0 then
9
         R := X;
10
      end if;
11
      -- flow analysis doesn't know that R is initialized
12
   end Absolute_Value;
13
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Absolute_Value_1
MD5: 69c233d22afdfdac679bf379b353a8d4
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

absolute_value.adb:3:04: medium: "R" might not be initialized in "Absolute_Value"

[reason for check: OUT parameter should be initialized on return] [possible fix:

initialize "R" on all paths or make "R" an IN OUT parameter]

gnatprove: unproved check messages considered as errors
```

To avoid this problem, you should make the control flow explicit, as in this second version of Absolute_Value:

Listing 17: absolute value.adb

```
procedure Absolute_Value
1
     (X : Integer;
2
      R : out Natural)
3
   is
4
   begin
5
      if X < 0 then
6
7
         R := -X;
8
      else
         R := X;
9
      end if;
10
      -- flow analysis knows that R is initialized
11
  end Absolute_Value;
12
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Absolute_Value_2
MD5: 9c773547f81e82a7aa1b45132b105937
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
```

2.4.4 Contract Computation

The final cause of unexpected flow messages that we'll discuss also comes from inaccuracy in computations of contracts. As we explained earlier, both Global and Depends contracts are optional, but GNATprove uses their data for some of its analysis.

For example, flow analysis can't detect reads from uninitialized variables without knowing the set of variables accessed. It needs to analyze and check both the Depends contracts you wrote for a subprogram and those you wrote for callers of that subprogram. Since each flow contract on a subprogram depends on the flow contracts of all the subprograms called inside its body, this computation can often be quite time-consuming. Therefore, flow analysis sometimes trades-off the precision of this computation against the time a more precise computation would take.

This is the case for Depends contracts, where flow analysis simply assumes the worst, that each subprogram's output depends on all of that subprogram's inputs. To avoid this assumption, all you have to do is supply contracts when default ones are not precise enough. You may also want to supply Global contracts to further speed up flow analysis on larger programs.

2.5 Code Examples / Pitfalls

2.5.1 Example #1

The procedure Search_Array searches for an occurrence of element E in an array A. If it finds one, it stores the index of the element in Result. Otherwise, it sets Found to **False**.

Listing 18: show_search_array.ads

```
package Show_Search_Array is
1
2
      type Array_Of_Positives is array (Natural range <>) of Positive;
3
4
      procedure Search Array
5
                       Array_Of_Positives;
        (A
               :
6
         Е
                       Positive;
7
                :
         Result : out Integer;
8
         Found : out Boolean);
9
10
   end Show_Search_Array;
11
```

```
Listing 19: show_search_array.adb
```

```
package body Show_Search_Array is
1
2
      procedure Search_Array
3
                       Array_Of Positives:
        (A
              :
4
         Е
                 :
                       Positive;
5
         Result : out Integer;
6
         Found : out Boolean) is
7
      begin
8
          for I in A'Range loop
9
             if A(I) = E then
10
                Result := I;
11
                Found := True;
12
                return:
13
             end if:
14
         end loop;
15
```

```
Found := False;
end Search_Array;
end Show_Search_Array;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Example_01
MD5: d2a27a5bde247767e2f6cd2d42a2d629
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

show_search_array.ads:8:07: medium: "Result" might not be initialized in "Search_

∴Array" [reason for check: OUT parameter should be initialized on return]

∴ [possible fix: initialize "Result" on all paths or make "Result" an IN OUT

∴ parameter]

gnatprove: unproved check messages considered as errors
```

GNATprove produces a message saying that Result is possibly uninitialized on return. There are perfectly legal uses of the function Search_Array, but flow analysis detects that Result is not initialized on the path that falls through from the loop. Even though this program is correct, you shouldn't ignore the message: it means flow analysis cannot guarantee that Result is always initialized at the call site and so assumes any read of Result at the call site will read initialized data. Therefore, you should either initialize Result when Found is false, which silences flow analysis, or verify this assumption at each call site by other means.

2.5.2 Example #2

To avoid the message previously issued by GNATprove, we modify Search_Array to raise an exception when E isn't found in A:

	Listing 2	20:	show	search	array.ads
--	-----------	-----	------	--------	-----------

```
package Show Search Array is
1
2
      type Array Of Positives is array (Natural range <>) of Positive;
3
4
      Not_Found : exception;
5
6
      procedure Search_Array
7
                       Array_Of_Positives;
         (A
                :
8
                       Positive;
         Е
9
                 1
         Result : out Integer);
10
   end Show_Search_Array;
11
```

Listing 21: show search array.adb

```
package body Show Search Array is
1
2
      procedure Search_Array
3
                      Array_Of_Positives;
4
        (A
                :
         Е
                       Positive;
5
                :
         Result : out Integer) is
6
      begin
7
         for I in A'Range loop
8
```

```
if A(I) = E then
9
                 Result := I;
10
                 return;
11
              end if;
12
          end loop;
13
          raise Not_Found;
14
       end Search_Array;
15
16
   end Show_Search_Array;
17
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Example_02
MD5: fa159faeb68974b1af3de2112e086b16

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_search_array.adb:14:07: medium: exception might be raised
gnatprove: unproved check messages considered as errors
```

Flow analysis doesn't emit any messages in this case, meaning it can verify that Result can't be read in SPARK code while uninitialized. But why is that, since Result is still not initialized when E is not in A? This is because the exception, Not_Found, can never be caught within SPARK code (SPAK doesn't allow exception handlers). However, the GNATprove tool also tries to ensure the absence of runtime errors in SPARK code, so tries to prove that Not_Found is never raised. When it can't do that here, it produces a different message.

2.5.3 Example #3

In this example, we're using a discriminated record for the result of Search_Array instead of conditionally raising an exception. By using such a structure, the place to store the index at which E was found exists only when E was indeed found. So if it wasn't found, there's nothing to be initialized.

```
Listing 22: show_search_array.ads
```

```
package Show Search Array is
1
2
      type Array Of Positives is array (Natural range <>) of Positive;
3
4
      type Search_Result (Found : Boolean := False) is record
5
         case Found is
6
             when True =>
7
                Content : Integer;
8
             when False => null;
9
          end case;
10
      end record;
11
12
13
      procedure Search Array
                       Array_Of_Positives;
         (A
                :
14
                       Positive;
15
         F
                 :
         Result : out Search_Result)
16
      with Pre => not Result'Constrained;
17
18
   end Show_Search_Array;
19
```

Listing 23: show sear	rch array.adb
-----------------------	---------------

```
package body Show_Search_Array is
1
2
      procedure Search Array
3
                      Array Of Positives;
         ( A )
               :
4
          Е
                       Positive;
                 :
5
         Result : out Search Result) is
6
      begin
7
          for I in A'Range loop
8
             if A(I) = E then
9
                Result := (Found
                                   => True,
10
                            Content => I);
11
                return:
12
             end if;
13
          end loop;
14
         Result := (Found => False);
15
      end Search Array;
16
17
   end Show Search Array;
18
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Example_03
MD5: 1d5ec5d78185fd75499b90b3d21f8ae2

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_search_array.adb:10:20: info: discriminant check proved show_search_array.adb:15:14: info: discriminant check proved show_search_array.ads:16:07: info: initialization of "Result" proved

This example is correct and flow analysis doesn't issue any message: it can verify both that no uninitialized variables are read in Search_Array's body, and that all its outputs are set on return. We've used the attribute Constrained in the precondition of Search_Array to indicate that the value of the Result in argument can be set to any variant of the record type Search_Result, specifically to either the variant where E was found and where it wasn't.

2.5.4 Example #4

The function Size_Of_Biggest_Increasing_Sequence is supposed to find all sequences within its parameter A that contain elements with increasing values and returns the length of the longest one. To do this, it calls a nested procedure Test_Index iteratively on all the elements of A. Test_Index checks if the sequence is still increasing. If so, it updates the largest value seen so far in this sequence. If not, it means it's found the end of a sequence, so it computes the size of that sequence and stores it in Size Of Seq.

Listing 24: show_biggest_increasing_sequence.ads

```
package Show_Biggest_Increasing_Sequence is
type Array_Of_Positives is array (Integer range <>) of Positive;
function Size_Of_Biggest_Increasing_Sequence (A : Array_Of_Positives)
return Natural;
```

```
8 end Show_Biggest_Increasing_Sequence;
```

```
Listing 25: show_biggest_increasing_sequence.adb
```

```
package body Show Biggest Increasing Sequence is
1
2
      function Size_Of_Biggest_Increasing_Sequence (A : Array_Of_Positives)
3
          return Natural
4
      is
5
          Max
                       : Natural:
6
          End Of Seq : Boolean;
7
          Size_Of_Seq : Natural;
8
          Beginning
                      : Integer;
9
10
          procedure Test Index (Current Index : Integer) is
11
          begin
12
             if A (Current Index) >= Max then
13
                Max := A (Current Index);
14
                End Of Seq := False;
15
             else
16
                Max
                             := 0;
17
                End_Of_Seq := True;
18
                Size_Of_Seq := Current_Index - Beginning;
19
                Beginning
                             := Current Index;
20
             end if;
21
          end Test Index;
22
23
          Biggest_Seq : Natural := 0;
24
25
      begin
26
          for I in A'Range loop
27
             Test Index (I);
28
             if End_Of_Seq then
29
                Biggest_Seq := Natural'Max (Size_Of_Seq, Biggest_Seq);
30
             end if;
31
          end loop;
32
          return Biggest Seq;
33
      end Size Of Biggest Increasing Sequence;
34
35
   end Show Biggest Increasing Sequence;
36
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Example_04
MD5: e6083665827d9dee4e00bdce4c1e962f
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

show_biggest_increasing_sequence.adb:13:34: medium: "Max" might not be initialized,

in call inlined at show_biggest_increasing_sequence.adb:28

show_biggest_increasing_sequence.adb:19:44: medium: "Beginning" might not be

initialized, in call inlined at show_biggest_increasing_sequence.adb:28

show_biggest_increasing_sequence.adb:30:41: medium: "Size_Of_Seq" might not be

initialized

gnatprove: unproved check messages considered as errors
```

However, this example is not correct. Flow analysis emits messages for Test_Index stating that Max, Beginning, and Size_Of_Seq should be initialized before being read. Indeed,

when you look carefully, you see that both Max and Beginning are missing initializations because they are read in Test_Index before being written. As for Size_Of_Seq, we only read its value when End_Of_Seq is true, so it actually can't be read before being written, but flow analysis isn't able to verify its initialization by using just flow information.

The call to Test_Index is automatically inlined by GNATprove, which leads to another messages above. If GNATprove couldn't inline the call to Test_Index, for example if it was defined in another unit, the same messages would be issued on the call to Test_Index.

2.5.5 Example #5

In the following example, we model permutations as arrays where the element at index I is the position of the I'th element in the permutation. The procedure Init initializes a permutation to the identity, where the I'th elements is at the I'th position. Cyclic_Permutation calls Init and then swaps elements to construct a cyclic permutation.

Listing 26: show permutation.ads

```
package Show Permutation is
1
2
      type Permutation is array (Positive range <>) of Positive;
3
4
                           : in out Permutation;
      procedure Swap (A
5
                       I, J : Positive);
6
7
      procedure Init (A : out Permutation);
8
9
      function Cyclic Permutation (N : Natural) return Permutation;
10
11
   end Show Permutation;
12
```

Listing 27: show_permutation.adb

```
package body Show Permutation is
1
2
      procedure Swap (A
                           : in out Permutation;
3
                       I, J : Positive)
4
5
         Tmp : Positive := A (I);
6
      begin
7
         A(I) := A(J);
8
         A (J) := Tmp;
9
      end Swap;
10
11
      procedure Init (A : out Permutation) is
12
      begin
13
         A (A'First) := A'First;
14
          for I in A'First + 1 .. A'Last loop
15
            A(I) := I;
16
         end loop;
17
      end Init;
18
19
      function Cyclic Permutation (N : Natural) return Permutation is
20
         A : Permutation (1 .. N);
21
      beain
22
          Init (A);
23
          for I in A'First .. A'Last - 1 loop
24
             Swap (A, I, I + 1);
25
          end loop;
26
          return A;
27
```

28 end Cyclic_Permutation;

```
29
30
```

end Show_Permutation;

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Example_05
MD5: 219b06617c636c18543128d77f90fcee
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ... show_permutation.ads:8:20: medium: "A" might not be initialized in "Init" [reason_ ofor check: OUT parameter should be fully initialized on return] [possible fix: oinitialize "A" on all paths, make "A" an IN OUT parameter or annotate it with oaspect Relaxed_Initialization] gnatprove: unproved check messages considered as errors

This program is correct. However, flow analysis will nevertheless still emit messages because it can't verify that every element of A is initialized by the loop in Init. This message is a false alarm. You can either ignore it or justify it safely.

2.5.6 Example #6

This program is the same as the previous one except that we've changed the mode of A in the specification of Init to **in out** to avoid the message from flow analysis on array assignment.

Listing 28: show permutation.ads

```
package Show Permutation is
1
2
      type Permutation is array (Positive range <>) of Positive;
3
4
      procedure Swap (A : in out Permutation;
5
                       I, J : Positive);
6
7
      procedure Init (A : in out Permutation);
8
a
      function Cyclic_Permutation (N : Natural) return Permutation;
10
11
   end Show_Permutation;
12
```

```
Listing 29: show_permutation.adb
```

```
package body Show Permutation is
1
2
      procedure Swap (A
                          : in out Permutation;
3
                       I, J : Positive)
4
      is
5
6
         Tmp : Positive := A (I);
7
      beain
8
         A (I) := A (J);
         A (J) := Tmp;
9
      end Swap;
10
11
      procedure Init (A : in out Permutation) is
12
```

```
begin
13
          A (A'First) := A'First;
14
          for I in A'First + 1 .. A'Last loop
15
             A (I) := I;
16
          end loop;
17
      end Init;
18
19
       function Cyclic_Permutation (N : Natural) return Permutation is
20
          A : Permutation (1 .. N);
21
       begin
22
          Init (A);
23
          for I in A'First .. A'Last - 1 loop
24
25
             Swap (A, I, I + 1);
26
          end loop;
27
          return A;
       end Cyclic_Permutation;
28
29
   end Show_Permutation;
30
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Example_06
MD5: 61406d9a66dda71630c74c12f3d67936

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ... show_permutation.adb:23:13: high: "A" is not initialized gnatprove: unproved check messages considered as errors

This program is not correct. Changing the mode of a parameter that should really be **out** to **in out** to silence a false alarm is not a good idea. Not only does this obfuscate the specification of Init, but flow analysis emits a message on the procedure where A is not initialized, as shown by the message in Cyclic_Permutation.

2.5.7 Example #7

Incr_Step_Function takes an array A as an argument and iterates through A to increment every element by the value of Increment, saturating at a specified threshold value. We specified a Global contract for Incr_Until_Threshold.

```
Listing 30: show_increments.ads
```

```
package Show_Increments is
type Array_Of_Positives is array (Natural range <>) of Positive;
Increment : constant Natural := 10;
procedure Incr_Step_Function (A : in out Array_Of_Positives);
end Show_Increments;
```

Listing 31: show increments.adb

```
package body Show_Increments is
```

```
2
```

```
(continued from previous page)
       procedure Incr_Step_Function (A : in out Array_Of_Positives) is
3
4
          Threshold : Positive := Positive'Last;
5
6
          procedure Incr_Until_Threshold (I : Integer) with
7
            Global => (Input => Threshold,
8
                        In_Out => A);
9
10
          procedure Incr_Until_Threshold (I : Integer) is
11
          begin
12
             if Threshold - Increment <= A (I) then
13
                A (I) := Threshold;
14
             else
15
                A (I) := A (I) + Increment;
16
17
             end if;
          end Incr_Until_Threshold;
18
19
       begin
20
          for I in A'Range loop
21
             if I > A'First then
22
                Threshold := A (I - 1);
23
             end if;
24
             Incr_Until_Threshold (I);
25
          end loop;
26
       end Incr_Step_Function;
27
28
   end Show_Increments;
29
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Example_07
MD5: 8e28a005cd9d78947e4bfc60db708bf5

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ... show increments.adb:8:09: info: data dependencies proved

Everything is fine here. Specifically, the Global contract is correct. It mentions both Threshold, which is read but not written in the procedure, and A, which is both read and written. The fact that A is a parameter of an enclosing unit doesn't prevent us from using it inside the Global contract; it really is global to Incr_Until_Threshold. We didn't mention Increment since it's a static constant.

2.5.8 Example #8

We now go back to the procedure Test_Index from *Example #4* (page 36) and correct the missing initializations. We want to know if the Global contract of Test_Index is correct.

Listing 32: show_biggest_increasing_sequence.ads

```
package Show_Biggest_Increasing_Sequence is
type Array_Of_Positives is array (Integer range <>) of Positive;
function Size_Of_Biggest_Increasing_Sequence (A : Array_Of_Positives)
return Natural;
```

```
8 end Show_Biggest_Increasing_Sequence;
```

Listing 33: show biggest increasing sequence.adb

```
package body Show Biggest Increasing Sequence is
1
2
      function Size_Of_Biggest_Increasing_Sequence (A : Array_Of_Positives)
3
          return Natural
4
      is
5
                       : Natural := 0;
         Max
6
         End_Of_Seq : Boolean;
7
          Size_Of_Seq : Natural := 0;
8
          Beginning
                      : Integer := A'First - 1;
9
10
          procedure Test Index (Current Index : Integer) with
11
            Global => (In Out => (Beginning, Max, Size Of Seq),
12
                        Output => End Of Seq,
13
                        Input => Current_Index)
14
          is
15
          begin
16
             if A (Current_Index) >= Max then
17
                Max := A (Current_Index);
18
                End_Of_Seq := False;
19
             else
20
                Max
                             := 0;
21
                End Of Seg := True;
22
                Size_Of_Seq := Current_Index - Beginning;
23
                Beginning
                             := Current_Index;
24
25
             end if;
         end Test_Index;
26
27
          Biggest_Seq : Natural := 0;
28
29
      beain
30
          for I in A'Range loop
31
             Test Index (I);
32
             if End Of Seq then
33
                Biggest Seq := Natural'Max (Size Of Seq, Biggest Seq);
34
             end if;
35
          end loop;
36
          return Biggest_Seq;
37
      end Size_Of_Biggest_Increasing_Sequence;
38
39
   end Show_Biggest_Increasing_Sequence;
40
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Example_08
MD5: 86fb934c32a38f6841ef736780b2e3b2

Prover output

```
Phase 1 of 2: generation of Global contracts ...
show_biggest_increasing_sequence.adb:14:30: error: global item cannot reference
□ aparameter of subprogram "Test_Index"
gnatprove: error during generation of Global contracts
```

The contract in this example is not correct: Current_Index is a parameter of Test_Index, so we shouldn't reference it as a global variable. Also, we should have listed variable A from the outer scope as an Input in the Global contract.

2.5.9 Example #9

1 2

4

5

7

8

Next, we change the Global contract of Test_Index into a Depends contract. In general, we don't need both contracts because the set of global variables accessed can be deduced from the Depends contract.

```
Listing 34: show biggest increasing sequence.ads
```

```
package Show_Biggest_Increasing_Sequence is
      type Array Of Positives is array (Integer range <>) of Positive;
3
      function Size Of Biggest Increasing Sequence (A : Array Of Positives)
         return Natural;
6
```

```
end Show Biggest Increasing Sequence;
```

```
Listing 35: show biggest increasing sequence.adb
```

```
package body Show Biggest Increasing Sequence is
1
2
      function Size Of Biggest Increasing Sequence (A : Array Of Positives)
3
          return Natural
4
      is
5
         Max
                      : Natural := 0;
6
          End Of Seq : Boolean;
7
          Size_Of_Seq : Natural := 0;
8
                      : Integer := A'First - 1;
          Beginning
9
10
          procedure Test_Index (Current_Index : Integer) with
11
            Depends => ((Max, End_Of_Seq)
                                                    => (A, Current Index, Max),
12
                         (Size_Of_Seq, Beginning) =>
13
                            + (A, Current_Index, Max, Beginning))
14
          is
15
          begin
16
             if A (Current Index) >= Max then
17
                Max := A (Current_Index);
18
                End_Of_Seq := False;
19
             else
20
                             := 0;
                Max
21
                End Of Seq := True;
22
                Size_Of_Seq := Current_Index - Beginning;
23
                             := Current_Index;
                Beginning
24
             end if;
25
          end Test_Index;
26
27
          Biggest_Seq : Natural := 0;
28
29
      begin
30
          for I in A'Range loop
31
             Test_Index (I);
32
             if End Of Seq then
33
                Biggest_Seq := Natural'Max (Size_Of_Seq, Biggest Seq);
34
             end if;
35
          end loop;
36
          return Biggest_Seq;
37
      end Size_Of_Biggest_Increasing_Sequence;
38
39
   end Show_Biggest_Increasing_Sequence;
40
```

Code block metadata

Project: Courses.Intro_To_Spark.Flow_Analysis.Example_09
MD5: d54ac5d4266738b1bf64869131644b33

Prover output

This example is correct. Some of the dependencies, such as Size_Of_Seq depending on Beginning, come directly from the assignments in the subprogram. Since the control flow influences the final value of all of the outputs, the variables that are being read, A, Current_Index, and Max, are present in every dependency relation. Finally, the dependencies of Size_Of_Eq and Beginning on themselves are because they may not be modified by the subprogram execution.

2.5.10 Example #10

The subprogram Identity swaps the value of its parameter two times. Its Depends contract says that the final value of X only depends on its initial value and likewise for Y.

Listing 36: show swap.ads

Listing 37: show_swap.adb

```
package body Show_Swap is
1
2
       procedure Swap (X, Y : in out Positive) is
3
         Tmp : constant Positive := X;
4
      begin
5
          X := Y;
6
          Y := Tmp;
7
      end Swap;
8
9
      procedure Identity (X, Y : in out Positive) is
10
      begin
11
          Swap (X, Y);
12
          Swap (Y, X);
13
      end Identity;
14
15
   end Show_Swap;
16
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Flow_Analysis.Example_10
MD5: 8567ece1e5bbc190f62dd483785d078a
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ... show_swap.ads:6:18: medium: missing dependency "X => Y" show_swap.ads:7:18: medium: missing dependency "Y => X" gnatprove: unproved check messages considered as errors

This code is correct, but flow analysis can't verify the Depends contract of Identity because we didn't supply a Depends contract for Swap. Therefore, flow analysis assumes that all outputs of Swap, X and Y, depend on all its inputs, both X and Y's initial values. To prevent this, we should manually specify a Depends contract for Swap.

PROOF OF PROGRAM INTEGRITY

This section presents the proof capability of GNATprove, a major tool for the SPARK language. We focus here on the simpler proofs that you'll need to write to verify your program's integrity. The primary objective of performing proof of your program's integrity is to ensure the absence of runtime errors during its execution.

The analysis steps discussed here are only sound if you've previously performed *Flow Analysis* (page 21). You shouldn't proceed further if you still have unjustified flow analysis messages for your program.

3.1 Runtime Errors

There's always the potential for errors that aren't detected during compilation to occur during a program's execution. These errors, called runtime errors, are those targeted by GNATprove.

There are various kinds of runtime errors, the most common being references that are out of the range of an array (buffer overflow¹³ in Ada), subtype range violations, overflows in computations, and divisions by zero. The code below illustrates many examples of possible runtime errors, all within a single statement. Look at the assignment statement setting the I + J'th cell of an array A to the value P /Q.

Listing 1: show_runtime_errors.ads

```
package Show_Runtime_Errors is
type Nat_Array is array (Integer range <>) of Natural;
procedure Update (A : in out Nat_Array; I, J, P, Q : Integer);
end Show_Runtime_Errors;
```

Listing 2: show_runtime_errors.adb

```
package body Show_Runtime_Errors is
procedure Update (A : in out Nat_Array; I, J, P, Q : Integer) is
begin
A (I + J) := P / Q;
end Update;
end Show Runtime Errors;
```

Code block metadata

¹³ https://en.wikipedia.org/wiki/Buffer_overflow

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Runtime_Errors
MD5: c0718b8cb6138b84a99e0040e2a9164e

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show runtime errors.adb:5:12: medium: overflow check might fail, cannot prove \rightarrow lower bound for I + J [reason for check: result of addition must fit in a 32- \rightarrow bits machine integer] [possible fix: add precondition (if J >= 0 then I <=, →Integer'Last - J else I >= Integer'First - J) to subprogram at show runtime ⊶errors.ads:51 show runtime errors.adb:5:12: medium: array index check might fail [reason for... -check: result of addition must be a valid index into the array [possible fix:... add precondition (if J >= 0 then I <= A'Last - J else I >= A'First - J) to, →subprogram at show runtime errors.ads:5] show runtime errors.adb:5:22: medium: divide by zero might fail [possible fix: add, \ominus precondition (Q /= 0) to subprogram at show runtime errors.ads:5] show runtime errors.adb:5:22: medium: overflow check might fail, cannot prove, $_{\rm \ominus} lower$ bound for P / Q [reason for check: result of division must fit in a 32-→bits machine integer] [possible fix: add precondition (P / Q in Integer) to, →subprogram at show runtime errors.ads:5] show_runtime_errors.adb:5:22: medium: range check might fail, cannot prove lower →bound for P / Q [reason for check: result of division must fit in the target, $_{-}$ type of the assignment] [possible fix: add precondition (P / Q in Natural) to, subprogram at show_runtime_errors.ads:5] gnatprove: unproved check messages considered as errors

There are quite a number of errors that may occur when executing this code. If we don't know anything about the values of I, J, P, and Q, we can't rule out any of those errors.

First, the computation of I + J can overflow, for example if I is **Integer**'Last and J is positive.

A (**Integer**'Last + 1) := P / Q;

Next, the sum, which is used as an array index, may not be in the range of the index of the array.

A (A'Last + 1) := P / Q;

On the other side of the assignment, the division may also overflow, though only in the very special case where P is **Integer**'First and Q is -1 because of the asymmetric range of signed integer types.

A (I + J) := Integer'First / -1;

The division is also not allowed if Q is 0.

A (I + J) := P / 0;

Finally, since the array contains natural numbers, it's also an error to store a negative value in it.

A (I + J) := 1 / -1;

The compiler generates checks in the executable code corresponding to each of those runtime errors. Each check raises an exception if it fails. For the above assignment statement, we can see examples of exceptions raised due to failed checks for each of the different cases above.

```
A (Integer'Last + 1) := P / Q;
-- raised CONSTRAINT_ERROR : overflow check failed
A (A'Last + 1) := P / Q;
-- raised CONSTRAINT_ERROR : index check failed
A (I + J) := Integer'First / (-1);
-- raised CONSTRAINT_ERROR : overflow check failed
A (I + J) := 1 / (-1);
-- raised CONSTRAINT_ERROR : range check failed
A (I + J) := P / 0;
-- raised CONSTRAINT ERROR : divide by zero
```

These runtime checks are costly, both in terms of program size and execution time. It may be appropriate to remove them if we can statically ensure they aren't needed at runtime, in other words if we can prove that the condition tested for can never occur.

This is where the analysis done by GNATprove comes in. It can be used to demonstrate statically that none of these errors can ever occur at runtime. Specifically, GNATprove logically interprets the meaning of every instruction in the program. Using this interpretation, GNATprove generates a logical formula called a *verification condition* for each check that would otherwise be required by the Ada (and hence SPARK) language.

```
A (Integer'Last + 1) := P / Q;
-- medium: overflow check might fail
A (A'Last + 1) := P / Q;
-- medium: array index check might fail
A (I + J) := Integer'First / (-1);
-- medium: overflow check might fail
A (I + J) := 1 / (-1);
-- medium: range check might fail
A (I + J) := P / 0;
-- medium: divide by zero might fail
```

GNATprove then passes these verification conditions to an automatic prover, stated as conditions that must be true to avoid the error. If every such condition can be validated by a prover (meaning that it can be mathematically shown to always be true), we've been able to prove that no error can ever be raised at runtime when executing that program.

3.2 Modularity

To scale to large programs, GNATprove performs proofs on a per-subprogram basis by relying on preconditions and postconditions to properly summarize the input and output state of each subprogram. More precisely, when verifying the body of a subprogram, GNATprove assumes it knows nothing about the possible initial values of its parameters and of the global variables it accesses except what you state in the subprogram's precondition. If you don't specify a precondition, it can't make any assumptions.

For example, the following code shows that the body of Increment can be successfully verified: its precondition constrains the value of its parameter X to be less than Integer'Last so we know the overflow check is always false. In the same way, when a subprogram is called, GNATprove assumes its **out** and **in out** parameters and the global variables it writes can be modified in any way compatible with their postconditions. For example, since Increment has no postcondition, GNATprove doesn't know that the value of X after the call is always less than **Integer**'Last. Therefore, it can't prove that the addition following the call to Increment can't overflow.

```
Listing 3: show_modularity.adb
```

```
procedure Show Modularity is
1
2
      procedure Increment (X : in out Integer) with
3
        Pre => X < Integer'Last is</pre>
4
      begin
5
         X := X + 1;
6
          -- info: overflow check proved
7
      end Increment;
8
9
      X : Integer;
10
   begin
11
      X := Integer'Last - 2;
12
      Increment (X);
13
       -- After the call, GNATprove no longer knows the value of X
14
15
      X := X + 1:
16
      -- medium: overflow check might fail
17
   end Show_Modularity;
18
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Modularity_1
MD5: ca8ff8d29792fd5a06f7cb0158e13689

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_modularity.adb:6:14: info: overflow check proved
show_modularity.adb:10:04: info: initialization of "X" proved
show_modularity.adb:13:04: info: precondition proved
show_modularity.adb:16:11: medium: overflow check might fail, cannot prove upper_____bound for X + 1 [reason for check: result of addition must fit in a 32-bits______machine integer] [possible fix: call at line 13 should mention X (for argument______X) in a postcondition]
gnatprove: unproved check messages considered as errors
```

3.2.1 Exceptions

There are two cases where GNATprove doesn't require modularity and hence doesn't make the above assumptions. First, local subprograms without contracts can be inlined if they're simple enough and are neither recursive nor have multiple return points. If we remove the contract from Increment, it fits the criteria for inlining.

Listing 4: show_modularity.adb

```
end Increment;
7
8
      X : Integer;
9
   beain
10
      X := Integer'Last - 2;
11
      Increment (X);
12
      X := X + 1;
13
       -- info: overflow check proved
14
   end Show_Modularity;
15
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Modularity_2
MD5: 448d576897c3e4606cd4b90621aad63a

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

show_modularity.adb:5:14: info: overflow check proved, in call inlined at show_

Generation of "X" proved

show_modularity.adb:9:04: info: initialization of "X" proved

show_modularity.adb:13:11: info: overflow check proved
```

GNATprove now sees the call to Increment exactly as if the increment on X was done outside that call, so it can successfully verify that neither addition can overflow.

Note: For more details on contextual analysis of subprograms, see the SPARK User's Guide¹⁴.

The other case involves functions. If we define a function as an expression function, with or without contracts, GNATprove uses the expression itself as the postcondition on the result of the function.

In our example, replacing Increment with an expression function allows GNATprove to successfully verify the overflow check in the addition.

Listing 5: show modularity.adb

```
procedure Show Modularity is
1
2
      function Increment (X : Integer) return Integer is
3
         (X + 1)
4
            info: overflow check proved
5
        with Pre => X < Integer'Last;</pre>
6
7
      X : Integer;
8
   begin
9
      X := Integer'Last - 2;
10
      X := Increment (X);
11
      X := X + 1;
12
13
       -- info: overflow check proved
   end Show Modularity;
14
```

Code block metadata

¹⁴ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/how_to_write_subprogram_ contracts.html#contextual-analysis-of-subprograms-without-contracts

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Modularity_3
MD5: b2b67845362929472e4e23867fcbd5e7

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_modularity.adb:4:09: info: overflow check proved show_modularity.adb:8:04: info: initialization of "X" proved show_modularity.adb:11:09: info: precondition proved show_modularity.adb:12:11: info: overflow check proved

Note: For more details on expression functions, see the SPARK User's Guide¹⁵.

3.3 Contracts

Ada contracts are perfectly suited for formal verification, but are primarily designed to be checked at runtime. When you specify the -gnata switch, the compiler generates code that verifies the contracts at runtime. If an Ada contract isn't satisfied for a given subprogram call, the program raises the Assert_Failure exception. This switch is particularly useful during development and testing, but you may also retain run-time execution of assertions, and specifically preconditions, during the program's deployment to avoid an inconsistent state.

Consider the incorrect call to Increment below, which violates its precondition. One way to detect this error is by compiling the function with assertions enabled and testing it with inputs that trigger the violation. Another way, one that doesn't require guessing the needed inputs, is to run GNATprove.

Listing 6: show_precondition_violation.adb

```
procedure Show Precondition Violation is
1
2
       procedure Increment (X : in out Integer) with
3
         Pre => X < Integer'Last is</pre>
4
       beain
5
         X := X + 1;
6
      end Increment;
7
8
      X : Integer;
9
10
   begin
11
      X := Integer'Last;
12
      Increment (X);
13
   end Show_Precondition_Violation;
14
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Precondition_Violation
MD5: 60cb889128fc6bca10e21b1baf041258
```

Prover output

¹⁵ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/specification_features.html# expression-functions

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_precondition_violation.adb:13:04: medium: precondition might fail
gnatprove: unproved check messages considered as errors
```

Runtime output

```
raised ADA.ASSERTIONS.ASSERTION_ERROR : failed precondition from show_precondition_

⇔violation.adb:4
```

Similarly, consider the incorrect implementation of function Absolute below, which violates its postcondition. Likewise, one way to detect this error is by compiling the function with assertions enabled and testing with inputs that trigger the violation. Another way, one which again doesn't require finding the inputs needed to demonstrate the error, is to run GNATprove.

Listing 7: show_postcondition_violation.adb

```
procedure Show Postcondition Violation is
1
2
      procedure Absolute (X : in out Integer) with
3
         Post => X >= 0 is
4
      begin
5
          if X > 0 then
6
             X := -X:
7
          end if:
8
      end Absolute;
9
10
      X : Integer;
11
12
   begin
13
      X := 1;
14
      Absolute (X);
15
   end Show_Postcondition_Violation;
16
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Postcondition_Violation
MD5: fb1340de7e082d801f177bd8a0cf90a6

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_postcondition_violation.adb:4:14: medium: postcondition might fail gnatprove: unproved check messages considered as errors

Runtime output

The benefits of dynamically checking contracts extends beyond making testing easier. Early failure detection also allows an easier recovery and facilitates debugging, so you may want to enable these checks at runtime to terminate execution before some damaging or hard-to-debug action occurs.

GNATprove statically analyses preconditions and postconditions. It verifies preconditions every time a subprogram is called, which is the runtime semantics of contracts. Postconditions, on the other hand, are verified once as part of the verification of the subprogram's

body. For example, GNATprove must wait until Increment is improperly called to detect the precondition violation, since a precondition is really a contract for the caller. On the other hand, it doesn't need Absolute to be called to detect that its postcondition doesn't hold for all its possible inputs.

Note: For more details on pre and postconditions, see the SPARK User's Guide¹⁶.

3.3.1 Executable Semantics

Expressions in Ada contracts have the same semantics as Boolean expressions elsewhere, so runtime errors can occur during their computation. To simplify both debugging of assertions and combining testing and static verification, the same semantics are used by GNATprove.

While proving programs, GNATprove verifies that no error can ever be raised during the execution of the contracts. However, you may sometimes find those semantics too heavy, in particular with respect to overflow checks, because they can make it harder to specify an appropriate precondition. We see this in the function Add below.

Listing 8: show executable semantics.adb

```
procedure Show_Executable_Semantics
1
     with SPARK Mode => On
2
   is
3
      function Add (X, Y : Integer) return Integer is (X + Y)
4
        with Pre => X + Y in Integer;
5
6
      X : Integer;
7
   begin
8
      X := Add (Integer'Last, 1);
9
  end Show Executable Semantics;
10
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Executable_Semantics
MD5: d85fa0507d7c35fb98ade7815020117e

Build output

```
show_executable_semantics.adb:5:24: warning: explicit membership test may be_

optimized away [enabled by default]

show_executable_semantics.adb:5:24: warning: use 'Valid attribute instead [enabled_

oby default]
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_executable_semantics.adb:5:20: medium: overflow check might fail, cannot_____prove lower bound for X + Y [reason for check: result of addition must fit in a_____32-bits machine integer] [possible fix: use pragma Overflow_Mode or switch -____gnato13 or unit Ada.Numerics.Big_Numerics.Big_Integers]
show_executable_semantics.adb:9:09: medium: precondition might fail, cannot prove_____upper bound for Add (Integer'Last, 1)
gnatprove: unproved check messages considered as errors
```

Runtime output

 $^{16}\ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/subprogram_contracts.html \# preconditions$

raised CONSTRAINT_ERROR : show_executable_semantics.adb:5 overflow check failed

GNATprove issues a message on this code warning about a possible overflow when computing the sum of X and Y in the precondition. Indeed, since expressions in assertions have normal Ada semantics, this addition can overflow, as you can easily see by compiling and running the code that calls Add with arguments **Integer**'Last and 1.

On the other hand, you sometimes may prefer GNATprove to use the mathematical semantics of addition in contracts while the generated code still properly verifies that no error is ever raised at runtime in the body of the program. You can get this behavior by using the compiler switch -gnato?? (for example -gnato13), which allows you to independently set the overflow mode in code (the first digit) and assertions (the second digit). For both, you can either reduce the number of overflow checks (the value 2), completely eliminate them (the value 3), or preserve the default Ada semantics (the value 1).

Note: For more details on overflow modes, see the SPARK User's Guide¹⁷.

3.3.2 Additional Assertions and Contracts

As we've seen, a key feature of SPARK is that it allows us to state properties to check using assertions and contracts. SPARK supports preconditions and postconditions as well as assertions introduced by the Assert pragma.

The SPARK language also includes new contract types used to assist formal verification. The new pragma Assume is treated as an assertion during execution but introduces an assumption when proving programs. Its value is a Boolean expression which GNATprove assumes to be true without any attempt to verify that it's true. You'll find this feature useful, but you must use it with great care. Here's an example of using it.

Listing 9: incr.adb

```
1 procedure Incr (X : in out Integer) is
2 begin
3 pragma Assume (X < Integer'Last);
4 X := X + 1;
5 end Incr;</pre>
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Pragma_Assume
MD5: bfbc4b8aca259d7516b6acaee571f8c2

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
incr.adb:4:11: info: overflow check proved
```

Note: For more details on pragma Assume, see the SPARK User's Guide¹⁸.

The Contract_Cases aspect is another construct introduced for GNATprove, but which also acts as an assertion during execution. It allows you to specify the behavior of a subprogram

¹⁷ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/overflow_modes.html ¹⁸ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/assertion_pragmas.html# pragma-assume

using a disjunction of cases. Each element of a Contract_Cases aspect is a *guard*, which is evaluated before the call and may only reference the subprogram's inputs, and a *consequence*. At each call of the subprogram, one and only one guard is permitted to evaluate to **True**. The consequence of that case is a contract that's required to be satisfied when the subprogram returns.

```
Listing 10: absolute.adb
```

```
procedure Absolute (X : in out Integer) with
1
                     => X > Integer'First,
2
     Pre
     Contract_Cases => (X < 0 => X = -X'Old,
3
                         X >= 0 => X = X'0ld
4
   is
5
   begin
6
      if X < 0 then
7
         X := -X;
8
      end if;
9
  end Absolute;
10
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Absolute
MD5: 5ac868f35be18bb6fffe2444ecbea28d

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
absolute.adb:3:03: info: disjoint contract cases proved
absolute.adb:3:03: info: complete contract cases proved
absolute.adb:3:29: info: contract case proved
absolute.adb:3:36: info: overflow check proved
absolute.adb:4:29: info: contract case proved
absolute.adb:8:12: info: overflow check proved
```

Similarly to how it analyzes a subprogram's precondition, GNATprove verifies the Contract_Cases only once. It verifies the validity of each consequence (given the truth of its guard) and the disjointness and completeness of the guard conditions (meaning that exactly one guard must be true for each possible set of input values).

Note: For more details on Contract_Cases, see the SPARK User's Guide¹⁹.

3.4 Debugging Failed Proof Attempts

GNATprove may report an error while verifying a program for any of the following reasons:

- there might be an error in the program; or
- the property may not be provable as written because more information is required; or
- the prover used by GNATprove may be unable to prove a perfectly valid property.

We spend the remainder of this section discussing the sometimes tricky task of debugging failed proof attempts.

¹⁹ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/subprogram_contracts.html# contract-cases

3.4.1 Debugging Errors in Code or Specification

First, let's discuss the case where there's indeed an error in the program. There are two possibilities: the code may be incorrect or, equally likely, the specification may be incorrect. As an example, there's an error in our procedure Incr_Until below which makes its Contract_Cases unprovable.

Listing 11: show_failed_proof_attempt.ads

```
package Show Failed Proof Attempt is
1
2
      Incremented : Boolean := False;
3
4
      procedure Incr Until (X : in out Natural) with
5
         Contract Cases =>
6
           (Incremented = X > X' Old,
7
            others
                        => X = X'Old);
8
9
   end Show Failed Proof Attempt;
10
```

Listing 12: show_failed_proof_attempt.adb

```
package body Show_Failed_Proof_Attempt is
1
2
      procedure Incr_Until (X : in out Natural) is
3
      begin
4
         if X < 1000 then
5
             X := X + 1;
6
             Incremented := True;
7
          else
8
             Incremented := False;
9
         end if;
10
      end Incr_Until;
11
12
   end Show Failed Proof Attempt;
13
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Failed_Proof_Attempt_1
MD5: 814636ae9df6f4f66ad69f5099a5729b

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_failed_proof_attempt.ads:7:21: medium: contract case might fail
show_failed_proof_attempt.ads:8:21: medium: contract case might fail
gnatprove: unproved check messages considered as errors
```

Since this is an assertion that can be executed, it may help you find the problem if you run the program with assertions enabled on representative sets of inputs. This allows you to find bugs in both the code and its contracts. In this case, testing Incr_Until with an input greater than 1000 raises an exception at runtime.

Listing 13: show_failed_proof_attempt.ads

```
package Show_Failed_Proof_Attempt is
Incremented : Boolean := False;
procedure Incr_Until (X : in out Natural) with
```

```
6 Contract_Cases =>
7 (Incremented => X > X'Old,
8 others => X = X'Old);
9
10 end Show_Failed_Proof_Attempt;
```

Listing 14: show_failed_proof_attempt.adb

```
package body Show Failed Proof Attempt is
1
2
      procedure Incr_Until (X : in out Natural) is
3
      begin
4
         if X < 1000 then
5
             X := X + 1:
6
             Incremented := True;
7
          else
8
             Incremented := False;
9
          end if;
10
      end Incr_Until;
11
12
   end Show_Failed_Proof_Attempt;
13
```

Listing 15: main.adb

```
with Show_Failed_Proof_Attempt; use Show_Failed_Proof_Attempt;
1
2
   procedure Main is
3
      Dummy : Integer;
4
   begin
5
      Dummy := 0;
6
      Incr_Until (Dummy);
7
8
9
      Dummy := 1000;
      Incr_Until (Dummy);
10
   end Main;
11
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Failed_Proof_Attempt_2
MD5: bd87cb0f64a6468eaab3cad1678271db

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_failed_proof_attempt.ads:7:21: medium: contract case might fail
show_failed_proof_attempt.ads:8:21: medium: contract case might fail
gnatprove: unproved check messages considered as errors
```

Runtime output

The error message shows that the first contract case is failing, which means that Incremented is **True**. However, if we print the value of Incremented before returning, we see that it's **False**, as expected for the input we provided. The error here is that guards of contract cases are evaluated before the call, so our specification is wrong! To correct this, we should either write X < 1000 as the guard of the first case or use a standard postcondition with an if-expression.

3.4.2 Debugging Cases where more Information is Required

Even if both the code and the assertions are correct, GNATprove may still report that it can't prove a verification condition for a property. This can happen for two reasons:

- The property may be unprovable because the code is missing some assertion. One category of these cases is due to the modularity of the analysis which, as we discussed above, means that GNATprove only knows about the properties of your subprograms that you have explicitly written.
- There may be some information missing in the logical model of the program used by GNATprove.

Let's look at the case where the code and the specification are correct but there's some information missing. As an example, GNATprove finds the postcondition of Increase to be unprovable.

Listing 16: show failed proof attempt.ads

```
package Show Failed Proof Attempt is
1
2
      C : Natural := 100;
3
4
      procedure Increase (X : in out Natural) with
5
         Post => (if X'Old < C then X > X'Old else X = C);
6
7
   end Show Failed Proof Attempt;
8
```

Listing 17: show failed proof attempt.adb

```
package body Show_Failed_Proof_Attempt is
1
2
      procedure Increase (X : in out Natural) is
3
      begin
4
          if X < 90 then
5
             X := X + 10;
6
          elsif X >= C then
7
             X := C;
8
          else
9
             X := X + 1;
10
          end if;
11
      end Increase;
12
13
   end Show_Failed_Proof_Attempt;
```

Code block metadata

Project: Courses.Intro To Spark.Proof of Program Integrity.Failed Proof Attempt 3 MD5: e01fc27a981bcb80757f30c94768237e

Prover output

14

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_failed_proof_attempt.ads:6:49: medium: postcondition might fail, cannot prove_ X = Cgnatprove: unproved check messages considered as errors

This postcondition is a conditional. It says that if the parameter (X) is less than a certain value (C), its value will be increased by the procedure while if it's greater, its value will be set to C (saturated). When C has the value 100, the code of Increases adds 10 to the value of X if it was initially less than 90, increments X by 1 if it was between 90 and 99, and sets

X to 100 if it was greater or equal to 100. This behavior does satisfy the postcondition, so why is the postcondition not provable?

The values in the counterexample returned by GNATprove in its message gives us a clue: C = 0 and X = 10 and X'Old = 0. Indeed, if C is not equal to 100, our reasoning above is incorrect: the values of 0 for C and X on entry indeed result in X being 10 on exit, which violates the postcondition!

We probably didn't expect the value of C to change, or at least not to go below 90. But, in that case, we should have stated so by either declaring C to be constant or by adding a precondition to the Increase subprogram. If we do either of those, GNATprove is able to prove the postcondition.

3.4.3 Debugging Prover Limitations

Finally, there are cases where GNATprove provides a perfectly valid verification condition for a property, but it's nevertheless not proved by the automatic prover that runs in the later stages of the tool's execution. This is quite common. Indeed, GNATprove produces its verification conditions in first-order logic, which is not decidable, especially in combination with the rules of arithmetic. Sometimes, the automatic prover just needs more time. Other times, the prover will abandon the search almost immediately or loop forever without reaching a conclusive answer (either a proof or a counterexample).

For example, the postcondition of our GCD function below — which calculates the value of the GCD of two positive numbers using Euclide's algorithm — can't be verified with GNATprove's default settings.

Listing	18:	show	failed	proof	attem	pt.ads

```
package Show_Failed_Proof_Attempt is
function GCD (A, B : Positive) return Positive with
Post =>
A mod GCD'Result = 0
and B mod GCD'Result = 0;
end Show_Failed_Proof_Attempt;
```

Listing 19: show_failed_proof_attempt.adb

```
package body Show Failed Proof Attempt is
1
2
      function GCD (A, B : Positive) return Positive is
3
      begin
4
         if A > B then
5
            return GCD (A - B, B);
6
         elsif B > A then
7
            return GCD (A, B - A);
8
         else
9
             return A;
10
         end if;
11
      end GCD;
12
13
   end Show Failed Proof Attempt;
14
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Failed_Proof_Attempt_4
MD5: a6f1a39ceb0793df8a00691d59a5d9ce
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_failed_proof_attempt.ads:5:08: medium: postcondition might fail, cannot prove_ ⇔A mod GCD'Result = 0 gnatprove: unproved check messages considered as errors

The first thing we try is increasing the amount of time the prover is allowed to spend on each verification condition using the --timeout option of GNATprove (e.g., by using the dialog box in GNAT Studio). In this example, increasing it to one minute, which is relatively high, doesn't help. We can also specify an alternative automatic prover — if we have one — using the option --prover of GNATprove (or the dialog box). For our postcondition, we tried Alt-Ergo, cvc5, and Z3 without any luck.

Listing 20: show_failed_proof_attempt.ads

```
package Show_Failed_Proof_Attempt is
function GCD (A, B : Positive) return Positive with
Post =>
A mod GCD'Result = 0
and B mod GCD'Result = 0;
end Show_Failed_Proof_Attempt;
```

Listing 21: show_failed_proof_attempt.adb

```
package body Show_Failed_Proof_Attempt is
1
2
      function GCD (A, B : Positive) return Positive
3
      is
4
          Result : Positive;
5
      begin
6
          if A > B then
7
             Result := GCD (A - B, B);
8
             pragma Assert ((A - B) mod Result = 0);
9
             -- info: assertion proved
10
             pragma Assert (B mod Result = 0);
11
             -- info: assertion proved
12
             pragma Assert (A mod Result = 0);
13
             -- medium: assertion might fail
14
          elsif B > A then
15
             Result := GCD (A, B - A);
16
             pragma Assert ((B - A) mod Result = 0);
17
             -- info: assertion proved
18
          else
19
             Result := A;
20
          end if;
21
          return Result;
22
      end GCD;
23
24
   end Show Failed Proof Attempt;
25
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Failed_Proof_Attempt_5
MD5: 954ecbf2177705770c3a44a477c1de17

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ...

```
(continued from previous page)
show_failed_proof_attempt.adb:5:07: info: initialization of "Result" proved
show_failed_proof_attempt.adb:8:27: info: range check proved
show_failed_proof_attempt.adb:9:25: info: assertion proved
show_failed_proof_attempt.adb:9:33: info: division check proved
show_failed_proof_attempt.adb:11:25: info: assertion proved
show_failed_proof_attempt.adb:11:27: info: division check proved
show_failed_proof_attempt.adb:13:25: medium: assertion might fail [possible fix:_
 subprogram at show_failed_proof_attempt.ads:3 should mention A in a precondition]
show_failed_proof_attempt.adb:13:27: info: division check proved
show_failed_proof_attempt.adb:16:30: info: range check proved
show_failed_proof_attempt.adb:17:25: info: assertion proved
show_failed_proof_attempt.adb:17:33: info: division check proved
show_failed_proof_attempt.ads:5:10: info: division check proved
show failed proof attempt.ads:6:12: medium: postcondition might fail, cannot prove
 \rightarrowB mod GCD'Result = 0
show_failed_proof_attempt.ads:6:14: info: division check proved
gnatprove: unproved check messages considered as errors
```

To better understand the reason for the failure, we added intermediate assertions to simplify the proof and pin down the part that's causing the problem. Adding such assertions is often a good idea when trying to understand why a property is not proved. Here, provers can't verify that if both A - B and B can be divided by Result so can A. This may seem surprising, but non-linear arithmetic, involving, for example, multiplication, modulo, or exponentiation, is a difficult topic for provers and is not handled very well in practice by any of the generalpurpose ones like Alt-Ergo, cvc5, or Z3.

Note: For more details on how to investigate unproved checks, see the SPARK User's Guide²⁰.

3.5 Code Examples / Pitfalls

We end with some code examples and pitfalls.

3.5.1 Example #1

The package Lists defines a linked-list data structure. We call Link(I,J) to make a link from index I to index J and call Goes_To(I,J) to determine if we've created a link from index I to index J. The postcondition of Link uses Goes_To to state that there must be a link between its arguments once Link completes.

```
Listing 22: lists.ads
```

```
package Lists with SPARK_Mode is
type Index is new Integer;
function Goes_To (I, J : Index) return Boolean;
procedure Link (I, J : Index) with Post => Goes_To (I, J);
private
```

²⁰ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/how_to_investigate_unproved_checks.html

```
10
       type Cell (Is_Set : Boolean := True) is record
11
          case Is_Set is
12
             when True =>
13
                 Next : Index;
14
             when False =>
15
                null;
16
          end case;
17
       end record;
18
19
       type Cell_Array is array (Index) of Cell;
20
21
       Memory : Cell_Array;
22
23
   end Lists;
24
```

Listing 23: lists.adb

```
package body Lists with SPARK_Mode is
1
2
      function Goes_To (I, J : Index) return Boolean is
3
      begin
4
          if Memory (I).Is_Set then
5
             return Memory (I).Next = J;
6
         end if;
7
          return False;
8
      end Goes_To;
9
10
      procedure Link (I, J : Index) is
11
12
      begin
         Memory (I) := (Is_Set => True, Next => J);
13
      end Link;
14
15
   end Lists:
16
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_01
MD5: c2246948c584304d5694b49b4d1fd0fc
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

lists.ads:7:47: medium: postcondition might fail [possible fix: you should

consider adding a postcondition to function Goes_To or turning it into an

cexpression function]

gnatprove: unproved check messages considered as errors
```

This example is correct, but can't be verified by GNATprove. This is because Goes_To itself has no postcondition, so nothing is known about its result.

3.5.2 Example #2

We now redefine Goes_To as an expression function.

```
package Lists with SPARK_Mode is
1
2
       type Index is new Integer;
3
4
      function Goes_To (I, J : Index) return Boolean;
5
6
      procedure Link (I, J : Index) with Post => Goes_To (I, J);
7
8
   private
9
10
       type Cell (Is_Set : Boolean := True) is record
11
          case Is_Set is
12
          when True =>
13
             Next : Index;
14
          when False =>
15
             null;
16
          end case;
17
      end record;
18
19
      type Cell_Array is array (Index) of Cell;
20
21
      Memory : Cell_Array;
22
23
       function Goes_To (I, J : Index) return Boolean is
24
         (Memory (I).Is_Set and then Memory (I).Next = J);
25
26
   end Lists;
27
```

Listing 25: lists.adb

Listing 24: lists.ads

```
package body Lists with SPARK_Mode is
procedure Link (I, J : Index) is
begin
Memory (I) := (Is_Set => True, Next => J);
end Link;
end Lists;
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_02
MD5: c65953bbe8a5f9fb77a4d94e2dd875f9

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... lists.adb:5:18: info: discriminant check proved lists.ads:7:47: info: postcondition proved lists.ads:25:44: info: discriminant check proved

GNATprove can fully prove this version: Goes_To is an expression function, so its body is available for proof (specifically, for creating the postcondition needed for the proof).

3.5.3 Example #3

The package Stacks defines an abstract stack type with a Push procedure that adds an element at the top of the stack and a function Peek that returns the content of the element at the top of the stack (without removing it).

```
Listing 26: stacks.ads
```

```
package Stacks with SPARK_Mode is
1
2
      type Stack is private;
3
4
      function Peek (S : Stack) return Natural;
5
      procedure Push (S : in out Stack; E : Natural) with
6
         Post => Peek (S) = E;
7
8
9
   private
10
      Max : constant := 10;
11
12
      type Stack Array is array (1 .. Max) of Natural;
13
14
      type Stack is record
15
                  : Positive;
         Top
16
          Content : Stack Array;
17
      end record;
18
19
      function Peek (S : Stack) return Natural is
20
         (if S.Top in S.Content'Range then S.Content (S.Top) else 0);
21
22
   end Stacks;
23
```

Listing 27: stacks.adb

```
package body Stacks with SPARK_Mode is
1
2
      procedure Push (S : in out Stack; E : Natural) is
3
      begin
4
          if S.Top >= Max then
5
             return:
6
          end if;
7
8
          S.Top := S.Top + 1;
9
          S.Content (S.Top) := E;
10
      end Push;
11
12
   end Stacks;
13
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_03
MD5: 917d624916c5ef14c4e454d6c56414fd

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... stacks.ads:7:14: medium: postcondition might fail gnatprove: unproved check messages considered as errors

This example isn't correct. The postcondition of Push is only satisfied if the stack isn't full when we call Push.
3.5.4 Example #4

We now change the behavior of Push so it raises an exception when the stack is full instead of returning.

```
Listing 28: stacks.ads
```

```
package Stacks with SPARK_Mode is
1
2
      type Stack is private;
3
4
      Is_Full_E : exception;
5
6
      function Peek (S : Stack) return Natural;
7
      procedure Push (S : in out Stack; E : Natural) with
8
        Post => Peek (S) = E;
9
10
   private
11
12
      Max : constant := 10;
13
14
      type Stack_Array is array (1 .. Max) of Natural;
15
16
       type Stack is record
17
          Тор
                 : Positive;
18
          Content : Stack_Array;
19
      end record;
20
21
       function Peek (S : Stack) return Natural is
22
         (if S.Top in S.Content'Range then S.Content (S.Top) else 0);
23
24
   end Stacks;
25
```

Listing 29: stacks.adb

```
package body Stacks with SPARK_Mode is
1
2
      procedure Push (S : in out Stack; E : Natural) is
3
      begin
4
          if S.Top >= Max then
5
             raise Is_Full_E;
6
         end if;
7
8
         S.Top := S.Top + 1;
9
          S.Content (S.Top) := E;
10
      end Push;
11
12
   end Stacks;
13
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_04
MD5: b573ebe93f85ea171166b6953cbb8956

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
stacks.adb:6:10: medium: exception might be raised
gnatprove: unproved check messages considered as errors
```

The postcondition of Push is now proved because GNAT prove only considers execution paths

leading to normal termination. But it issues a message warning that exception Is_Full_E may be raised at runtime.

3.5.5 Example #5

Let's add a precondition to Push stating that the stack shouldn't be full.

```
Listing 30: stacks.ads
```

```
package Stacks with SPARK Mode is
1
2
      type Stack is private;
3
4
      Is_Full_E : exception;
5
6
      function Peek (S : Stack) return Natural;
7
      function Is Full (S : Stack) return Boolean;
8
      procedure Push (S : in out Stack; E : Natural) with
9
        Pre => not Is Full (S),
10
        Post => Peek (S) = E;
11
12
   private
13
14
      Max : constant := 10;
15
16
      type Stack_Array is array (1 .. Max) of Natural;
17
18
      type Stack is record
19
         Тор
                 : Positive;
20
         Content : Stack_Array;
21
      end record;
22
23
      function Peek (S : Stack) return Natural is
24
         (if S.Top in S.Content'Range then S.Content (S.Top) else 0);
25
      function Is_Full (S : Stack) return Boolean is (S.Top >= Max);
26
27
```

28 end Stacks;

Listing 31: stacks.adb

```
package body Stacks with SPARK_Mode is
1
2
      procedure Push (S : in out Stack; E : Natural) is
3
      begin
4
          if S.Top >= Max then
5
             raise Is_Full_E;
6
          end if;
7
          S.Top := S.Top + 1;
8
         S.Content (S.Top) := E;
9
      end Push;
10
11
   end Stacks;
12
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_05
MD5: 63c2dfd68dd5acd91d8d497206e7423e
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
stacks.adb:6:10: info: raise statement or expression proved unreachable
stacks.adb:8:22: info: overflow check proved
stacks.adb:9:19: info: index check proved
stacks.ads:11:14: info: postcondition proved
stacks.ads:25:52: info: index check proved
```

This example is correct. With the addition of the precondition, GNATprove can now verify that Is_Full_E can never be raised at runtime.

3.5.6 Example #6

The package Memories defines a type Chunk that models chunks of memory. Each element of the array, represented by its index, corresponds to one data element. The procedure Read_Record reads two pieces of data starting at index From out of the chunk represented by the value of Memory.

Listing 32: memories.ads

```
package Memories is
1
2
      type Chunk is array (Integer range <>) of Integer
3
        with Predicate => Chunk'Length >= 10;
4
5
      function Is_Too_Coarse (V : Integer) return Boolean;
6
7
      procedure Treat_Value (V : out Integer);
8
9
   end Memories;
10
```

Listing 33: read_record.adb

```
with Memories; use Memories;
1
2
   procedure Read Record (Memory : Chunk; From : Integer)
3
     with SPARK_Mode => On,
4
           Pre => From in Memory'First .. Memory'Last - 2
5
   is
6
      function Read_One (First : Integer; Offset : Integer) return Integer
7
        with Pre => First + Offset in Memory'Range
8
      is
9
         Value : Integer := Memory (First + Offset);
10
      begin
11
         if Is_Too_Coarse (Value) then
12
             Treat_Value (Value);
13
         end if;
14
         return Value;
15
      end Read_One;
16
17
      Data1, Data2 : Integer;
18
19
   begin
20
      Data1 := Read One (From, 1);
21
      Data2 := Read_One (From, 2);
22
  end Read_Record;
23
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_06
MD5: aec8014dc291708999092fa123ee7416

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

read_record.adb:8:24: medium: overflow check might fail, cannot prove lower bound_

Grow First + Offset [reason for check: result of addition must fit in a 32-bits_

Grachine integer] [possible fix: use pragma Overflow_Mode or switch -gnato13 or

Gunit Ada.Numerics.Big_Numerics.Big_Integers]

gnatprove: unproved check messages considered as errors
```

This example is correct, but it can't be verified by GNATprove, which analyses Read_One on its own and notices that an overflow may occur in its precondition in certain contexts.

3.5.7 Example #7

Let's rewrite the precondition of Read_One to avoid any possible overflow.

Listing 34: memories.ads

```
package Memories is
1
2
      type Chunk is array (Integer range <>) of Integer
3
        with Predicate => Chunk'Length >= 10;
4
5
      function Is_Too_Coarse (V : Integer) return Boolean;
6
7
      procedure Treat Value (V : out Integer);
8
9
   end Memories;
10
```

Listing 35: read_record.adb

```
with Memories; use Memories;
1
2
   procedure Read_Record (Memory : Chunk; From : Integer)
3
     with SPARK Mode => On,
4
           Pre => From in Memory'First .. Memory'Last - 2
5
   is
6
      function Read_One (First : Integer; Offset : Integer) return Integer
7
        with Pre => First >= Memory'First
8
                and then Offset in 0 .. Memory'Last - First
9
      is
10
          Value : Integer := Memory (First + Offset);
11
      begin
12
          if Is_Too_Coarse (Value) then
13
             Treat_Value (Value);
14
          end if;
15
          return Value;
16
      end Read_One;
17
18
      Data1, Data2 : Integer;
19
20
   begin
21
      Data1 := Read One (From, 1);
22
      Data2 := Read_One (From, 2);
23
   end Read Record;
24
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_07
MD5: 6b4c6a41b652ad76bc7ef8934dcd9bfc
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

read_record.adb:9:49: medium: overflow check might fail, cannot prove lower bound_

Grow Memory'Last - First [reason for check: result of subtraction must fit in a_

G32-bits machine integer] [possible fix: use pragma Overflow_Mode or switch -

Ggnato13 or unit Ada.Numerics.Big_Numerics.Big_Integers]

gnatprove: unproved check messages considered as errors
```

This example is also not correct: unfortunately, our attempt to correct Read_One's precondition failed. For example, an overflow will occur at runtime if First is **Integer**'Last and Memory'Last is negative. This is possible here because type Chunk uses **Integer** as base index type instead of **Natural** or **Positive**.

3.5.8 Example #8

Let's completely remove the precondition of Read_One.

Listing 36: memories.ads

```
package Memories is
type Chunk is array (Integer range <>) of Integer
with Predicate => Chunk'Length >= 10;
function Is_Too_Coarse (V : Integer) return Boolean;
procedure Treat_Value (V : out Integer);
end Memories;
```

Listing 37: read record.adb

```
with Memories; use Memories;
1
   procedure Read Record (Memory : Chunk; From : Integer)
3
     with SPARK Mode => On,
4
           Pre => From in Memory'First .. Memory'Last - 2
5
   is
6
      function Read One (First : Integer; Offset : Integer) return Integer is
7
         Value : Integer := Memory (First + Offset);
8
      begin
9
          if Is Too Coarse (Value) then
10
             Treat Value (Value);
11
         end if;
12
         return Value;
13
      end Read One;
14
15
      Data1, Data2 : Integer;
16
17
   begin
18
      Data1 := Read One (From, 1);
19
      Data2 := Read One (From, 2);
20
   end Read Record;
21
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_08
MD5: 5a806fb84b50d2dc1f2af428b1bc8d0a
```

Prover output

This example is correct and fully proved. We could have fixed the contract of Read_One to correctly handle both positive and negative values of Memory'Last, but we found it simpler to let the function be inlined for proof by removing its precondition.

3.5.9 Example #9

The procedure Compute performs various computations on its argument. The computation performed depends on its input range and is reflected in its contract, which we express using a Contract_Cases aspect.

```
Listing 38: compute.adb
```

```
procedure Compute (X : in out Integer) with
1
     Contract_Cases => ((X in -100 .. 100) => X = X'Old * 2,
2
                          (X in
                                   0 .. 199) => X = X'Old + 1,
3
                          (X in -199 .. 0) => X = X'Old - 1,
4
                          X >= 200
                                              => X = 200,
5
                           others
                                               = X = -200)
6
   is
7
   begin
8
      if X in -100 .. 100 then
9
         X := X * 2;
10
      elsif X in 0 .. 199 then
11
         X := X + 1;
12
      elsif X in -199 .. 0 then
13
         X := X - 1;
14
      elsif X \ge 200 then
15
         X := 200;
16
      else
17
         X := -200;
18
      end if;
19
   end Compute;
20
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_09
MD5: 51962d1bb6dd1b081ed498dd11559685
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... compute.adb:2:03: medium: contract cases might not be disjoint compute.adb:3:41: medium: contract case might fail compute.adb:4:41: medium: contract case might fail gnatprove: unproved check messages considered as errors

This example isn't correct. We duplicated the content of Compute's body in its contract. This is incorrect because the semantics of Contract_Cases require disjoint cases, just like a case statement. The counterexample returned by GNATprove shows that X = 0 is covered by two different case-guards (the first and the second).

3.5.10 Example #10

Let's rewrite the contract of Compute to avoid overlapping cases.

```
procedure Compute (X : in out Integer) with
1
     Contract_Cases => ((X in 0 .. 199) => X >= X'Old,
2
                         (X in -199 .. -1) => X <= X'Old,
3
                          X >= 200
                                               = X = 200,
4
                          X < -200
                                               = X = -200)
5
   is
6
7
   begin
      if X in -100 .. 100 then
8
         X := X * 2;
9
      elsif X in 0 .. 199 then
10
         X := X + 1;
11
      elsif X in -199 .. 0 then
12
         X := X - 1;
13
      elsif X \ge 200 then
14
         X := 200;
15
      else
16
         X := -200;
17
      end if;
18
   end Compute;
19
```

Listing 39: compute.adb

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Program_Integrity.Example_10
MD5: 01d33b10fd60f384ffa4ae8fea1e7d87
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... compute.adb:2:03: medium: contract cases might not be complete gnatprove: unproved check messages considered as errors

This example is still not correct. GNATprove can successfully prove the different cases are disjoint and also successfully verify each case individually. This isn't enough, though: a Contract_Cases must cover all cases. Here, we forgot the value -200, which is what GNATprove reports in its counterexample.

CHAPTER FOUR

STATE ABSTRACTION

Abstraction is a key concept in programming that can drastically simplify both the implementation and maintenance of code. It's particularly well suited to SPARK and its modular analysis. This section explains what state abstraction is and how you use it in SPARK. We explain how it impacts GNATprove's analysis both in terms of information flow and proof of program properties.

State abstraction allows us to:

- express dependencies that wouldn't otherwise be expressible because some data that's read or written isn't visible at the point where a subprogram is declared — examples are dependencies on data, for which we use the Global contract, and on flow, for which we use the Depends contract.
- reduce the number of variables that need to be considered in flow analysis and proof, a reduction which may be critical in order to scale the analysis to programs with thousands of global variables.

4.1 What's an Abstraction?

Abstraction is an important part of programming language design. It provides two views of the same object: an abstract one and a refined one. The abstract one — usually called *specification* — describes what the object does in a coarse way. A subprogram's specification usually describes how it should be called (e.g., parameter information such as how many and of what types) as well as what it does (e.g., returns a result or modifies one or more of its parameters).

Contract-based programming, as supported in Ada, allows contracts to be added to a subprogram's specification. You use contracts to describe the subprogram's behavior in a more fine-grained manner, but all the details of how the subprogram actually works are left to its refined view, its implementation.

Take a look at the example code shown below.

Listing 1: increase.ads

```
procedure Increase (X : in out Integer) with
Global => null,
Pre => X <= 100,
Post => X'Old < X;</pre>
```

Listing 2: increase.adb

```
procedure Increase (X : in out Integer) is
begin
X := X + 1;
end Increase;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.No_Abstraction
MD5: c4c8f229aeb1b5c12744d26369a8603f
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... increase.adb:3:11: info: overflow check proved increase.ads:2:03: info: data dependencies proved increase.ads:4:13: info: postcondition proved

We've written a specification of the subprogram Increase to say that it's called with a single argument, a variable of type **Integer** whose initial value is less than 100. Our contract says that the only effect of the subprogram is to increase the value of its argument.

4.2 Why is Abstraction Useful?

A good abstraction of a subprogram's implementation is one whose specification precisely and completely summarizes what its callers can rely on. In other words, a caller of that subprogram shouldn't rely on any behavior of its implementation if that behavior isn't documented in its specification.

For example, callers of the subprogram Increase can assume that it always strictly increases the value of its argument. In the code snippet shown below, this means the loop must terminate.

Listing 3: increase.ads

```
procedure Increase (X : in out Integer) with
Global => null,
Pre => X <= 100,
Post => X'Old < X;</pre>
```

Listing 4: client.adb

```
with Increase;
1
  procedure Client is
2
      X : Integer := 0;
3
  begin
4
      while X <= 100 loop
                               -- The loop will terminate
5
                               -- Increase can be called safely
         Increase (X);
6
      end loop;
7
      pragma Assert (X = 101); -- Will this hold?
8
  end Client:
a
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Using_Abstraction
MD5: 9cd07cb04ae2194343931f0561693be4
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... client.adb:8:19: medium: assertion might fail gnatprove: unproved check messages considered as errors Callers can also assume that the implementation of Increase won't cause any runtime errors when called in the loop. On the other hand, nothing in the specification guarantees that the assertion show above is correct: it may fail if Increase's implementation is changed.

If you follow this basic principle, abstraction can bring you significant benefits. It simplifies both your program's implementation and verification. It also makes maintenance and code reuse much easier since changes to the implementation of an object shouldn't affect the code using this object. Your goal in using it is that it should be enough to understand the specification of an object in order to use that object, since understanding the specification is usually much simpler than understanding the implementation.

GNATprove relies on the abstraction defined by subprogram contracts and therefore doesn't prove the assertion after the loop in Client above.

4.3 Abstraction of a Package's State

Subprograms aren't the only objects that benefit from abstraction. The state of a package — the set of persistent variables defined in it — can also be hidden from external users. You achieve this form of abstraction — called *state abstraction* — by defining variables in the body or private part of a package so they can only be accessed through subprogram calls. For example, our Stack package shown below provides an abstraction for a Stack object which can only be modified using the Pop and Push procedures.

```
package Stack is
    procedure Pop (E : out Element);
    procedure Push (E : in Element);
end Stack;
package body Stack is
    Content : Element_Array (1 .. Max);
    Top : Natural;
    ...
end Stack;
```

The fact that we implemented it using an array is irrelevant to the caller. We could change that without impacting our callers' code.

4.4 Declaring a State Abstraction

Hidden state influences a program's behavior, so SPARK allows that state to be declared. You can use the Abstract_State aspect, an abstraction that names a state, to do this, but you aren't required to use it even for a package with hidden state. You can use several state abstractions to declare the hidden state of a single package or you can use it for a package with no hidden state at all. However, since SPARK doesn't allow aliasing, different state abstractions must always refer to disjoint sets of variables. A state abstraction isn't a variable: it doesn't have a type and can't be used inside expressions, either those in bodies or contracts.

As an example of the use of this aspect, we can optionally define a state abstraction for the entire hidden state of the Stack package like this:

```
package Stack with
  Abstract_State => The_Stack
  is
   ...
```

Alternatively, we can define a state abstraction for each hidden variable:

```
package Stack with
  Abstract_State => (Top_State, Content_State)
is
....
```

Remember: a state abstraction isn't a variable (it has no type) and can't be used inside expressions. For example:

```
pragma Assert (Stack.Top_State = ...);
-- compilation error: Top_State is not a variable
```

4.5 Refining an Abstract State

Once you've declared an abstract state in a package, you must refine it into its constituents using a Refined_State aspect. You must place the Refined_State aspect on the package body even if the package wouldn't otherwise have required a body. For each state abstraction you've declared for the package, you list the set of variables represented by that state abstraction in its refined state.

If you specify an abstract state for a package, it must be complete, meaning you must have listed every hidden variable as part of some state abstraction. For example, we must add a Refined_State aspect on our Stack package's body linking the state abstraction (The_Stack) to the entire hidden state of the package, which consists of both Content and Top.

Listing 5: stack.ads

```
1 package Stack with
2 Abstract_State => The_Stack
3 is
4 type Element is new Integer;
5
6 procedure Pop (E : out Element);
7 procedure Push (E : Element);
8
9 end Stack;
```

Listing 6: stack.adb

```
package body Stack with
1
     Refined State => (The Stack => (Content, Top))
2
   is
3
      Max : constant := 100;
4
5
      type Element Array is array (1 .. Max) of Element;
6
7
      Content : Element Array := (others => 0);
8
               : Natural range 0 .. Max := 0;
      Тор
9
      -- Both Content and Top must be listed in the list of
10
      -- constituents of The Stack
11
12
      procedure Pop (E : out Element) is
13
      begin
14
         Е
             := Content (Top);
15
         Top := Top - 1;
16
      end Pop;
17
18
      procedure Push (E : Element) is
19
```

```
20 begin
21 Top := Top + 1;
22 Content (Top) := E;
23 end Push;
24
25 end Stack;
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Refined_State
MD5: 3a794c7a4e4920dab7d01248e50901ab

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
stack.ads:6:20: info: initialization of "E" proved
```

4.6 Representing Private Variables

You can refine state abstractions in the package body, where all the variables are visible. When only the package's specification is available, you need a way to specify which state abstraction each private variable belongs to. You do this by adding the Part_Of aspect to the variable's declaration.

Part_Of annotations are mandatory: if you gave a package an abstract state annotation, you must link all the hidden variables defined in its private part to a state abstraction. For example:

Listing 7: stack.ads

```
package Stack with
1
     Abstract_State => The_Stack
2
   is
3
      type Element is new Integer;
4
5
      procedure Pop (E : out Element);
6
      procedure Push (E : Element);
7
8
   private
9
10
      Max : constant := 100;
11
12
      type Element_Array is array (1 .. Max) of Element;
13
14
      Content : Element_Array
                                          with Part Of => The Stack;
15
               : Natural range 0 .. Max with Part_Of => The_Stack;
      Top
16
17
   end Stack;
18
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Private_Variables
MD5: 3b5f7edca8a4511071d2397197b01fda
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ...

Since we chose to define Content and Top in Stack's private part instead of its body, we had to add a Part_Of aspect to both of their declarations, associating them with the state abstraction The_Stack, even though it's the only state abstraction. However, we still need to list them in the Refined_State aspect in Stack's body.

package body Stack with
 Refined_State => (The_Stack => (Content, Top))

4.7 Additional State

4.7.1 Nested Packages

So far, we've only discussed hidden variables. But variables aren't the only component of a package's state. If a package P contains a nested package, the nested package's state is also part of P's state. If the nested package is hidden, its state is part of P's hidden state and must be listed in P's state refinement.

We see this in the example below, where the package Hidden_Nested's hidden state is part of P's hidden state.

```
Listing 8: p.ads
```

```
package P with
1
2
      Abstract State => State
3
   is
      package Visible Nested with
4
         Abstract State => Visible State
5
6
      is
         procedure Get (E : out Integer);
7
      end Visible_Nested;
8
  end P;
9
```

```
Listing 9: p.adb
```

```
package body P with
1
      Refined_State => (State => Hidden_Nested.Hidden_State)
2
   is
3
      package Hidden Nested with
4
         Abstract State => Hidden State,
5
         Initializes
                        => Hidden_State
6
      is
7
         function Get return Integer;
8
      end Hidden_Nested;
9
10
      package body Hidden_Nested with
11
         Refined_State => (Hidden_State => Cnt)
12
      is
13
         Cnt : Integer := 0;
14
15
          function Get return Integer is (Cnt);
16
17
      end Hidden_Nested;
18
      package body Visible_Nested with
19
          Refined_State => (Visible_State => Checked)
20
```

```
is
21
          Checked : Boolean := False;
22
23
          procedure Get (E : out Integer) is
24
          begin
25
              Checked := True;
26
              E := Hidden_Nested.Get;
27
          end Get;
28
       end Visible Nested;
29
   end P;
30
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Nested_Packages
MD5: 8260089cbd651de296dd790506c76fd8
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
p.adb:6:07: info: flow dependencies proved
p.ads:7:22: info: initialization of "E" proved
```

Any visible state of Hidden_Nested would also have been part of P's hidden state. However, if P contains a visible nested package, that nested package's state isn't part of P's hidden state. Instead, you should declare that package's hidden state in a separate state abstraction on its own declaration, like we did above for Visible_Nested.

4.7.2 Constants that Depend on Variables

Some constants are also possible components of a state abstraction. These are constants whose value depends either on a variable or a subprogram parameter. They're handled as variables during flow analysis because they participate in the flow of information between variables throughout the program. Therefore, GNATprove considers these constants to be part of a package's state just like it does for variables.

If you've specified a state abstraction for a package, you must list such hidden constants declared in that package in the state abstraction refinement. However, constants that don't depend on variables don't participate in the flow of information and must not appear in a state refinement.

Let's look at this example.

```
Listing 10: stack.ads
```

```
1 package Stack with
2 Abstract_State => The_Stack
3 is
4 type Element is new Integer;
5
6 procedure Pop (E : out Element);
7 procedure Push (E : Element);
8 end Stack;
```

Listing 11: configuration.ads

```
1 package Configuration with
2 Initializes => External_Variable
3 is
```

```
4 External_Variable : Positive with Volatile;
5 end Configuration;
```

```
Listing 12: stack.adb
```

```
with Configuration;
1
   pragma Elaborate (Configuration);
2
3
   package body Stack with
4
     Refined_State => (The_Stack => (Content, Top, Max))
5
     -- Max has variable inputs. It must appear as a
6
     -- constituent of The_Stack
7
   is
8
      Max : constant Positive := Configuration.External Variable;
9
10
      type Element Array is array (1 .. Max) of Element;
11
12
      Content : Element Array := (others => 0);
13
               : Natural range 0 .. Max := 0;
      Тор
14
15
      procedure Pop (E : out Element) is
16
      begin
17
         Е
             := Content (Top);
18
         Top := Top - 1;
19
      end Pop;
20
21
      procedure Push (E : Element) is
22
      begin
23
          Top
                         := Top + 1;
24
          Content (Top) := E;
25
      end Push;
26
27
   end Stack;
28
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Constants_And_Variables
MD5: 109a6340ef0f3b0dc88e0fe5888b9a53

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ... stack.ads:6:20: info: initialization of "E" proved configuration.ads:2:03: info: flow dependencies proved

Here, Max — the maximum number of elements that can be stored in the stack — is initialized from a variable in an external package. Because of this, we must include Max as part of the state abstraction The_Stack.

Note: For more details on state abstractions, see the SPARK User's Guide²¹.

 $^{^{21}\} https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/package_contracts.html# state-abstraction$

4.8 Subprogram Contracts

4.8.1 Global and Depends

Hidden variables can only be accessed through subprogram calls, so you document how state abstractions are modified during the program's execution via the contracts of those subprograms. You use Global and Depends contracts to specify which of the state abstractions are used by a subprogram and how values flow through the different variables. The Global and Depends contracts that you write when referring to state abstractions are often less precise than contracts referring to visible variables since the possibly different dependencies of the hidden variables contained within a state abstraction are collapsed into a single dependency.

Let's add Global and Depends contracts to the Pop procedure in our stack.

```
Listing 13: stack.ads
```

```
package Stack with
1
      Abstract_State => (Top_State, Content_State)
2
   is
3
      type Element is new Integer;
4
5
      procedure Pop (E : out Element) with
6
        Global => (Input => Content State,
7
                     In Out => Top State),
8
         Depends => (Top State => Top State,
9
                                => (Content_State, Top_State));
                     F
10
11
   end Stack;
12
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Global_Depends
MD5: a7b383c35508d6a8294bf7cf0fe332ac

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ...

In this example, the Pop procedure only modifies the value of the hidden variable Top, while Content is unchanged. By using distinct state abstractions for the two variables, we're able to preserve this semantic in the contract.

Let's contrast this example with a different representation of Global and Depends contracts, this time using a single abstract state.

Listing 14: stack.ads

```
package Stack with
1
     Abstract_State => The_Stack
2
   is
3
      type Element is new Integer;
4
5
      procedure Pop (E : out Element) with
6
        Global => (In_Out => The_Stack),
7
        Depends => ((The_Stack, E) => The_Stack);
8
9
   end Stack;
10
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Global_Single_Abstract_State
MD5: f89f6026fa5ee3c18baf0af9d7c3dbca

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: analysis of data and information flow ...

Here, Top_State and Content_State are merged into a single state abstraction, The_Stack. By doing so, we've hidden the fact that Content isn't modified (though we're still showing that Top may be modified). This loss in precision is reasonable here, since it's the whole point of the abstraction. However, you must be careful not to aggregate unrelated hidden state because this risks their annotations becoming meaningless.

Even though imprecise contracts that consider state abstractions as a whole are perfectly reasonable for users of a package, you should write Global and Depends contracts that are as precise as possible within the package body. To allow this, SPARK introduces the notion of *refined contracts*, which are precise contracts specified on the bodies of subprograms where state refinements are visible. These contracts are the same as normal Global and Depends contracts except they refer directly to the hidden state of the package.

When a subprogram is called inside the package body, you should write refined contracts instead of the general ones so that the verification can be as precise as possible. However, refined Global and Depends are optional: if you don't specify them, GNATprove will compute them to check the package's implementation.

For our Stack example, we could add refined contracts as shown below.

```
Listing 15: stack.ads
```

```
package Stack with
1
     Abstract State => The Stack
2
   is
3
      type Element is new Integer;
4
5
      procedure Pop (E : out Element) with
6
        Global => (In Out => The Stack),
7
        Depends => ((The Stack, E) => The Stack);
8
9
      procedure Push (E : Element) with
10
                              => The Stack),
        Global => (In_Out
11
        Depends => (The_Stack => (The_Stack, E));
12
13
   end Stack:
14
```

```
Listing 16: stack.adb
```

```
package body Stack with
1
     Refined State => (The Stack => (Content, Top))
2
   is
3
      Max : constant := 100;
4
5
      type Element_Array is array (1 .. Max) of Element;
6
7
8
      Content : Element_Array := (others => 0);
9
      Тор
               : Natural range 0 .. Max := 0;
10
      procedure Pop (E : out Element) with
11
        Refined_Global => (Input => Content,
12
                             In Out => Top),
13
        Refined Depends => (Top => Top,
14
```

```
Е
                                   => (Content, Top))
15
      is
16
      begin
17
              := Content (Top);
          Е
18
          Top := Top - 1;
19
      end Pop;
20
21
      procedure Push (E : Element) with
22
         Refined_Global => (In_Out => (Content, Top)),
23
         Refined_Depends => (Content =>+ (Content, Top, E),
24
                               Тор
                                        => Top) is
25
      begin
26
         Top := Top + 1;
27
         Content (Top) := E;
28
       end Push;
29
30
   end Stack;
31
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Global_Refined
MD5: b7e700645885155ea7faf2f4170f0462
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
```

4.8.2 Preconditions and Postconditions

We mostly express functional properties of subprograms using preconditions and postconditions. These are standard Boolean expressions, so they can't directly refer to state abstractions. To work around this restriction, we can define functions to query the value of hidden variables. We then use these functions in place of the state abstraction in the contract of other subprograms.

For example, we can query the state of the stack with functions Is_Empty and Is_Full and call these in the contracts of procedures Pop and Push:

```
Listing 17: stack.ads
```

```
package Stack is
1
      type Element is new Integer;
2
3
      function Is_Empty return Boolean;
4
      function Is Full return Boolean;
5
6
      procedure Pop (E : out Element) with
7
        Pre => not Is_Empty,
8
        Post => not Is_Full;
9
10
      procedure Push (E : Element) with
11
        Pre => not Is_Full,
12
        Post => not Is_Empty;
13
14
   end Stack;
15
```

```
Listing 18: stack.adb
```

```
package body Stack is
1
2
      Max : constant := 100;
3
4
      type Element Array is array (1 .. Max) of Element;
5
6
      Content : Element_Array := (others => 0);
7
      Top
               : Natural range 0 .. Max := 0;
8
9
      function Is_Empty return Boolean is (Top = 0);
10
      function Is_Full return Boolean is (Top = Max);
11
12
      procedure Pop (E : out Element) is
13
      begin
14
             := Content (Top);
         F
15
          Top := Top -1;
16
      end Pop;
17
18
      procedure Push (E : Element) is
19
      begin
20
                         := Top + 1;
          Top
21
          Content (Top) := E;
22
      end Push:
23
24
   end Stack;
25
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Pre_Postconditions_1
MD5: fe9d4b65ba1beeabc7cf0feda29b8b3c

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
stack.adb:15:23: info: index check proved
stack.adb:16:18: info: range check proved
stack.adb:21:28: info: range check proved
stack.adb:22:16: info: index check proved
stack.ads:7:19: info: initialization of "E" proved
stack.ads:9:14: info: postcondition proved
stack.ads:13:14: info: postcondition proved
```

Just like we saw for Global and Depends contracts, you may often find it useful to have a more precise view of functional contracts in the context where the hidden variables are visible. You do this using expression functions in the same way we did for the functions Is_Empty and Is_Full above. As expression function, bodies act as contracts for GNATprove, so they automatically give a more precise version of the contracts when their implementation is visible.

You may often need a more constraining contract to verify the package's implementation but want to be less strict outside the abstraction. You do this using the Refined_Post aspect. This aspect, when placed on a subprogram's body, provides stronger guarantees to internal callers of a subprogram. If you provide one, the refined postcondition must imply the subprogram's postcondition. This is checked by GNATprove, which reports a failing postcondition if the refined postcondition is too weak, even if it's actually implied by the subprogram's body. SPARK doesn't peform a similar verification for normal preconditions.

For example, we can refine the postconditions in the bodies of Pop and Push to be more detailed than what we wrote for them in their specification.

Listing 19: stack.ads

```
package Stack is
1
      type Element is new Integer;
2
3
      function Is_Empty return Boolean;
4
      function Is_Full return Boolean;
5
6
      procedure Pop (E : out Element) with
7
        Pre => not Is_Empty,
8
        Post => not Is Full;
9
10
      procedure Push (E : Element) with
11
        Pre => not Is_Full,
12
        Post => not Is_Empty;
13
14
   end Stack:
15
```

Listing 20: stack.adb

```
package body Stack is
1
2
      Max : constant := 100;
3
4
      type Element Array is array (1 .. Max) of Element;
5
6
      Content : Element_Array := (others => 0);
7
      Тор
               : Natural range 0 .. Max := 0;
8
9
      function Is_Empty return Boolean is (Top = 0);
10
      function Is_Full return Boolean is (Top = Max);
11
12
      procedure Pop (E : out Element) with
13
        Refined_Post => not Is_Full and E = Content (Top)'Old
14
      is
15
      begin
16
         Е
              := Content (Top);
17
         Top := Top - 1;
18
      end Pop;
19
20
      procedure Push (E : Element) with
21
        Refined_Post => not Is_Empty and E = Content (Top)
22
      is
23
      begin
24
          Тор
                         := Top + 1;
25
          Content (Top) := E;
26
      end Push;
27
28
   end Stack;
29
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Pre_Postconditions_2
MD5: 4691565d58ba039b3cbd06e65cecfa88
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
stack.adb:14:22: info: refined post proved
stack.adb:14:51: info: index check proved
```

```
stack.adb:17:23: info: index check proved
stack.adb:18:18: info: range check proved
stack.adb:22:22: info: refined post proved
stack.adb:22:52: info: index check proved
stack.adb:25:28: info: range check proved
stack.adb:26:16: info: index check proved
stack.ads:7:19: info: initialization of "E" proved
stack.ads:9:14: info: postcondition proved
stack.ads:13:14: info: postcondition proved
```

Note: For more details on refinement in contracts, see the SPARK User's Guide²².

4.9 Initialization of Local Variables

As part of flow analysis, GNATprove checks for the proper initialization of variables. Therefore, flow analysis needs to know which variables are initialized during the package's elaboration.

You can use the Initializes aspect to specify the set of visible variables and state abstractions that are initialized during the elaboration of a package. An Initializes aspect can't refer to a variable that isn't defined in the unit since, in SPARK, a package can only initialize variables declared immediately within the package.

Initializes aspects are optional. If you don't supply any, they'll be derived by GNATprove.

For our Stack example, we could add an Initializes aspect.

```
Listing 21: stack.ads
```

```
package Stack with
1
     Abstract State => The Stack,
2
     Initializes
                    => The Stack
3
   is
4
      type Element is new Integer;
5
6
      procedure Pop (E : out Element);
7
8
   end Stack;
```

Listing 22: stack.adb

```
package body Stack with
1
     Refined_State => (The_Stack => (Content, Top))
2
   is
3
      Max : constant := 100;
4
5
      type Element_Array is array (1 .. Max) of Element;
6
7
      Content : Element_Array := (others => 0);
8
      Тор
               : Natural range 0 .. Max := 0;
9
10
      procedure Pop (E : out Element) is
11
      begin
12
         Е
13
              := Content (Top);
```

 $^{^{22}}$ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/subprogram_contracts.html# state-abstraction-and-contracts

```
14 Top := Top - 1;
15 end Pop;
16
17 end Stack;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Local_Init
MD5: 710e74959fd2ef8f5089c4636d7ec13b
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
stack.ads:3:03: info: flow dependencies proved
stack.ads:7:20: info: initialization of "E" proved
```

Flow analysis also checks for dependencies between variables, so it must be aware of how information flows through the code that performs the initialization of states. We discussed one use of the Initializes aspect above. But you also can use it to provide flow information. If the initial value of a variable or state abstraction is dependent on the value of another visible variable or state abstraction from another package, you must list this dependency in the Initializes contract. You specify the list of entities on which a variable's initial value depends using an arrow following that variable's name.

Let's look at this example:

```
Listing 23: q.ads
```

```
package Q is
External_Variable : Integer := 2;
end Q;
```

Listing 24: p.ads

```
vith Q;
package P with
Initializes => (V1, V2 => Q.External_Variable)
is
V1 : Integer := 0;
V2 : Integer := Q.External_Variable;
end P;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Initializes
MD5: c8aa7f21729f3b926bf3d25a826cccb2
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
p.ads:3:03: info: flow dependencies proved
```

Here we indicated that V2's initial value depends on the value of Q.External_Variable by including that dependency in the Initializes aspect of P. We didn't list any dependency for V1 because its initial value doesn't depend on any external variable. We could also have stated that lack of dependency explicitly by writing V1 => null.

GNATprove computes dependencies of initial values if you don't supply an Initializes aspect. However, if you do provide an Initializes aspect for a package, it must be com-

plete: you must list every initialized state of the package, along with all its external dependencies.

Note: For more details on Initializes, see the SPARK User's Guide²³.

4.10 Code Examples / Pitfalls

This section contains some code examples to illustrate potential pitfalls.

4.10.1 Example #1

Package Communication defines a hidden local package, Ring_Buffer, whose capacity is initialized from an external configuration during elaboration.

```
Listing 25: configuration.ads
```

```
package Configuration is
    External_Variable : Natural := 1;
    end Configuration;
```

Listing 26: communication.ads

```
with Configuration;
1
2
   package Communication with
3
     Abstract_State => State,
4
     Initializes
                   => (State => Configuration.External_Variable)
5
   is
6
      function Get_Capacity return Natural;
7
8
   private
9
10
      package Ring Buffer with
11
        Initializes => (Capacity => Configuration.External_Variable)
12
13
      is
         Capacity : constant Natural := Configuration.External_Variable;
14
      end Ring_Buffer;
15
16
   end Communication;
17
```



```
package body Communication with
Refined_State => (State => Ring_Buffer.Capacity)
is
function Get_Capacity return Natural is
begin
return Ring_Buffer.Capacity;
end Get_Capacity;
```

 $^{^{23}\} https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/package_contracts.html \# package-initialization$

10 end Communication;

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_01
MD5: 207e999f85a5b39fa2b9aebbc836b479
```

Prover output

Phase 1 of 2: generation of Global contracts ... communication.adb:2:41: error: "Capacity" cannot act as constituent of state "State ¬" communication.adb:2:41: error: missing Part_Of indicator at communication.ads:14 ¬should specify encapsulator "State" gnatprove: error during generation of Global contracts

This example isn't correct. Capacity is declared in the private part of Communication. Therefore, we should have linked it to State by using the Part Of aspect in its declaration.

4.10.2 Example #2

Let's add Part_Of to the state of hidden local package Ring_Buffer, but this time we hide variable Capacity inside the private part of Ring_Buffer.

```
Listing 28: configuration.ads
```

```
package Configuration is
    External_Variable : Natural := 1;
    end Configuration;
```

Listing 29: communication.ads

```
with Configuration;
1
2
   package Communication with
3
     Abstract State => State
4
   is
5
   private
6
7
      package Ring Buffer with
8
         Abstract_State => (B_State with Part_Of => State),
9
         Initializes
                      => (B State => Configuration.External Variable)
10
      is
11
          function Get_Capacity return Natural;
12
13
      private
          Capacity : constant Natural := Configuration.External_Variable
14
            with Part_Of => B_State;
15
      end Ring Buffer;
16
17
   end Communication;
18
```

Listing 30: communication.adb

```
package body Communication with
```

```
2 Refined_State => (State => Ring_Buffer.B_State)
```

```
is
3
4
      package body Ring_Buffer with
5
          Refined_State => (B_State => Capacity)
6
      is
7
          function Get_Capacity return Natural is (Capacity);
8
      end Ring_Buffer;
9
10
   end Communication;
11
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_02
MD5: b8d31fcfbd11bf305646efe07baeb91b
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
communication.ads:10:06: info: flow dependencies proved
```

This program is correct and GNATprove is able to verify it.

4.10.3 Example #3

Package Counting defines two counters: Black_Counter and Red_Counter. It provides separate initialization procedures for each, both called from the main procedure.

Listing 31: counting.ads

```
1 package Counting with
2 Abstract_State => State
3 is
4 procedure Reset_Black_Count;
5 procedure Reset_Red_Count;
6 end Counting;
```

Listing 32: counting.adb

```
package body Counting with
1
     Refined_State => (State => (Black_Counter, Red_Counter))
2
   is
3
      Black_Counter, Red_Counter : Natural;
4
5
      procedure Reset_Black_Count is
6
      beain
7
          Black Counter := 0;
8
      end Reset_Black_Count;
9
10
      procedure Reset Red Count is
11
      begin
12
          Red Counter := 0;
13
      end Reset_Red_Count;
14
   end Counting;
15
```

```
Listing 33: main.adb
```

```
with Counting; use Counting;
procedure Main is
begin
Reset_Black_Count;
Reset_Red_Count;
rend Main;
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Example_03
MD5: bc2d7ccd7419d34f7156a16dfc484229

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: analysis of data and information flow ...

main.adb:5:04: medium: "Counting.State" might not be initialized after elaboration.

Gof main program "Main"

counting.ads:2:21: warning: no procedure exists that can initialize abstract state

Grounting.State"

gnatprove: unproved check messages considered as errors
```

This program doesn't read any uninitialized data, but GNATprove fails to verify that. This is because we provided a state abstraction for package Counting, so flow analysis computes the effects of subprograms in terms of this state abstraction and thus considers State to be an in-out global consisting of both Black_Counter and Red_Counter. So it issues the message requiring that State be initialized after elaboration as well as the warning that no procedure in package Counting can initialize its state.

4.10.4 Example #4

Let's remove the abstract state on package Counting.

Listing 34: counting.ads

```
package Counting is
procedure Reset_Black_Count;
procedure Reset_Red_Count;
end Counting;
```

Listing 35: counting.adb

```
package body Counting is
1
      Black Counter, Red Counter : Natural;
2
3
      procedure Reset_Black_Count is
4
      begin
5
          Black_Counter := 0;
6
      end Reset_Black_Count;
7
8
      procedure Reset_Red_Count is
9
       begin
10
          Red Counter := 0;
11
      end Reset Red Count;
12
   end Counting;
13
```

Listing 36: main.adb

```
with Counting; use Counting;

procedure Main is
begin
Reset_Black_Count;
Reset_Red_Count;
rend Main;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_04
MD5: 3ddd934b6ede6df7b823e46828694d12
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
```

This example is correct. Because we didn't provide a state abstraction, GNATprove reasons in terms of variables, instead of states, and proves data initialization without any problem.

4.10.5 Example #5

Let's restore the abstract state to package Counting, but this time provide a procedure Reset_All that calls the initialization procedures Reset_Black_Counter and Reset_Red_Counter.

Listing 37: counting.ads

```
1 package Counting with
2 Abstract_State => State
3 is
4 procedure Reset_Black_Count with Global => (In_Out => State);
5 procedure Reset_Red_Count with Global => (In_Out => State);
6 procedure Reset_All with Global => (Output => State);
7 end Counting;
```

Listing 38: counting.adb

```
package body Counting with
1
     Refined State => (State => (Black Counter, Red Counter))
2
   is
3
      Black Counter, Red Counter : Natural;
4
5
      procedure Reset_Black_Count is
6
      begin
7
          Black Counter := 0:
8
      end Reset Black Count;
9
10
      procedure Reset Red Count is
11
      begin
12
          Red Counter := 0;
13
      end Reset_Red_Count;
14
15
      procedure Reset_All is
16
      beain
17
          Reset_Black_Count;
18
```

```
19 Reset_Red_Count;
20 end Reset_All;
21 end Counting;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_05
MD5: d123ccc644fe6999699388708f2ecf89
```

Prover output

This example is correct. Flow analysis computes refined versions of Global contracts for internal calls and uses these to verify that Reset_All indeed properly initializes State. The Refined_Global and Global annotations are not mandatory and can be computed by GNATprove.

4.10.6 Example #6

Let's consider yet another version of our abstract stack unit.

```
Listing 39: stack.ads
```

```
package Stack with
1
     Abstract_State => The_Stack
2
   is
3
      pragma Unevaluated Use Of Old (Allow);
4
5
      type Element is new Integer;
6
7
      type Element_Array is array (Positive range <>) of Element;
8
      Max : constant Natural := 100;
9
      subtype Length_Type is Natural range 0 .. Max;
10
11
      procedure Push (E : Element) with
12
        Post =>
13
          not Is Empty and
14
           (if Is Full'Old then The Stack = The Stack'Old else Peek = E);
15
16
      function Peek
                         return Element with Pre => not Is Empty;
17
      function Is_Full return Boolean;
18
      function Is Empty return Boolean;
19
   end Stack;
20
```

Listing 40: stack.adb

```
1 package body Stack with
2 Refined_State => (The_Stack => (Top, Content))
3 is
4 Top : Length_Type := 0;
```

```
Content : Element_Array (1 .. Max) := (others => 0);
5
6
       procedure Push (E : Element) is
7
       begin
8
                             := Top + 1;
           Top
9
           Content (Top) := E;
10
       end Push:
11
12
       function Peek
                               return Element is (Content (Top));
13
       function Is_Full return Boolean is (Top >= Max);
function Is_Empty return Boolean is (Top = 0);
14
15
    end Stack;
16
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_06
MD5: 9da2b74da203a639dc66b2d33cbd500d
```

Build output

Prover output

This example isn't correct. There's a compilation error in Push's postcondition: The_Stack is a state abstraction, not a variable, and therefore can't be used in an expression.

4.10.7 Example #7

In this version of our abstract stack unit, a copy of the stack is returned by function Get_Stack, which we call in the postcondition of Push to specify that the stack shouldn't be modified if it's full. We also assert that after we push an element on the stack, either the stack is unchanged (if it was already full) or its top element is equal to the element just pushed.

```
Listing 41: stack.ads
```

```
package Stack with
1
     Abstract State => The Stack
2
   is
3
      pragma Unevaluated Use Of Old (Allow);
4
5
      type Stack Model is private;
6
7
      type Element is new Integer;
8
      type Element Array is array (Positive range <>) of Element;
9
      Max : constant Natural := 100;
10
      subtype Length_Type is Natural range 0 .. Max;
11
12
      function Peek
                          return Element with Pre => not Is Empty;
13
      function Is Full
                          return Boolean;
14
      function Is_Empty return Boolean;
15
```

```
function Get_Stack return Stack_Model;
16
17
       procedure Push (E : Element) with
18
        Post => not Is_Empty and
19
           (if Is_Full'Old then Get_Stack = Get_Stack'Old else Peek = E);
20
21
   private
22
23
      type Stack_Model is record
24
          Тор
                : Length_Type := 0;
25
          Content : Element_Array (1 .. Max) := (others => 0);
26
       end record;
27
28
   end Stack;
29
```

Listing 42: stack.adb

```
package body Stack with
1
     Refined_State => (The_Stack => (Top, Content))
2
3
   is
               : Length_Type := 0;
4
      Top
      Content : Element_Array (1 .. Max) := (others => 0);
5
6
      procedure Push (E : Element) is
7
      begin
8
          if Top >= Max then
9
             return;
10
          end if;
11
                           := Top + 1;
12
         Тор
          Content (Top) := E;
13
      end Push;
14
15
                          return Element is (Content (Top));
      function Peek
16
      function Is_Full return Boolean is (Top >= Max);
17
      function Is_Empty return Boolean is (Top = 0);
18
19
      function Get_Stack return Stack Model is (Stack_Model'(Top, Content));
20
21
   end Stack;
22
```

Listing 43: use_stack.adb

```
with Stack; use Stack;
1
2
   procedure Use_Stack (E : Element) with
3
     Pre => not Is_Empty
4
   is
5
      F : Element := Peek;
6
   begin
7
      Push (E);
8
      pragma Assert (Peek = E or Peek = F);
9
  end Use_Stack;
10
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_07
MD5: 4831aa7f018f2e2d4e6d102095f8f631
```

Prover output

This program is correct, but GNATprove can't prove the assertion in Use_Stack. Indeed, even if Get_Stack is an expression function, its body isn't visible outside of Stack's body, where it's defined.

4.10.8 Example #8

Let's move the definition of Get_Stack and other expression functions inside the private part of the spec of Stack.

```
Listing 44: stack.ads
```

```
package Stack with
1
     Abstract_State => The_Stack
2
   is
3
      pragma Unevaluated Use Of Old (Allow);
4
5
      type Stack Model is private;
6
7
8
      type Element is new Integer;
      type Element Array is array (Positive range <>) of Element;
9
10
      Max : constant Natural := 100;
      subtype Length_Type is Natural range 0 .. Max;
11
12
      function Peek
                          return Element with Pre => not Is_Empty;
13
      function Is Full return Boolean;
14
      function Is_Empty return Boolean;
15
      function Get_Stack return Stack_Model;
16
17
      procedure Push (E : Element) with
18
        Post => not Is Empty and
19
           (if Is_Full'Old then Get_Stack = Get_Stack'Old else Peek = E);
20
21
   private
22
23
                                           := 0 with Part Of => The Stack;
              : Length_Type
24
      Top
      Content : Element_Array (1 .. Max) := (others => 0) with
25
        Part_Of => The_Stack;
26
27
      type Stack Model is record
28
                 : Length Type := 0;
         Top
29
         Content : Element_Array (1 .. Max) := (others => 0);
30
      end record;
31
32
      function Peek
                          return Element
                                              is (Content (Top));
33
      function Is_Full return Boolean
                                              is (Top >= Max);
34
      function Is_Empty return Boolean
                                              is (Top = 0);
35
36
      function Get_Stack return Stack_Model is (Stack_Model'(Top, Content));
37
38
   end Stack;
39
```

```
Listing 45: stack.adb
```

```
package body Stack with
1
     Refined_State => (The_Stack => (Top, Content))
2
   is
3
4
      procedure Push (E : Element) is
5
      begin
6
          if Top >= Max then
7
             return;
8
          end if;
9
          Тор
                            := Top + 1;
10
          Content (Top) := E;
11
      end Push;
12
13
   end Stack;
14
```

Listing 46: use_stack.adb

```
with Stack; use Stack;
1
2
   procedure Use Stack (E : Element) with
3
     Pre => not Is_Empty
4
5
   is
      F : Element := Peek;
6
   begin
7
8
      Push (E);
      pragma Assert (Peek = E or Peek = F);
9
   end Use_Stack;
10
```

Code block metadata

Project: Courses.Intro_To_Spark.State_Abstraction.Example_08
MD5: 7e5204d3f69e71c212e7263906a89da4

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... use_stack.adb:6:19: info: precondition proved use_stack.adb:9:19: info: precondition proved use_stack.adb:9:19: info: assertion proved use_stack.adb:9:31: info: precondition proved stack.adb:10:30: info: range check proved stack.adb:11:16: info: index check proved stack.ads:19:14: info: postcondition proved stack.ads:20:60: info: precondition proved stack.ads:33:55: info: index check proved

This example is correct. GNATprove can verify the assertion in Use_Stack because it has visibility to Get_Stack's body.

4.10.9 Example #9

Package Data defines three variables, Data_1, Data_2 and Data_3, that are initialized at elaboration (in Data's package body) from an external interface that reads the file system.

Listing 47:	external	interface	.ads
-------------	----------	-----------	------

```
package External_Interface with
1
     Abstract_State => File_System,
2
     Initializes => File_System
3
   is
4
      type Data_Type_1 is new Integer;
5
      type Data_Type_2 is new Integer;
6
      type Data_Type_3 is new Integer;
7
8
      type Data_Record is record
9
         Field_1 : Data_Type_1;
10
         Field_2 : Data_Type_2;
11
         Field_3 : Data_Type_3;
12
      end record;
13
14
      procedure Read_Data (File_Name : String; Data : out Data_Record)
15
        with Global => File_System;
16
   end External_Interface;
17
```

Listing 48: data.ads

```
with External_Interface; use External_Interface;
1
2
   package Data with
3
     Initializes => (Data_1, Data_2, Data_3)
4
5
   is
      pragma Elaborate_Body;
6
7
      Data_1 : Data_Type_1;
8
      Data_2 : Data_Type_2;
9
      Data_3 : Data_Type_3;
10
11
   end Data;
12
```

Listing 49: data.adb

```
with External_Interface;
1
   pragma Elaborate_All (External_Interface);
2
3
   package body Data is
4
   begin
5
      declare
6
         Data_Read : Data_Record;
7
8
      begin
         Read_Data ("data_file_name", Data_Read);
9
          Data_1 := Data_Read.Field_1;
10
         Data_2 := Data_Read.Field_2;
11
          Data_3 := Data_Read.Field_3;
12
      end;
13
  end Data;
14
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_09
MD5: 0ca44501f0c991865ea50d2ef663d992
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
data.adb:9:07: high: "External_Interface.File_System" must be mentioned as an

input of the Initializes aspect of "Data" (SPARK RM 7.1.5(11))
gnatprove: unproved check messages considered as errors
```

This example isn't correct. The dependency between Data_1's, Data_2's, and Data_3's initial values and File_System must be listed in Data's Initializes aspect.

4.10.10 Example #10

Let's remove the Initializes contract on package Data.

```
Listing 50: external_interface.ads
```

```
package External Interface with
1
     Abstract State => File System,
2
                   => File_System
     Initializes
3
   is
4
      type Data Type 1 is new Integer;
5
      type Data Type 2 is new Integer;
6
      type Data_Type_3 is new Integer;
7
8
      type Data_Record is record
9
         Field_1 : Data_Type_1;
10
         Field_2 : Data_Type_2;
11
         Field_3 : Data_Type_3;
12
      end record;
13
14
      procedure Read_Data (File_Name : String; Data : out Data_Record)
15
        with Global => File System;
16
   end External_Interface;
17
```

Listing 51: data.ads

```
with External_Interface; use External_Interface;
package Data is
pragma Elaborate_Body;
Data_1 : Data_Type_1;
Data_2 : Data_Type_2;
Data_3 : Data_Type_3;
```

```
10 end Data;
```

Listing 52: data.adb

```
with External Interface;
1
   pragma Elaborate All (External Interface);
2
З
   package body Data is
4
   begin
5
      declare
6
         Data_Read : Data_Record;
7
      begin
8
         Read_Data ("data_file_name", Data_Read);
9
         Data_1 := Data_Read.Field_1;
10
```

```
11 Data_2 := Data_Read.Field_2;
12 Data_3 := Data_Read.Field_3;
13 end;
14 end Data;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.State_Abstraction.Example_10
MD5: 60cba2c920c7b1031d13c82a982ed0e9
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: analysis of data and information flow ...
data.adb:7:07: info: initialization of "Data_Read" proved
external_interface.ads:3:03: info: flow dependencies proved
```

This example is correct. Since Data has no Initializes aspect, GNATprove computes the set of variables initialized during its elaboration as well as their dependencies.

PROOF OF FUNCTIONAL CORRECTNESS

This section is dedicated to the functional correctness of programs. It presents advanced proof features that you may need to use for the specification and verification of your program's complex properties.

5.1 Beyond Program Integrity

When we speak about the *correctness* of a program or subprogram, we mean the extent to which it complies with its specification. Functional correctness is specifically concerned with properties that involve the relations between the subprogram's inputs and outputs, as opposed to other properties such as running time or memory consumption.

For functional correctness, we usually specify stronger properties than those required to just prove program integrity. When we're involved in a certification processes, we should derive these properties from the requirements of the system, but, especially in non-certification contexts, they can also come from more informal sources, such as the program's documentation, comments in its code, or test oracles.

For example, if one of our goals is to ensure that no runtime error is raised when using the result of the function Find below, it may be enough to know that the result is either 0 or in the range of A. We can express this as a postcondition of Find.

Listing 1: show_find.ads

```
package Show_Find is
type Nat_Array is array (Positive range <>) of Natural;
function Find (A : Nat_Array; E : Natural) return Natural with
Post => Find'Result in 0 | A'Range;
end Show_Find;
```

```
Listing 2: show_find.adb
```

```
package body Show Find is
1
2
      function Find (A : Nat Array; E : Natural) return Natural is
3
      begin
4
          for I in A'Range loop
5
             if A(I) = E then
6
                return I:
7
             end if:
8
          end loop;
9
          return 0;
10
      end Find:
11
```
12

13 end Show_Find;

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Find_1
MD5: d8f4ace6620fd46af170977c29947289
```

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_find.adb:7:20: info: range check proved show_find.ads:6:14: info: postcondition proved

In this case, it's automatically proved by GNATprove.

However, to be sure that Find performs the task we expect, we may want to verify more complex properties of that function. For example, we want to ensure it returns an index of A where E is stored and returns 0 only if E is nowhere in A. Again, we can express this as a postcondition of Find.

Listing 3: show_find.ads

```
package Show_Find is
1
2
      type Nat_Array is array (Positive range <>) of Natural;
3
4
      function Find (A : Nat Array; E : Natural) return Natural with
5
        Post =>
6
           (if (for all I in A'Range => A (I) /= E)
7
              then Find'Result = 0
8
            else Find'Result in A'Range and then A (Find'Result) = E);
9
10
   end Show_Find;
11
```

Listing 4: show_find.adb

```
package body Show Find is
1
2
      function Find (A : Nat Array; E : Natural) return Natural is
3
      beain
4
          for I in A'Range loop
5
             if A(I) = E then
6
                return I:
7
             end if;
8
          end loop;
9
          return 0;
10
      end Find;
11
12
   end Show_Find;
13
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Find_2
MD5: 8c12b9768228a3ea45ca02199f65057b
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
```

This time, GNATprove can't prove this postcondition automatically, but we'll see later that we can help GNATprove by providing a loop invariant, which is checked by GNATprove and allows it to automatically prove the postcondition for Find.

Writing at least part of your program's specification in the form of contracts has many advantages. You can execute those contracts during testing, which improves the maintainability of the code by detecting discrepancies between the program and its specification in earlier stages of development. If the contracts are precise enough, you can use them as oracles to decide whether a given test passed or failed. In that case, they can allow you to verify the outputs of specific subprograms while running a larger block of code. This may, in certain contexts, replace the need for you to perform unit testing, instead allowing you to run integration tests with assertions enabled. Finally, if the code is in SPARK, you can also use GNATprove to formally prove these contracts.

The advantage of a formal proof is that it verifies all possible execution paths, something which isn't always possible by running test cases. For example, during testing, the post-condition of the subprogram Find shown below is checked dynamically for the set of inputs for which Find is called in that test, but just for that set.

Listing 5: show_find.ads

```
package Show Find is
1
2
      type Nat Array is array (Positive range <>) of Natural;
З
4
      function Find (A : Nat Array; E : Natural) return Natural with
5
        Post =>
6
           (if (for all I in A'Range => A (I) /= E)
7
              then Find'Result = 0
8
            else Find'Result in A'Range and then A (Find'Result) = E);
9
10
   end Show_Find;
11
```

Listing 6: show find.adb

```
package body Show_Find is
1
2
       function Find (A : Nat_Array; E : Natural) return Natural is
3
       begin
4
          for I in A'Range loop
5
             if A(I) = E then
6
                return I;
7
             end if;
8
          end loop;
9
          return 0;
10
       end Find;
11
12
   end Show_Find;
13
```

Listing 7: use_find.adb

```
with Ada.Text_I0; use Ada.Text_I0;
with Show_Find; use Show_Find;
procedure Use_Find with
SPARK Mode => Off
```

```
6 is
7 Seq : constant Nat_Array (1 .. 3) := (1, 5, 3);
8 Res : Natural;
9 begin
10 Res := Find (Seq, 3);
11 Put_Line ("Found 3 in index #" & Natural'Image (Res) & " of array");
12 end Use_Find;
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Find_3
MD5: 05283ef7808ee5d8254cfa4b883e639d

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_find.ads:9:14: medium: postcondition might fail, cannot prove Find'Result in A

→'range
gnatprove: unproved check messages considered as errors
```

Runtime output

Found 3 in index # 3 of array

However, if Find is formally verified, that verification checks its postcondition for all possible inputs. During development, you can attempt such verification earlier than testing since it's performed modularly on a per-subprogram basis. For example, in the code shown above, you can formally verify Use_Find even before you write the body for subprogram Find.

5.2 Advanced Contracts

Contracts for functional correctness are usually more complex than contracts for program integrity, so they more often require you to use the new forms of expressions introduced by the Ada 2012 standard. In particular, quantified expressions, which allow you to specify properties that must hold for all or for at least one element of a range, come in handy when specifying properties of arrays.

As contracts become more complex, you may find it useful to introduce new abstractions to improve the readability of your contracts. Expression functions are a good means to this end because you can retain their bodies in your package's specification.

Finally, some properties, especially those better described as invariants over data than as properties of subprograms, may be cumbersome to express as subprogram contracts. Type predicates, which must hold for every object of a given type, are usually a better match for this purpose. Here's an example.

Listing 8: show_sort.ads

```
package Show_Sort is
type Nat_Array is array (Positive range <>) of Natural;
function Is_Sorted (A : Nat_Array) return Boolean is
(for all I in A'Range =>
   (if I < A'Last then A (I) <= A (I + 1)));
.-- Returns True if A is sorted in increasing order.
</pre>
```

```
subtype Sorted_Nat_Array is Nat_Array with
Dynamic_Predicate => Is_Sorted (Sorted_Nat_Array);
-- Elements of type Sorted_Nat_Array are all sorted.
Good_Array : Sorted_Nat_Array := (1, 2, 4, 8, 42);
end Show_Sort;
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Sort
MD5: d3b3d26d62074d11b19d9282cc548c1b

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_sort.ads:7:32: info: index check proved show_sort.ads:7:43: info: overflow check proved show_sort.ads:7:43: info: index check proved show_sort.ads:14:37: info: range check proved show_sort.ads:14:37: info: predicate check proved

We can use the subtype Sorted_Nat_Array as the type of a variable that must remain sorted throughout the program's execution. Specifying that an array is sorted requires a rather complex expression involving quantifiers, so we abstract away this property as an expression function to improve readability. Is_Sorted's body remains in the package's specification and allows users of the package to retain a precise knowledge of its meaning when necessary. (You must use Nat_Array as the type of the operand of Is_Sorted. If you use Sorted_Nat_Array, you'll get infinite recursion at runtime when assertion checks are enabled since that function is called to check all operands of type Sorted_Nat_Array.)

5.2.1 Ghost Code

As the properties you need to specify grow more complex, you may have entities that are only needed because they are used in specifications (contracts). You may find it important to ensure that these entities can't affect the behavior of the program or that they're completely removed from production code. This concept, having entities that are only used for specifications, is usually called having *ghost* code and is supported in SPARK by the Ghost aspect.

You can use Ghost aspects to annotate any entity including variables, types, subprograms, and packages. If you mark an entity as Ghost, GNATprove ensures it can't affect the program's behavior. When the program is compiled with assertions enabled, ghost code is executed like normal code so it can execute the contracts using it. You can also instruct the compiler to not generate code for ghost entities.

Consider the procedure Do_Something below, which calls a complex function on its input, X, and wants to check that the initial and modified values of X are related in that complex way.

Listing 9: show ghost.ads

```
1 package Show_Ghost is
2
3 type T is record
4 A, B, C, D, E : Boolean;
5 end record;
6
```

```
function Formula (X : T) return Boolean is
    ((X.A and X.B) or (X.C and (X.D or X.E)));

function Is_Correct (X, Y : T) return Boolean is
    (Formula (X) = Formula (Y));

procedure Do_Something (X : in out T);

end Show_Ghost;
```

Listing 10: show_ghost.adb

```
package body Show Ghost is
1
2
      procedure Do Some Complex Stuff (X : in out T) is
3
      begin
4
         X := T'(X.B, X.A, X.C, X.E, X.D);
5
      end Do Some Complex Stuff;
6
7
      procedure Do_Something (X : in out T) is
8
         X Init : constant T := X with Ghost;
9
      begin
10
         Do_Some_Complex_Stuff (X);
11
          pragma Assert (Is_Correct (X_Init, X));
12
          -- It is OK to use X Init inside an assertion.
13
      end Do Something;
14
15
   end Show Ghost;
16
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Ghost_1
MD5: 0a6caaec950b3b043a53c18bab3cb39b

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_ghost.adb:12:22: info: assertion proved
```

Do_Something stores the initial value of X in a ghost constant, X_Init. We reference it in an assertion to check that the computation performed by the call to Do_Some_Complex_Stuff modified the value of X in the expected manner.

However, X_Init can't be used in normal code, for example to restore the initial value of X.

Listing 11: show_ghost.ads

```
package Show_Ghost is
1
2
      type T is record
3
         A, B, C, D, E : Boolean;
4
      end record;
5
6
      function Formula (X : T) return Boolean is
7
         ((X.A and X.B) or (X.C and (X.D or X.E)));
8
9
      function Is Correct (X, Y : T) return Boolean is
10
         (Formula (X) = Formula (Y));
11
12
```

```
procedure Do_Something (X : in out T);
 end Show_Ghost;
```

Listing 12: show_ghost.adb

```
package body Show Ghost is
1
2
      procedure Do_Some_Complex_Stuff (X : in out T) is
3
      begin
4
         X := T'(X.B, X.A, X.C, X.E, X.D);
5
      end Do_Some_Complex_Stuff;
6
7
      procedure Do_Something (X : in out T) is
8
         X Init : constant T := X with Ghost;
9
      begin
10
          Do Some Complex Stuff (X);
11
          pragma Assert (Is Correct (X Init, X));
12
13
         X := X Init; -- ERROR
14
15
      end Do_Something;
16
17
   end Show_Ghost;
18
```

Listing 13: use_ghost.adb

```
with Show_Ghost; use Show_Ghost;
procedure Use_Ghost is
   X : T := (True, True, False, False, True);
begin
   Do_Something (X);
   end Use_Ghost;
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Ghost_2
MD5: 464bb4bc355a648e2b92940ec80b4717
```

Build output

```
show_ghost.adb:14:12: error: ghost entity cannot appear in this context
gprbuild: *** compilation phase failed
```

Prover output

Phase 1 of 2: generation of Global contracts ... show_ghost.adb:14:12: error: ghost entity cannot appear in this context gnatprove: error during generation of Global contracts

When compiling this example, the compiler flags the use of X_Init as illegal, but more complex cases of interference between ghost and normal code may sometimes only be detected when you run GNATprove.

5.2.2 Ghost Functions

Functions used only in specifications are a common occurrence when writing contracts for functional correctness. For example, expression functions used to simplify or factor out common patterns in contracts can usually be marked as ghost.

But ghost functions can do more than improve readability. In real-world programs, it's often the case that some information necessary for functional specification isn't accessible in the package's specification because of abstraction.

Making this information available to users of the packages is generally out of the question because that breaks the abstraction. Ghost functions come in handy in that case since they provide a way to give access to that information without making it available to normal client code.

Let's look at the following example.

```
Listing 14: stacks.ads
```

```
package Stacks is
1
2
      pragma Unevaluated Use Of Old (Allow);
3
4
      type Stack is private;
5
6
      type Element is new Natural;
7
      type Element_Array is array (Positive range <>) of Element;
8
      Max : constant Natural := 100;
9
10
      function Get_Model (S : Stack) return Element_Array with Ghost;
11
          Returns an array as a model of a stack.
12
13
      procedure Push (S : in out Stack; E : Element) with
14
         Pre => Get Model (S)'Length < Max,</pre>
15
         Post => Get_Model (S) = Get_Model (S)'Old & E;
16
17
   private
18
19
      subtype Length_Type is Natural range 0 .. Max;
20
21
      type Stack is record
22
                 : Length Type := 0;
          Тор
23
          Content : Element Array (1 .. Max) := (others => 0);
24
      end record;
25
26
   end Stacks;
27
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Ghost_Functions
MD5: e287612bd66753f07ac3eecb36c693de

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ...

Here, the type Stack is private. To specify the expected behavior of the Push procedure, we need to go inside this abstraction and access the values of the elements stored in S. For this, we introduce a function Get_Model that returns an array as a representation of the stack. However, we don't want code that uses the Stack package to use Get_Model in normal code since this breaks our stack's abstraction.

Here's an example of trying to break that abstraction in the subprogram Peek below.

```
Listing 15: stacks.ads
```

```
package Stacks is
1
2
      pragma Unevaluated Use Of Old (Allow);
3
4
      type Stack is private;
5
6
      type Element is new Natural;
7
      type Element_Array is array (Positive range <>) of Element;
8
      Max : constant Natural := 100;
9
10
      function Get Model (S : Stack) return Element Array with Ghost;
11
       -- Returns an array as a model of a stack.
12
13
      procedure Push (S : in out Stack; E : Element) with
14
         Pre => Get_Model (S)'Length < Max,</pre>
15
         Post => Get_Model (S) = Get_Model (S)'Old & E;
16
17
      function Peek (S : Stack; I : Positive) return Element is
18
         (Get_Model (S) (I)); -- ERROR
19
20
   private
21
22
      subtype Length_Type is Natural range 0 .. Max;
23
24
      type Stack is record
25
                  : Length_Type := 0;
          Top
26
          Content : Element_Array (1 .. Max) := (others => 0);
27
      end record:
28
29
   end Stacks;
30
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Ghost_Model
MD5: c00b5d86c9d0b665ccdda7f68f16f07a

Prover output

```
Phase 1 of 2: generation of Global contracts ...
stacks.ads:19:07: error: ghost entity cannot appear in this context
gnatprove: error during generation of Global contracts
```

We see that marking the function as Ghost achieves this goal: it ensures that the subprogram Get_Model is never used in production code.

5.2.3 Global Ghost Variables

Though it happens less frequently, you may have specifications requiring you to store additional information in global variables that isn't needed in normal code. You should mark these global variables as ghost, allowing the compiler to remove them when assertions aren't enabled. You can use these variables for any purpose within the contracts that make up your specifications. A common scenario is writing specifications for subprograms that modify a complex or private global data structure: you can use these variables to provide a model for that structure that's updated by the ghost code as the program modifies the data structure itself.

You can also use ghost variables to store information about previous runs of subprograms

to specify temporal properties. In the following example, we have two procedures, one that accesses a state A and the other that accesses a state B. We use the ghost variable Last_Accessed_Is_A to specify that B can't be accessed twice in a row without accessing A in between.

Listing 16: call_sequence.ads

```
1
   package Call_Sequence is
2
      type T is new Integer;
3
4
      Last_Accessed_Is_A : Boolean := False with Ghost;
5
6
      procedure Access_A with
7
        Post => Last_Accessed_Is_A;
8
9
      procedure Access_B with
10
        Pre => Last_Accessed_Is_A,
11
        Post => not Last_Accessed_Is_A;
12
13
      -- B can only be accessed after A
14
   end Call_Sequence;
15
```



```
package body Call_Sequence is
1
2
      procedure Access A is
3
      begin
4
5
          Last Accessed Is A := True;
6
      end Access A;
7
8
      procedure Access_B is
9
10
      begin
11
          Last_Accessed_Is_A := False;
12
      end Access B;
13
14
   end Call Sequence;
15
```

Listing 18: main.adb

```
with Call_Sequence; use Call_Sequence;
procedure Main is
begin
Access_A;
Access_B;
Access_B;
Access_B; -- ERROR
end Main;
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Global_Ghost_Vars
MD5: f33fa2ad2bd31eb03d4400c78f22eb71

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
```

```
main.adb:7:04: medium: precondition might fail
gnatprove: unproved check messages considered as errors
```

Runtime output

```
raised ADA.ASSERTIONS.ASSERTION_ERROR : failed precondition from call_sequence. 

→ads:11
```

Let's look at another example. The specification of a subprogram's expected behavior is sometimes best expressed as a sequence of actions it must perform. You can use global ghost variables that store intermediate values of normal variables to write this sort of specification more easily.

For example, we specify the subprogram Do_Two_Things below in two steps, using the ghost variable V_Interm to store the intermediate value of V between those steps. We could also express this using an existential quantification on the variable V_Interm, but it would be impractical to iterate over all integers at runtime and this can't always be written in SPARK because quantification is restricted to **for ... loop** patterns.

Finally, supplying the value of the variable may help the prover verify the contracts.

Listing 19: action_sequence.ads

```
package Action_Sequence is
1
2
      type T is new Integer;
3
4
      V_Interm : T with Ghost;
5
6
      function First_Thing_Done (X, Y : T) return Boolean with Ghost;
7
      function Second_Thing_Done (X, Y : T) return Boolean with Ghost;
8
9
      procedure Do_Two_Things (V : in out T) with
10
        Post => First_Thing_Done (V'Old, V_Interm)
11
          and then Second_Thing_Done (V_Interm, V);
12
13
   end Action_Sequence;
14
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Intermediate_Values
MD5: 2ffbd2cb187c0a81423c78e0989d62f0

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
```

Note: For more details on ghost code, see the SPARK User's Guide²⁴.

 $^{24}\ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/specification_features.html \# ghost-code$

5.3 Guide Proof

Since properties of interest for functional correctness are more complex than those involved in proofs of program integrity, we expect GNATprove to initially be unable to verify them even though they're valid. You'll find the techniques we discussed in *Debugging Failed Proof Attempts* (page 56) to come in handy here. We now go beyond those techniques and focus on more ways of improving results in the cases where the property is valid but GNATprove can't prove it in a reasonable amount of time.

In those cases, you may want to try and guide GNATprove to either complete the proof or strip it down to a small number of easily-reviewable assumptions. For this purpose, you can add assertions to break complex proofs into smaller steps.

```
pragma Assert (Assertion_Checked_By_The_Tool);
-- info: assertion proved
pragma Assert (Assumption_Validated_By_Other_Means);
-- medium: assertion might fail
pragma Assume (Assumption_Validated_By_Other_Means);
-- The tool does not attempt to check this expression.
-- It is recorded as an assumption.
```

One such intermediate step you may find useful is to try to prove a theoretically-equivalent version of the desired property, but one where you've simplified things for the prover, such as by splitting up different cases or inlining the definitions of functions.

Some intermediate assertions may not be proved by GNATprove either because it's missing some information or because the amount of information available is confusing. You can verify these remaining assertions by other means such as testing (since they're executable) or by review. You can then choose to instruct GNATprove to ignore them, either by turning them into assumptions, as in our example, or by using a **pragma** *Annotate*. In both cases, the compiler generates code to check these assumptions at runtime when you enable assertions.

5.3.1 Local Ghost Variables

You can use ghost code to enhance what you can express inside intermediate assertions in the same way we did above to enhance our contracts in specifications. In particular, you'll commonly have local variables or constants whose only purpose is to be used in assertions. You'll mostly use these ghost variables to store previous values of variables or expressions you want to refer to in assertions. They're especially useful to refer to initial values of parameters and expressions since the '0ld attribute is only allowed in postconditions.

In the example below, we want to help GNATprove verify the postcondition of P. We do this by introducing a local ghost constant, X_Init, to represent this value and writing an assertion in both branches of an **if** statement that repeats the postcondition, but using X_Init.

Listing 20: show_local_ghost.ads

```
package Show_Local_Ghost is
type T is new Natural;
function F (X, Y : T) return Boolean is (X > Y) with Ghost;
function Condition (X : T) return Boolean is (X mod 2 = 0);
```

```
9 procedure P (X : in out T) with

10 Pre => X < 1_000_000,

11 Post => F (X, X'0ld);

12

13 end Show_Local_Ghost;
```

Listing 21: show_local_ghost.adb

```
package body Show Local Ghost is
1
2
      procedure P (X : in out T) is
3
         X Init : constant T := X with Ghost;
4
       beain
5
          if Condition (X) then
6
             X := X + 1;
7
             pragma Assert (F (X, X Init));
8
          else
9
             X := X * 2;
10
             pragma Assert (F (X, X_Init));
11
          end if;
12
      end P;
13
14
   end Show Local Ghost;
15
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Local_Ghost MD5: 071ee53a06a6b5880eee6e9ea06dbcf3

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_local_ghost.adb:7:17: info: overflow check proved
show_local_ghost.adb:10:17: info: overflow check proved
show_local_ghost.adb:11:25: info: assertion proved
show_local_ghost.ads:7:52: info: division check proved
show_local_ghost.ads:11:14: info: postcondition proved
```

You can also use local ghost variables for more complex purposes such as building a data structure that serves as witness for a complex property of a subprogram. In our example, we want to prove that the Sort procedure doesn't create new elements, that is, that all the elements present in A after the sort were in A before the sort. This property isn't enough to ensure that a call to Sort produces a value for A that's a permutation of its value before the call (or that the values are indeed sorted). However, it's already complex for a prover to verify because it involves a nesting of quantifiers. To help GNATprove, you may find it useful to store, for each index I, an index J that has the expected property.

5.3.2 Ghost Procedures

Ghost procedures can't affect the value of normal variables, so they're mostly used to perform operations on ghost variables or to group together a set of intermediate assertions.

Abstracting away the treatment of assertions and ghost variables inside a ghost procedure has several advantages. First, you're allowed to use these variables in any way you choose in code inside ghost procedures. This isn't the case outside ghost procedures, where the only ghost statements allowed are assignments to ghost variables and calls to ghost procedures.

As an example, the **for** loop contained in Increase_A couldn't appear by itself in normal code.

Listing 22:	show	ghost	proc.ads
-------------	------	-------	----------

```
package Show_Ghost_Proc is
1
2
      type Nat_Array is array (Integer range <>) of Natural;
3
4
      A : Nat Array (1 .. 100) with Ghost;
5
6
      procedure Increase A with
7
         Ghost,
8
         Pre => (for all I in A'Range => A (I) < Natural'Last);</pre>
9
10
   end Show_Ghost_Proc;
11
```

Listing 25. Show ghost proclaus	Listing	23:	show	ghost	proc.adb
---------------------------------	---------	-----	------	-------	----------

```
package body Show Ghost Proc is
1
2
      procedure Increase A is
3
      beain
4
          for I in A'Range loop
5
             A(I) := A(I) + 1;
6
         end loop:
7
      end Increase A;
8
   end Show Ghost Proc;
10
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Ghost_Proc MD5: 4b9cfe25011169a0cd3b4a3b03135dc4

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_ghost_proc.adb:6:25: info: overflow check proved
```

Using the abstraction also improves readability by hiding complex code that isn't part of the functional behavior of the subprogram. Finally, it can help GNATprove by abstracting away assertions that would otherwise make its job more complex.

In the example below, calling Prove_P with X as an operand only adds P (X) to the proof context instead of the larger set of assertions required to verify it. In addition, the proof of P need only be done once and may be made easier not having any unnecessary information present in its context while verifying it. Also, if GNATprove can't fully verify Prove_P, you can review the remaining assumptions more easily since they're in a smaller context.

```
procedure Prove_P (X : T) with Ghost,
Global => null,
Post => P (X);
```

5.3.3 Handling of Loops

When the program involves a loop, you're almost always required to provide additional annotations to allow GNATprove to complete a proof because the verification techniques used by GNATprove don't handle cycles in a subprogram's control flow. Instead, loops are flattened by dividing them into several acyclic parts.

As an example, let's look at a simple loop with an exit condition.

```
Stmt1;
loop
Stmt2;
exit when Cond;
Stmt3;
end loop;
Stmt4;
```

As shown below, the control flow is divided into three parts.



The first, shown in yellow, starts earlier in the subprogram and enters the loop statement. The loop itself is divided into two parts. Red represents a complete execution of the loop's body: an execution where the exit condition isn't satisfied. Blue represents the last execution of the loop, which includes some of the subprogram following it. For that path, the exit condition is assumed to hold. The red and blue parts are always executed after the yellow one.

GNATprove analyzes these parts independently since it doesn't have a way to track how variables may have been updated by an iteration of the loop. It forgets everything it knows about those variables from one part when entering another part. However, values of constants and variables that aren't modified in the loop are not an issue.

In other words, handling loops in that way makes GNATprove imprecise when verifying a subprogram involving a loop: it can't verify a property that relies on values of variables modified inside the loop. It won't forget any information it had on the value of constants or unmodified variables, but it nevertheless won't be able to deduce new information about them from the loop.

For example, consider the function Find which iterates over the array A and searches for an element where E is stored in A.

Listing Z+, show mutaus	L	isting	24:	show	find	.ads
-------------------------	---	--------	-----	------	------	------

1	package	Show_	Find	is

```
type Nat_Array is array (Positive range <>) of Natural;
function Find (A : Nat_Array; E : Natural) return Natural;
end Show_Find;
```

Listing 25: show_find.adb

```
package body Show Find is
1
2
      function Find (A : Nat Array; E : Natural) return Natural is
3
      begin
4
          for I in A'Range loop
5
             pragma Assert (for all J in A'First .. I - 1 => A (J) /= E);
6
             -- assertion is not proved
7
             if A(I) = E then
8
                return I;
9
             end if;
10
             pragma Assert (A (I) /= E);
11
             -- assertion is proved
12
         end loop;
13
          return 0:
14
      end Find;
15
16
  end Show Find;
17
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Loop MD5: cb9cd0cb102c3baba3b21a788b6e4ae3

Prover output

Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show_find.adb:6:51: info: overflow check proved
show_find.adb:6:58: medium: assertion might fail, cannot prove A (J) /= E_u
 [possible fix: subprogram at show_find.ads:5 should mention A and E in a_u
 precondition]
show_find.adb:6:61: info: index check proved
show_find.adb:9:20: info: range check proved
show_find.adb:11:25: info: assertion proved
gnatprove: unproved check messages considered as errors

At the end of each loop iteration, GNATprove knows that the value stored at index I in A must not be E. (If it were, the loop wouldn't have reached the end of the interation.) This proves the second assertion. But it's unable to aggregate this information over multiple loop iterations to deduce that it's true for all the indexes smaller than I, so it can't prove the first assertion.

5.3.4 Loop Invariants

To overcome these limitations, you can provide additional information to GNATprove in the form of a *loop invariant*. In SPARK, a loop invariant is a Boolean expression which holds true at every iteration of the loop. Like other assertions, you can have it checked at runtime by compiling the program with assertions enabled.

The major difference between loop invariants and other assertions is the way it's treated for proofs. GNATprove performs the proof of a loop invariant in two steps: first, it checks that it holds for the first iteration of the loop and then it checks that it holds in an arbitrary iteration assuming it held in the previous iteration. This is called proof by induction²⁵.

As an example, let's add a loop invariant to the Find function stating that the first element of A is not E.

```
Listing 26: show_find.ads
```

```
package Show_Find is
type Nat_Array is array (Positive range <>) of Natural;
function Find (A : Nat_Array; E : Natural) return Natural;
end Show_Find;
```



```
package body Show Find is
1
2
      function Find (A : Nat Array; E : Natural) return Natural is
З
      begin
4
          for I in A'Range loop
5
             pragma Loop Invariant (A (A'First) /= E);
6
             -- loop invariant not proved in first iteration
7
             -- but preservation of loop invariant is proved
8
             if A(I) = E then
9
                return I:
10
             end if:
11
         end loop:
12
          return 0:
13
      end Find:
14
15
   end Show Find;
16
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Loop_Invariant_1
MD5: 8d5fefdca9deacd4eb50850be91fbefe

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

show_find.adb:6:33: info: loop invariant preservation proved

show_find.adb:6:33: medium: loop invariant might fail in first iteration [possible_

_______fix: subprogram at show_find.ads:5 should mention A and E in a precondition]

show_find.adb:6:37: info: index check proved

show_find.adb:10:20: info: range check proved

gnatprove: unproved check messages considered as errors
```

²⁵ https://en.wikipedia.org/wiki/Mathematical_induction

To verify this invariant, GNATprove generates two checks. The first checks that the assertion holds in the first iteration of the loop. This isn't verified by GNATprove. And indeed there's no reason to expect the first element of A to always be different from E in this iteration. However, the second check is proved: it's easy to deduce that if the first element of A was not E in a given iteration it's still not E in the next. However, if we move the invariant to the end of the loop, then it is successfully verified by GNATprove.

Not only do loop invariants allow you to verify complex properties of loops, but GNATprove also uses them to verify other properties, such as the absence of runtime errors over both the loop's body and the statements following the loop. More precisely, when verifying a runtime check or other assertion there, GNATprove assumes that the last occurrence of the loop invariant preceding the check or assertion is true.

Let's look at a version of Find where we use a loop invariant instead of an assertion to state that none of the array elements seen so far are equal to E.

Listing 28: show_find.ads

```
package Show_Find is
type Nat_Array is array (Positive range <>) of Natural;
function Find (A : Nat_Array; E : Natural) return Natural;
end Show_Find;
```

Listing 29: show_find.adb

```
package body Show Find is
1
2
      function Find (A : Nat Array; E : Natural) return Natural is
3
      begin
4
          for I in A'Range loop
5
             pragma Loop_Invariant
6
               (for all J in A'First .. I - 1 => A (J) /= E);
7
             if A(I) = E then
8
                return I;
9
             end if;
10
          end loop;
11
          pragma Assert (for all I in A'Range => A (I) /= E);
12
          return 0;
13
      end Find;
14
15
   end Show_Find;
16
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Loop_Invariant_2
MD5: 21588161eaddb82f54c3cb3dcc14a6ac

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_find.adb:7:13: info: loop invariant initialization proved show_find.adb:7:13: info: loop invariant preservation proved show_find.adb:7:39: info: overflow check proved show_find.adb:7:49: info: index check proved show_find.adb:9:20: info: range check proved show_find.adb:12:22: info: assertion proved show_find.adb:12:49: info: index check proved

This version is fully verified by GNATprove! This time, it proves that the loop invariant holds

in every iteration of the loop (separately proving this property for the first iteration and then for the following iterations). It also proves that none of the elements of A are equal to E after the loop exits by assuming that the loop invariant holds in the last iteration of the loop.

Note: For more details on loop invariants, see the SPARK User's Guide²⁶.

Finding a good loop invariant can turn out to be quite a challenge. To make this task easier, let's review the four good properties of a good loop invariant:

Prop- erty	Description
INIT	It should be provable in the first iteration of the loop.
INSIDE	It should allow proving the absence of run-time errors and local assertions inside the loop.
AFTER	It should allow proving absence of run-time errors, local assertions, and the subprogram postcondition after the loop.
PRE- SERVE	It should be provable after the first iteration of the loop.

Let's look at each of these in turn. First, the loop invariant should be provable in the first iteration of the loop (INIT). If your invariant fails to achieve this property, you can debug the loop invariant's initialization like any failing proof attempt using strategies for *Debugging Failed Proof Attempts* (page 56).

Second, the loop invariant should be precise enough to allow GNATprove to prove absence of runtime errors in both statements from the loop's body (INSIDE) and those following the loop (AFTER). To do this, you should remember that all information concerning a variable modified in the loop that's not included in the invariant is forgotten by GNATprove. In particular, you should take care to include in your invariant what's usually called the loop's *frame condition*, which lists properties of variables that are true throughout the execution of the loop even though those variables are modified by the loop.

Finally, the loop invariant should be precise enough to prove that it's preserved through successive iterations of the loop (PRESERVE). This is generally the trickiest part. To understand why GNATprove hasn't been able to verify the preservation of a loop invariant you provided, you may find it useful to repeat it as local assertions throughout the loop's body to determine at which point it can no longer be proved.

As an example, let's look at a loop that iterates through an array A and applies a function F to each of its elements.

Listing 30: show_map.ads

```
package Show Map is
1
2
      type Nat Array is array (Positive range <>) of Natural;
3
4
      function F (V : Natural) return Natural is
5
        (if V /= Natural'Last then V + 1 else V);
6
7
      procedure Map (A : in out Nat Array);
8
a
   end Show Map;
10
```

²⁶ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/assertion_pragmas.html# loop-invariants

Listing 31: show_map.adb

```
package body Show Map is
1
2
      procedure Map (A : in out Nat Array) is
3
         A I : constant Nat Array := A with Ghost;
4
      begin
5
         for K in A'Range loop
6
             A(K) := F(A(K));
7
             pragma Loop_Invariant
8
               (for all J in A'First .. K => A (J) = F (A'Loop_Entry (J)));
9
         end loop;
10
         pragma Assert (for all K in A'Range => A (K) = F (A I (K)));
11
      end Map;
12
13
   end Show Map;
14
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Loop_Invariant_3
MD5: 1a4583c9b2b772f79bcf29cff0caa96a

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... show_map.adb:9:13: info: loop invariant initialization proved show_map.adb:9:13: info: loop invariant preservation proved show_map.adb:9:45: info: index check proved show_map.adb:9:67: info: index check proved show_map.adb:11:22: info: assertion proved show_map.adb:11:49: info: index check proved show_map.adb:11:62: info: index check proved show_map.adb:11:62: info: overflow check proved

After the loop, each element of A should be the result of applying F to its previous value. We want to prove this. To specify this property, we copy the value of A before the loop into a ghost variable, A_I. Our loop invariant states that the element at each index less than K has been modified in the expected way. We use the Loop_Entry attribute to refer to the value of A on entry of the loop instead of using A_I.

Does our loop invariant have the four properties of a good loop-invariant? When launching GNATprove, we see that INIT is fulfilled: the invariant's initialization is proved. So are INSIDE and AFTER: no potential runtime errors are reported and the assertion following the loop is successfully verified.

The situation is slightly more complex for the PRESERVE property. GNATprove manages to prove that the invariant holds after the first iteration thanks to the automatic generation of frame conditions. It was able to do this because it completes the provided loop invariant with the following frame condition stating what part of the array hasn't been modified so far:

pragma Loop_Invariant
 (for all J in K .. A'Last => A (J) = (if J > K then A'Loop_Entry (J)));

GNATprove then uses both our and the internally-generated loop invariants to prove PRE-SERVE. However, in more complex cases, the heuristics used by GNATprove to generate the frame condition may not be sufficient and you'll have to provide one as a loop invariant. For example, consider a version of Map where the result of applying F to an element at index K is stored at index K-1: Listing 32: show_map.ads

```
package Show_Map is
type Nat_Array is array (Positive range <>) of Natural;
function F (V : Natural) return Natural is
(if V /= Natural'Last then V + 1 else V);
procedure Map (A : in out Nat_Array);
end Show_Map;
```



```
package body Show_Map is
1
2
      procedure Map (A : in out Nat_Array) is
3
         A_I : constant Nat_Array := A with Ghost;
4
      begin
5
          for K in A'Range loop
6
             if K /= A'First then
7
                A (K - 1) := F (A (K));
8
             end if;
9
             pragma Loop_Invariant
10
               (for all J in A'First .. K =>
11
                 (if J /= A'First then A (J - 1) = F (A'Loop_Entry (J))));
12
13
             - -
                 pragma Loop_Invariant
                 (for all J in K .. A'Last => A (J) = A'Loop_Entry (J));
             - -
14
          end loop;
15
          pragma Assert (for all K in A'Range =>
16
                           (if K /= A'First then A (K - 1) = F (A_I (K)));
17
      end Map;
18
19
   end Show_Map;
20
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Loop_Invariant_4
MD5: 6c51768547d3baa2c19d0e33959388fe

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
show map.adb:8:18: info: overflow check proved
show map.adb:8:18: info: index check proved
show map.adb:11:13: info: loop invariant initialization proved
show map.adb:12:36: medium: loop invariant might not be preserved by an arbitrary,
\ominusiteration, cannot prove A (J - 1) = F (A'Loop Entry (J))
show map.adb:12:41: info: overflow check proved
show_map.adb:12:41: info: index check proved
show_map.adb:12:65: info: index check proved
show_map.adb:16:22: info: assertion proved
show_map.adb:17:50: info: overflow check proved
show_map.adb:17:50: info: index check proved
show_map.adb:17:65: info: index check proved
show_map.ads:6:35: info: overflow check proved
gnatprove: unproved check messages considered as errors
```

You need to uncomment the second loop invariant containing the frame condition in order to prove the assertion after the loop.

Note: For more details on how to write a loop invariant, see the SPARK User's Guide²⁷.

5.4 Code Examples / Pitfalls

This section contains some code examples and pitfalls.

5.4.1 Example #1

We implement a ring buffer inside an array Content, where the contents of a ring buffer of length Length are obtained by starting at index First and possibly wrapping around the end of the buffer. We use a ghost function Get_Model to return the contents of the ring buffer for use in contracts.

Listing 34: ring buffer.ads

```
package Ring_Buffer is
1
2
      Max Size : constant := 100;
3
4
      type Nat_Array is array (Positive range <>) of Natural;
5
6
      function Get_Model return Nat_Array with Ghost;
7
8
      procedure Push Last (E : Natural) with
9
         Pre => Get_Model'Length < Max_Size,</pre>
10
         Post => Get_Model'Length = Get_Model'Old'Length + 1;
11
12
   end Ring_Buffer;
13
```

Listing 35: ring_buffer.adb

```
package body Ring Buffer is
1
2
      subtype Length_Range is Natural range 0 .. Max Size;
3
      subtype Index Range is Natural range 1 .. Max Size;
4
5
      Content : Nat_Array (1 .. Max_Size) := (others => 0);
6
      First : Index Range
                                            := 1;
7
      Length : Length Range
                                            := 0:
8
9
      function Get Model return Nat Array with
10
        Refined Post => Get Model'Result'Length = Length
11
      is
12
               : constant Length Range := Length;
         Size
13
         Result : Nat_Array (1 .. Size) := (others => 0);
14
      begin
15
         if First + Length - 1 <= Max_Size then</pre>
16
            Result := Content (First .. First + Length - 1);
17
         else
18
            declare
19
                Len : constant Length Range := Max Size - First + 1;
20
21
            begin
                Result (1 .. Len) := Content (First .. Max_Size);
22
```

(continues on next page)

²⁷ https://docs.adacore.com/live/wave/spark2014/html/spark2014_ug/en/source/how_to_write_loop_invariants. html

```
Result (Len + 1 .. Length) := Content (1 .. Length - Len);
23
              end;
24
          end if;
25
          return Result;
26
       end Get_Model;
27
28
       procedure Push_Last (E : Natural) is
29
       beain
30
          if First + Length <= Max Size then</pre>
31
              Content (First + Length) := E;
32
          else
33
              Content (Length - Max_Size + First) := E;
34
          end if;
35
          Length := Length + 1;
36
       end Push_Last;
37
38
   end Ring_Buffer;
39
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_01
MD5: 3afd7d58f97001618acc05062115f1a3

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
ring buffer.adb:11:22: info: refined post proved
ring buffer.adb:11:38: info: range check proved
ring_buffer.adb:14:07: info: range check proved
ring_buffer.adb:14:41: info: length check proved
ring_buffer.adb:17:17: info: length check proved
ring_buffer.adb:17:20: info: range check proved
ring_buffer.adb:17:20: info: length check proved
ring_buffer.adb:20:61: info: range check proved
ring_buffer.adb:22:13: info: range check proved
ring_buffer.adb:22:31: info: length check proved
ring buffer.adb:22:34: info: range check proved
ring buffer.adb:22:34: info: length check proved
ring buffer.adb:23:13: info: range check proved
ring buffer.adb:23:40: info: length check proved
ring buffer.adb:23:43: info: range check proved
ring buffer.adb:23:43: info: length check proved
ring_buffer.adb:32:25: info: index check proved
ring buffer.adb:34:37: info: index check proved
ring buffer.adb:36:24: info: range check proved
ring buffer.ads:11:14: info: postcondition proved
```

This is correct: Get_Model is used only in contracts. Calls to Get_Model make copies of the buffer's contents, which isn't efficient, but is fine because Get_Model is only used for verification, not in production code. We enforce this by making it a ghost function. We'll produce the final production code with appropriate compiler switches (i.e., not using -gnata) that ensure assertions are ignored.

5.4.2 Example #2

Instead of using a ghost function, Get_Model, to retrieve the contents of the ring buffer, we're now using a global ghost variable, Model.

```
Listing 36: ring_buffer.ads
```

```
package Ring_Buffer is
1
2
      Max_Size : constant := 100;
3
      subtype Length_Range is Natural range 0 .. Max_Size;
4
      subtype Index_Range is Natural range 1 .. Max_Size;
5
6
      type Nat_Array is array (Positive range <>) of Natural;
7
8
      type Model_Type (Length : Length_Range := 0) is record
9
         Content : Nat_Array (1 .. Length);
10
      end record
11
        with Ghost;
12
13
      Model : Model_Type with Ghost;
14
15
      function Valid_Model return Boolean;
16
17
      procedure Push_Last (E : Natural) with
18
         Pre => Valid Model
19
           and then Model.Length < Max_Size,
20
         Post => Model.Length = Model.Length'Old + 1;
21
22
   end Ring_Buffer;
23
```

Listing 37: ring_buffer.adb

```
package body Ring_Buffer is
1
2
      Content : Nat_Array (1 .. Max_Size) := (others => 0);
3
      First : Index_Range
                                              := 1:
4
      Length : Length_Range
                                              := 0;
5
6
      function Valid Model return Boolean is
7
          (Model.Content'Length = Length);
8
9
      procedure Push_Last (E : Natural) is
10
11
      begin
          if First + Length <= Max_Size then</pre>
12
             Content (First + Length) := E;
13
         else
14
             Content (Length - Max_Size + First) := E;
15
          end if;
16
         Length := Length + 1;
17
      end Push Last;
18
19
   end Ring Buffer;
20
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_02
MD5: 144f58bd95cd460e4ed388d4f3351fe3
```

Build output

ring_buffer.adb:8:08: error: ghost entity cannot appear in this context
gprbuild: *** compilation phase failed

Prover output

Phase 1 of 2: generation of Global contracts ... ring_buffer.adb:8:08: error: ghost entity cannot appear in this context gnatprove: error during generation of Global contracts

This example isn't correct. Model, which is a ghost variable, must not influence the return value of the normal function Valid_Model. Since Valid_Model is only used in specifications, we should have marked it as Ghost. Another problem is that Model needs to be updated inside Push_Last to reflect the changes to the ring buffer.

5.4.3 Example #3

Let's mark Valid_Model as Ghost and update Model inside Push_Last.

Listing 38: ring_buffer.ads

```
package Ring Buffer is
1
2
      Max Size : constant := 100;
3
      subtype Length_Range is Natural range 0 .. Max_Size;
4
      subtype Index_Range is Natural range 1 .. Max_Size;
5
6
      type Nat_Array is array (Positive range <>) of Natural;
7
8
      type Model Type (Length : Length Range := 0) is record
9
10
         Content : Nat_Array (1 .. Length);
      end record
11
        with Ghost;
12
13
      Model : Model Type with Ghost;
14
15
      function Valid Model return Boolean with Ghost;
16
17
      procedure Push Last (E : Natural) with
18
        Pre => Valid Model
19
          and then Model.Length < Max Size,
20
         Post => Model.Length = Model.Length'Old + 1;
21
22
   end Ring_Buffer;
23
```

Listing 39: ring_buffer.adb

```
package body Ring_Buffer is
1
2
      Content : Nat_Array (1 .. Max_Size) := (others => 0);
3
               : Index_Range
      First
                                             := 1:
4
      Length : Length_Range
                                             := 0;
5
6
      function Valid Model return Boolean is
7
          (Model.Content'Length = Length);
8
9
10
      procedure Push_Last (E : Natural) is
      begin
11
          if First + Length <= Max_Size then</pre>
12
             Content (First + Length) := E;
13
```

```
else
14
             Content (Length - Max_Size + First) := E;
15
          end if;
16
          Length := Length + 1;
17
          Model := (Length => Model.Length + 1,
18
                     Content => Model.Content & E);
19
       end Push_Last;
20
21
   end Ring_Buffer;
22
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_03
MD5: 08b74f5fe560d238550a06c6323959cf

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

ring_buffer.adb:8:21: info: range check proved

ring_buffer.adb:13:25: info: index check proved

ring_buffer.adb:15:37: info: index check proved

ring_buffer.adb:17:24: info: range check proved

ring_buffer.adb:18:13: info: discriminant check proved

ring_buffer.adb:18:41: info: range check proved

ring_buffer.adb:19:42: info: range check proved

ring_buffer.adb:19:42: info: range check proved

ring_buffer.adb:19:42: info: length check proved

ring_buffer.ads:10:07: info: range check proved
```

This example is correct. The ghost variable Model can be referenced both from the body of the ghost function Valid_Model and the non-ghost procedure Push_Last as long as it's only used in ghost statements.

5.4.4 Example #4

We're now modifying Push_Last to share the computation of the new length between the operational and ghost code.

Listing 40: ring_buffer.ads

```
package Ring Buffer is
1
      Max Size : constant := 100;
3
      subtype Length Range is Natural range 0 .. Max Size;
4
      subtype Index_Range is Natural range 1 .. Max_Size;
5
6
      type Nat Array is array (Positive range <>) of Natural;
7
8
      type Model_Type (Length : Length_Range := 0) is record
9
         Content : Nat Array (1 .. Length);
10
      end record
11
        with Ghost;
12
13
      Model : Model Type with Ghost;
14
15
      function Valid Model return Boolean with Ghost;
16
17
      procedure Push_Last (E : Natural) with
18
```

```
Pre => Valid_Model
and then Model.Length < Max_Size,
Post => Model.Length = Model.Length'Old + 1;
end Ring_Buffer;
```

Listing 41: ring_buffer.adb

```
package body Ring Buffer is
1
2
      Content : Nat_Array (1 .. Max_Size) := (others => 0);
3
               : Index Range
      First
                                             := 1:
4
      Length : Length_Range
                                             := 0;
5
6
      function Valid Model return Boolean is
7
          (Model.Content'Length = Length);
8
9
      procedure Push Last (E : Natural) is
10
         New_Length : constant Length_Range := Model.Length + 1;
11
      beain
12
          if First + Length <= Max_Size then</pre>
13
             Content (First + Length) := E;
14
          else
15
             Content (Length - Max_Size + First) := E;
16
          end if;
17
          Length := New Length;
18
         Model := (Length => New Length,
19
                     Content => Model.Content & E);
20
      end Push_Last;
21
22
   end Ring Buffer;
23
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_04
MD5: e27f0b4729be72d83f2cb981b1d00412
```

Build output

ring_buffer.adb:11:45: error: ghost entity cannot appear in this context
gprbuild: *** compilation phase failed

Prover output

Phase 1 of 2: generation of Global contracts ... ring_buffer.adb:11:45: error: ghost entity cannot appear in this context gnatprove: error during generation of Global contracts

This example isn't correct. We didn't mark local constant New_Length as Ghost, so it can't be computed from the value of ghost variable Model. If we made New_Length a ghost constant, the compiler would report the problem on the assignment from New_Length to Length. The correct solution here is to compute New_Length from the value of the non-ghost variable Length.

5.4.5 Example #5

Let's move the code updating Model inside a local ghost procedure, Update_Model, but still using a local variable, New_Length, to compute the length.

```
Listing 42: ring_buffer.ads
```

```
package Ring_Buffer is
1
2
      Max_Size : constant := 100;
3
      subtype Length_Range is Natural range 0 .. Max_Size;
4
      subtype Index_Range is Natural range 1 .. Max_Size;
5
6
      type Nat_Array is array (Positive range <>) of Natural;
7
8
      type Model_Type (Length : Length_Range := 0) is record
9
         Content : Nat_Array (1 .. Length);
10
      end record
11
        with Ghost;
12
13
      Model : Model_Type with Ghost;
14
15
      function Valid_Model return Boolean with Ghost;
16
17
      procedure Push_Last (E : Natural) with
18
         Pre => Valid Model
19
          and then Model.Length < Max_Size,
20
         Post => Model.Length = Model.Length'Old + 1;
21
22
   end Ring_Buffer;
23
```

Listing 43: ring_buffer.adb

```
package body Ring_Buffer is
1
2
       Content : Nat_Array (1 .. Max_Size) := (others => 0);
3
       First : Index_Range
                                              := 1:
4
       Length : Length_Range
                                              := 0;
5
6
       function Valid Model return Boolean is
7
          (Model.Content'Length = Length);
8
9
       procedure Push_Last (E : Natural) is
10
11
          procedure Update_Model with Ghost is
12
             New_Length : constant Length_Range := Model.Length + 1;
13
          begin
14
             Model := (Length => New Length,
15
                        Content => Model.Content & E);
16
          end Update_Model;
17
18
       begin
19
          if First + Length <= Max_Size then</pre>
20
             Content (First + Length) := E;
21
          else
22
             Content (Length - Max_Size + First) := E;
23
          end if;
24
          Length := Length + 1;
25
          Update Model;
26
       end Push Last;
27
28
   end Ring_Buffer;
29
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_05
MD5: cc97fb35205c9a6de06001cf489f34e9
```

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
ring_buffer.adb:8:21: info: range check proved
ring_buffer.adb:13:61: info: range check proved, in call inlined at ring_buffer.
→adb:26
ring buffer.adb:15:16: info: discriminant check proved, in call inlined at ring
→buffer.adb:26
ring_buffer.adb:16:45: info: range check proved, in call inlined at ring_buffer.
→adb:26
ring buffer.adb:16:45: info: length check proved, in call inlined at ring buffer.
→adb:26
ring buffer.adb:21:25: info: index check proved
ring_buffer.adb:23:37: info: index check proved
ring_buffer.adb:25:24: info: range check proved
ring_buffer.ads:10:07: info: range check proved
ring_buffer.ads:21:14: info: postcondition proved
```

Everything's fine here. Model is only accessed inside Update_Model, itself a ghost procedure, so it's fine to declare local variable New_Length without the Ghost aspect: everything inside a ghost procedure body is ghost. Moreover, we don't need to add any contract to Update_Model: it's inlined by GNATprove because it's a local procedure without a contract.

5.4.6 Example #6

The function Max_Array takes two arrays of the same length (but not necessarily with the same bounds) as arguments and returns an array with each entry being the maximum values of both arguments at that index.

Listing 44: array util.ads

```
package Array_Util is
type Nat_Array is array (Positive range <>) of Natural;
function Max_Array (A, B : Nat_Array) return Nat_Array with
Pre => A'Length = B'Length;
end Array_Util;
```

Listing 45: array util.adb

```
package body Array Util is
1
2
      function Max Array (A, B : Nat Array) return Nat Array is
3
         R : Nat Array (A'Range);
4
         J : Integer := B'First;
5
      begin
6
         for I in A'Range loop
7
            if A(I) > B(J) then
8
                R(I) := A(I);
9
             else
10
               R(I) := B(J);
11
             end if:
12
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_06
MD5: 4b8a6a9b1a3d4d228fe1e944914084fe

Prover output

Phase 1 of 2: generation of Global contracts ... Phase 2 of 2: flow analysis and proof ... array_util.adb:8:24: medium: array index check might fail [reason for check: value_ □must be a valid index into the array] [possible fix: loop at line 7 should_ □mention J in a loop invariant] array_util.adb:13:17: medium: overflow check might fail, cannot prove upper bound_ □for J + 1 [reason for check: result of addition must fit in a 32-bits machine_ □integer] [possible fix: loop at line 7 should mention J in a loop invariant] gnatprove: unproved check messages considered as errors

This program is correct, but GNATprove can't prove that J is always in the index range of B (the unproved index check) or even that it's always within the bounds of its type (the unproved overflow check). Indeed, when checking the body of the loop, GNATprove forgets everything about the current value of J because it's been modified by previous loop iterations. To get more precise results, we need to provide a loop invariant.

5.4.7 Example #7

Let's add a loop invariant that states that J stays in the index range of B and let's protect the increment to J by checking that it's not already the maximal integer value.

Listing 46: array util.ads

```
package Array_Util is
type Nat_Array is array (Positive range <>) of Natural;
function Max_Array (A, B : Nat_Array) return Nat_Array with
Pre => A'Length = B'Length;
end Array_Util;
```

Listing 47: array util.adb

```
package body Array_Util is
1
2
      function Max_Array (A, B : Nat_Array) return Nat_Array is
3
         R : Nat_Array (A'Range);
4
         J : Integer := B'First;
5
      begin
6
         for I in A'Range loop
7
            pragma Loop_Invariant (J in B'Range);
8
             if A(I) > B(J) then
9
                R(I) := A(I);
10
```

```
else
11
                  R(I) := B(J);
12
              end if;
13
              if J < Integer'Last then</pre>
14
                  J := J + 1;
15
              end if;
16
          end loop;
17
           return R;
18
       end Max_Array;
19
20
   end Array Util;
21
```

Code block metadata

```
Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_07
MD5: 917629e0683725c23198f8a905a73c57
```

Prover output

The loop invariant now allows verifying that no runtime error can occur in the loop's body (property INSIDE seen in section *Loop Invariants* (page 117)). Unfortunately, GNATprove fails to verify that the invariant stays valid after the first iteration of the loop (property PRESERVE). Indeed, knowing that J is in B'Range in a given iteration isn't enough to prove it'll remain so in the next iteration. We need a more precise invariant, linking J to the value of the loop index I, like J = I - A'First + B'First.

5.4.8 Example #8

We now consider a version of Max_Array which takes arguments that have the same bounds. We want to prove that Max_Array returns an array of the maximum values of both its arguments at each index.

Listing 48: array_util.ads

```
package Array_Util is
1
2
      type Nat Array is array (Positive range <>) of Natural;
3
4
      function Max Array (A, B : Nat Array) return Nat Array with
5
        Pre => A'First = B'First and A'Last = B'Last,
6
        Post => (for all K in A'Range =>
7
                   Max_Array'Result (K) = Natural'Max (A (K), B (K)));
8
   end Array_Util;
10
```

Listing 49: array util.adb

```
package body Array_Util is
function Max_Array (A, B : Nat_Array) return Nat_Array is
R : Nat_Array (A'Range) := (others => 0);
begin
```

```
for I in A'Range loop
6
             pragma Loop_Invariant (for all K in A'First .. I =>
7
                                       R(K) = Natural'Max (A(K), B(K)));
8
             if A(I) > B(I) then
9
                R(I) := A(I);
10
             else
11
                R(I) := B(I);
12
             end if;
13
         end loop;
14
          return R;
15
      end Max_Array;
16
17
   end Array_Util;
18
```

Listing 50: main.adb

```
with Array Util; use Array Util;
1
2
   procedure Main is
3
      A : Nat_Array := (1, 1, 2);
4
      B : Nat_Array := (2, 1, 0);
5
      R : Nat_Array (1 .. 3);
6
  begin
7
      R := Max_Array (A, B);
8
  end Main;
a
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_08
MD5: d0a04c214a632466a4fe4ec6cb7f8842

Prover output

```
Phase 1 of 2: generation of Global contracts ...

Phase 2 of 2: flow analysis and proof ...

main.adb:8:09: medium: length check might fail [reason for check: array must be of

othe appropriate length]

array_util.adb:8:35: medium: loop invariant might not be preserved by an arbitrary

oiteration, cannot prove R (K) = Natural'max

array_util.adb:8:35: medium: loop invariant might fail in first iteration, cannot

oprove R (K) = Natural'max

gnatprove: unproved check messages considered as errors
```

Runtime output

raised ADA.ASSERTIONS.ASSERTION_ERROR : Loop_Invariant failed at array_util.adb:7

Here, GNATprove doesn't manage to prove the loop invariant even for the first loop iteration (property INIT seen in section *Loop Invariants* (page 117)). In fact, the loop invariant is incorrect, as you can see by executing the function Max_Array with assertions enabled: at each loop iteration, R contains the maximum of A and B only until I - 1 because the I'th index wasn't yet handled.

5.4.9 Example #9

We now consider a procedural version of Max_Array which updates its first argument instead of returning a new array. We want to prove that Max_Array sets the maximum values of both its arguments into each index in its first argument.

```
Listing 51: array_util.ads
```

```
package Array_Util is
1
2
      type Nat Array is array (Positive range <>) of Natural;
3
4
      procedure Max Array (A : in out Nat Array; B : Nat Array) with
5
        Pre => A'First = B'First and A'Last = B'Last,
6
        Post => (for all K in A'Range =>
7
                   A(K) = Natural'Max (A'Old (K), B(K)));
8
9
   end Array Util;
10
```

Listing 52: array util.adb

```
package body Array Util is
1
2
      procedure Max_Array (A : in out Nat_Array; B : Nat_Array) is
3
      begin
4
          for I in A'Range loop
5
             pragma Loop_Invariant
6
               (for all K in A'First .. I - 1 =>
7
                  A (K) = Natural'Max (A'Loop_Entry (K), B (K)));
8
             pragma Loop Invariant
9
               (for all K in I .. A'Last => A (K) = A'Loop_Entry (K));
10
             if A (I) <= B (I) then</pre>
11
                A(I) := B(I);
12
             end if;
13
          end loop;
14
15
      end Max_Array;
16
   end Array Util;
17
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_09
MD5: 2de4bdd9c59d7d1eccb6259067ffdcf3

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
array_util.adb:7:13: info: loop invariant preservation proved
array_util.adb:7:13: info: loop invariant initialization proved
array_util.adb:7:39: info: overflow check proved
array_util.adb:8:18: info: index check proved
array_util.adb:8:50: info: index check proved
array util.adb:8:57: info: index check proved
array_util.adb:10:13: info: loop invariant initialization proved
array_util.adb:10:13: info: loop invariant preservation proved
array util.adb:10:44: info: index check proved
array_util.adb:10:63: info: index check proved
array_util.adb:11:25: info: index check proved
array_util.adb:12:25: info: index check proved
array_util.ads:7:14: info: postcondition proved
array_util.ads:8:20: info: index check proved
```

```
array_util.ads:8:45: info: index check proved
array_util.ads:8:52: info: index check proved
```

Everything is proved. The first loop invariant states that the values of A before the loop index contains the maximum values of the arguments of Max_Array (referring to the input value of A with A'Loop_Entry). The second loop invariant states that the values of A beyond and including the loop index are the same as they were on entry. This is the frame condition of the loop.

5.4.10 Example #10

Let's remove the frame condition from the previous example.

Listing 53: array_util.ads

```
package Array Util is
1
2
      type Nat Array is array (Positive range <>) of Natural;
3
4
      procedure Max Array (A : in out Nat Array; B : Nat Array) with
5
        Pre => A'First = B'First and A'Last = B'Last,
6
        Post => (for all K in A'Range =>
7
                    A(K) = Natural'Max (A'Old (K), B(K)));
8
9
   end Array Util;
10
```

Listing 54: array_util.adb

```
package body Array Util is
1
2
      procedure Max Array (A : in out Nat Array; B : Nat Array) is
3
      begin
4
          for I in A'Range loop
5
             pragma Loop Invariant
6
               (for all K in A'First .. I - 1 =>
7
                  A (K) = Natural'Max (A'Loop_Entry (K), B (K)));
8
             if A (I) <= B (I) then
9
                A (I) := B (I);
10
             end if;
11
         end loop:
12
      end Max_Array;
13
14
   end Array_Util;
15
```

Code block metadata

Project: Courses.Intro_To_Spark.Proof_of_Functional_Correctness.Example_10
MD5: 8bdc8432cbb3f26f58f63457408c7172

Prover output

```
Phase 1 of 2: generation of Global contracts ...
Phase 2 of 2: flow analysis and proof ...
array_util.adb:7:13: info: loop invariant initialization proved
array_util.adb:7:13: info: loop invariant preservation proved
array_util.adb:7:39: info: overflow check proved
array_util.adb:8:18: info: index check proved
array_util.adb:8:50: info: index check proved
```

array_util.adb:8:57: info: index check proved array_util.adb:9:25: info: index check proved array_util.adb:10:25: info: index check proved array_util.ads:7:14: info: postcondition proved array_util.ads:8:20: info: index check proved array_util.ads:8:45: info: index check proved array_util.ads:8:52: info: index check proved

Everything is still proved. GNATprove internally generates the frame condition for the loop, so it's sufficient here to state that A before the loop index contains the maximum values of the arguments of Max_Array.